


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

NOTES:

1. SEE CURRENT CATALOG FOR VARIOUS APPLICATIONS AND TO INDICATE PACKAGE QUANTITY.
2. PATCH CORDS CAN BE USED WITH GIGA-PUNCH FOUR-PAIR CONNECTING BLOCKS.
3. THE GIGA-PUNCH PATCH CORD IS POLARIZED TO PREVENT REVERSE INSTALLATION TO THE CONNECTOR BLOCK, INCORPORATES A CABLE JACKET RETENTION FEATURE WHICH MINIMIZES WIRE UNTWISTING, AND HAS AN INTEGRAL STRAIN RELIEF.
4. PATCH CORDS CONSTRUCTED USING UL OR ETL VERIFIED CABLE.
5. MATERIAL: CONNECTOR: POLYCARBONATE  
CABLE: CAT6, 24 AWG STRANDED-TIN/COPPER  
JACKET: PVC  
JACKET COLOR: WHITE



PANDUIT P/N	LENGTH (MIN) FEET (mm)	WEIGHT LB/10 PCS (530 g/10 PCS)
GPPC41G3Y	3 FT. (914mm)	1.17
GPPC41G5Y	5 FT. (1524mm)	1.70
GPPC41G7Y	7 FT. (2134mm)	2.17
GPPC41G9Y	9 FT. (2743mm)	2.70
GPPC41G14Y	14 FT. (4267mm)	4.03
GPPC41G20Y	20 FT. (6096mm)	5.82
GPPC41G1MY	1 METER	1.97
GPPC41G2MY	2 METERS	3.77
GPPC41G3MY	3 METERS	5.41
GPPC41G5MY	5 METERS	8.93

CAD FILENAME/LAYERS M02479NT\_DC358\_00A.PRT

**PANDUIT** CORP. TINLEY PARK, ILLINOIS  
GIGA-PUNCH(TM) PATCH CORDS (GPPC41G\*\*Y) CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:  
(.XX) ± .031(.8) ANGLES ±  
(.XXX) ± .010(.3)  
UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY: NER	MAT'L: NONE	SCALE: NONE
DATE: 3-21-06	SEE NOTES	DWG NO. 02479-358
CHK'D: OTH		SIZE: A
REV: R	DATE: 3-21-06	NER
BY: CHK	DESCRIPTION: RELEASED FOR PRODUCTION	02479-358
ECN: R	CUST: SUP	OTH