В. Copper Systems

C. **Fiber Optic Systems**

D. Power over Ethernet

E. Zone Cabling

Wireless

G. **Outlets**

Н. Media Distribution

Ι. **Physical** Infrastructure Management

J. Overhead & Underfloor Routing

Surface Raceway

L. Cabinets, Racks & Cable Managemen^a

Grounding 8 Bonding

N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

> 0. Index

Opti-Core® Singlemode 9/125µm (OS1/OS2) Fiber Optic Patch Cords and Pigtails

- Available in riser (OFNR) or plenum (OFNP) flame ratings; part numbers listed are for OFNR (F9E10-10M1Y)
- For OFNP, place a P after the X in the part number and drop the Y (F9PE10-10M1)
- Pass all TIA/EIA-568-B.3 performance requirements
- · LC and SC connector housing and boot colors follow TIA/EIA-568-C.3 suggested color identification scheme
- 100% factory inspected end face geometry in compliance with Telcordia GR-326-CORE, Issue 3

Part Number

F9E10-10M1Y

F9F10-10M1Y

F9B10-NM1Y

- Typical insertion loss per connection: 0.25dB
- UPC polished (55dB minimum return loss)
- Factory terminated and 100% tested for insertion loss and return loss
- Insertion loss and return loss data recorded for every singlemode patch cord
- · Lifetime traceability of test data to a Q.C. number on each patch cord

Std. Std.

Pkg. Ctn.

Qty. Qty.

10

10

10

10

Length

 $(m)^{\wedge}$


 Highest quality flame retardant fiber optic cable with tight-buffered coating on each optical fiber




F9E10-10M*Y



F9F10-10M*V



F9B10-NM*Y



F9D3-3M*Y




F9S3-3M*Y




F9B3-NM*Y



F9D2-2M*Y



F9S2-2M*Y



	end) – 9/125µm.					
SC to SC - OS1	/OS2 Singlemode Duplex Patch Cords – 3mm Jackete	d Cable				
F9D3-3M1Y	SC to SC singlemode duplex patch cord, 3mm jacketed cable (two SC connectors on each end) $-$ 9/125 μ m.	1	1	10		
SC to SC – OS1/OS2 Singlemode Simplex Patch Cords – 3mm Jacketed Cable						
F9S3-3M1Y	SC to SC singlemode simplex patch cord, 3mm jacketed cable (one SC connector on each end) – 9/125µm.	1	1	10		
SC to Pigtail – OS1/OS2 Singlemode Simplex Pigtails – 900µm Buffered Fiber						
F9B3-NM1Y	SC to pigtail singlemode simplex pigtail, 900µm buffered fiber (one SC connector on one end and open on the other end) – 9/125µm.	1	1	10		
ST to ST – OS1/OS2 Singlemode Duplex Patch Cords – 3mm Jacketed Cable						
F9D2-2M1Y	ST to ST singlemode duplex patch cord, 3mm jacketed cable (two ST connectors on each end) – 9/125µm.	1	1	10		
ST to ST – OS1/OS2 Singlemode Simplex Patch Cords – 3mm Jacketed Cable						
F9S2-2M1Y	ST to ST singlemode simplex patch cord, 3mm jacketed cable (one ST connector on each end) – 9/125µm.	1	1	10		
ST to Pigtail – C	OS1/OS2 Singlemode Simplex Pigtails – 900µm Buffere	ed Fiber				
F9B2-NM1Y	ST to pigtail singlemode simplex pigtail, 900µm buffered fiber (one ST connector on one end and open on the other end) – 9/125µm.	1	1	10		
FJ® Plug to FJ® Plug – OS1/OS2 Singlemode Duplex Patch Cords – 3mm Jacketed Cable						
F9D6P-6PM1Y	FJ® Plug to FJ® Plug singlemode duplex patch cord, 3mm jacketed cable (one FJ® Plug on each end) – 9/125µm.	1	1	10		

Part Description

LC to LC - OS1/OS2 Singlemode Duplex Patch Cords - 1.6mm Jacketed Cable

LC to LC singlemode duplex patch cord, 1.6mm jacketed

cable (one duplex LC connector on each end) - 9/125µm.

LC to LC singlemode simplex patch cord, 1.6mm jacketed

LC to pigtail singlemode simplex pigtail, 900µm buffered fiber

LC to LC - OS1/OS2 Singlemode Simplex Patch Cords - 1.6mm Jacketed Cable

cable (one LC connector on each end) - 9/125µm.

LC to Pigtail - OS1/OS2 Singlemode Simplex Pigtails - 900µm Buffered Fiber

(one LC connector on one end and open on the other

^Additional lengths and availability: Patch cords are available in 1 - 10 meter lengths in 1 meter increments, and 15, 20, 25 and 30 meter lengths. Pigtails are available in 1, 2, and 3 meter lengths. To order lengths other than 1 meter, replace the 1 after the M (F9D3-3M1Y) with the desired length (F9D3-3M2Y for 2 meter length). The above lengths are stock items. For other lengths, contact Customer Service for actual lead time.

FJ® Jack Module to Pigtail – OS1/OS2 Singlemode Duplex Pigtails – 3mm Jacketed Cable

jacketed cable (one FJ® Jack Module on one end and open on

FJ® Jack Module to pigtail singlemode duplex pigtail, 3mm




the other end) $-9/125\mu m$.

F9D6J-NM1Y


Opti-Core® Singlemode 9/125µm (OS1/OS2) Fiber Optic Patch Cords and Pigtails (continued)

10.00			
	_	- 4	
		_	
4	1	-411	=000


F9B6J-NM*Y



F9E3-10M*Y




F9F3-10M*Y



F9D2-3M*Y



F9S2-3M*Y



F9E6P-10M*Y



F9D6P-3M*Y

Part Number	Part Description	Length (m)^	Std. Pkg. Qty.			
FJ® Jack Module to Pigtail – OS1/OS2 Singlemode Duplex Pigtails – 900µm Buffered Fiber						
F9B6J-NM1Y	FJ® Jack Module to pigtail singlemode duplex pigtail, 900μm buffered fiber (one FJ® Jack Module on one end and open on the other end) – 9/125μm.		1	10		
SC to LC – OS1/OS2 Singlemode Duplex Patch Cords – 1.6mm Jacketed Cable						
F9E3-10M1Y	SC to LC singlemode duplex patch cord, 1.6mm jacketed cable (two SC connectors on one end and one duplex LC connector on the other end) – 9/125µm.	1	1	10		
SC to LC – OS1/OS2 Singlemode Simplex Patch Cords – 1.6mm Jacketed Cable						
F9F3-10M1Y	SC to LC singlemode simplex patch cord, 1.6mm jacketed cable (one SC connector on one end and one LC connector on the other end) – 9/125µm.	1	1	10		
ST to SC – OS1/OS2 Singlemode Duplex Patch Cords – 3mm Jacketed Cable						
F9D2-3M1Y	ST to SC singlemode duplex patch cord, 3mm jacketed cable (two ST connectors on one end and two SC connectors on the other end) – 9/125µm.	1	1	10		
ST to SC – OS1/OS2 Singlemode Simplex Patch Cord – 3mm Jacketed Cable						
F9S2-3M1Y	ST to SC singlemode simplex patch cord, 3mm jacketed cable (one ST connector on one end and one SC connector on the other end) – 9/125µm.	1	1	10		
FJ® Plug to LC -	- OS1/OS2 Singlemode Duplex Patch Cords - 1.6mm	Jacketed	l Cab	le		
F9E6P-10M1Y	FJ® Plug to LC singlemode duplex patch cord, 1.6mm jacketed cable (one FJ® Plug on one end and one duplex LC connector on the other end) – 9/125μm.	1	1	10		
FJ® Plug to SC	- OS1/OS2 Singlemode Duplex Patch Cords – 3mm Ja	cketed (Cable			
F9D6P-3M1Y	FJ® Plug to SC singlemode duplex patch cord, 3mm jacketed cable (one FJ® Plug on one end and two SC connectors on the other end) – 9/125μm.	1	1	10		

^Additional lengths and availability: Patch cords are available in 1 - 10 meter lengths in 1 meter increments, and 15, 20, 25 and 30 meter lengths. Pigtails are available in 1, 2, and 3 meter lengths. To order lengths other than 1 meter, replace the 1 after the M (F9D3-3M1Y) with the desired length (F9D3-3M2Y for 2 meter length). The above lengths are stock items. For other lengths, contact Customer Service for actual lead time.

Copper Systems

Fiber Optic Systems

D. Power over **Ethernet**

E. Zone Cabling

Wireless

G. Outlets

Media Distribution

Ι. Physical Infrastructure Management

J. Overhead & Underfloor Routing

> Surface Raceway

Cabinets, Racks & Cable Management

Grounding & Bonding

Industrial

Labeling & Identification

Cable Management Accessories

> Q. Index

B. Copper Systems

C. Fiber Optic Systems

D. Power over Ethernet

E. Zone Cabling

F. Wireless

> G. Outlets

H. Media Distribution

I. Physical Infrastructure Management

J. Overhead & Underfloor Routing

K. Surface Raceway

L. Cabinets, Racks & Cable Management

M. Grounding & Bonding

N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

> Q. Index

Cable Self-Laminating Labels for Opti-Core® Singlemode 9/125µm (OS1/OS2) Fiber Optic Patch Cords and Pigtails



Suggested Label Solutions for TIA/EIA-606-A Compliance					
Patch Cord Part Number	Laser/Ink Jet Desktop Printer Label	TDP43ME Thermal Transfer Desktop Printer Label	PanTher™ LS8E Hand-Held Printer Label	Cougar™ LS9 Hand-Held Printer Label	
All F9F parts	S100X160YAJ and NWSLC-2Y‡	S100X150VATY and NWSLC-2Y‡	S100X160VAC and NWSLC-2Y‡	T100X000CBC-BK and NWSLC-2Y	
All F9S and F9E parts	S100X160YAJ and NWSLC-3Y‡	S100X150VATY and NWSLC-3Y‡	S100X160VAC and NWSLC-3Y‡	T100X000CBC-BK and NWSLC-3Y	
All F9D parts	S100X220YAJ and NWSLC-7Y‡	S100X225VATY and NWSLC-7Y‡	S100X220VAC and NWSLC-7Y‡	T100X000CBC-BK and NWSLC-7Y	

For complete labeling solutions and product information, reference charts on pages O.1 – O.18 of SA-NCCB51. ‡For complete information on fiber optic cable identification solutions, reference page C.92 of SA-NCCB51.