


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.
 MATERIAL: NYLON 6

MATERIAL: LOW DENSITY POLYETHYLENE

PART NO.	DIMENSIONS		WALL THICKNESS	WEIGHT lbs / 100 ft (g)
	A	B		
CLT25N-630	0.397 (10.081)	0.277 (7.041)	.0155" ± .0025"	0.81 (370.01)
CLT35N-630	0.500 (12.7)	0.350 (8.891)	.0200" ± .0050"	1.28 (580.01)
CLT38N-630	0.556 (14.12)	0.415 (10.541)	.0200" ± .0050"	1.47 (670.01)
CLT50N-630	0.670 (17.02)	0.505 (12.831)	.0200" ± .0050"	1.98 (900.01)
CLT62N-630	0.816 (20.73)	0.650 (16.511)	.0200" ± .0050"	2.39 (1085.01)
CLT75N-630	0.935 (23.75)	0.760 (19.301)	.0200" ± .0050"	2.75 (1250.01)
CLT100N-630	1.090 (27.69)	0.915 (23.241)	.0200" ± .0030"	3.70 (1680.01)
CLT125N-630	1.500 (38.10)	1.290 (32.771)	.0235" ± .0065"	5.77 (2620.01)
CLT150N-630	1.728 ± 0.085 (43.89 ± 2.16)	1.479 ± 0.085 (37.57 ± 2.16)	.0235" ± .0065"	6.16 (2800.01)
CLT188N-630	2.169 ± 0.085 (55.09 ± 2.16)	1.881 ± 0.085 (47.78 ± 2.16)	.0235" ± .0065"	11.20 (5088.00)

PART NO.	DIMENSIONS		WALL THICKNESS	WEIGHT lbs / 100 ft (g)
	A	B		
CLT25F-20	0.397 (10.081)	0.277 (7.041)	.0155" ± .0025"	0.75 (340.01)
CLT35F-20	0.500 (12.7)	0.350 (8.891)	.0200" ± .0050"	1.12 (510.01)
CLT38F-20	0.556 (14.121)	0.415 (10.541)	.0200" ± .0050"	1.38 (625.01)
CLT50F-20	0.670 (17.02)	0.505 (12.831)	.0200" ± .0050"	1.85 (840.01)
CLT62F-20	0.816 (20.73)	0.650 (16.511)	.0200" ± .0050"	2.29 (1040.01)
CLT75F-20	0.935 (23.75)	0.760 (19.301)	.0200" ± .0050"	2.64 (1200.01)
CLT100F-20	1.090 (27.69)	0.915 (23.241)	.0200" ± .0030"	3.52 (1600.01)
CLT125F-20	1.500 (38.10)	1.290 (32.771)	.0235" ± .0065"	6.03 (2740.01)
CLT150F-20	1.728 ± 0.085 (43.92 ± 2.16)	1.482 ± 0.085 (39.64 ± 2.16)	.0235" ± .0065"	7.39 (3360.01)
CLT188F-20	2.169 ± 0.085 (55.09 ± 2.16)	1.881 ± 0.085 (47.78 ± 2.16)	.0235" ± .0065"	9.10 (4127.3)



NOTES:

1. SEE PART NUMBER SUFFIX DESIGNATION ON CURRENT PRICE SHEET FOR PACKAGE SIZE AND PART COLOR.

2. FOR ROLL SIZES LARGER THAN 10 FEET, SPLICES MAY OCCUR.

REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP
8	6/22/11	LEF	JVL	B: ADD WALL THICKNESS FROM POLYETHYLENE TO NYLON 6 COLUMN C: CORRECTION TO (MM) CONVERSION ON B DIM. FOR CLT38F-20 FROM (10.39 TO 10.54)			B	RAMI
7	5/17/11	LEF	VJS	A: ADDED NOTE #2			7	RAMI
6	9/25/02	LEF	LEF	CHG MAT. TO LOW DENSITY POLYETHYLENE			6	RAMI
5	4/5/02	LEF	LEF	CHG DIM ON A & B DIM FOR CLT150F, CLT150F.			5	RAMI

DIMENSIONS IN PARENTHESES ARE IN METRIC UNITS
 CAD FILENAME/LAYERS G03597BN_DC_GB0222BP_08/00A

PANDUIT CORP. TINLEY PARK, ILLINOIS

CLT()N, CLT()F
 SLIT CORRUGATED TUBING

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:
 (.XX) ± (.XXX) ± 0.050 (1.27)
 ANGLES ±

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.

SCALE NONE
 DRAWING NO. GB0222BP
 DWG SIZE A

SEE ABOVE