


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT PART#	DESCRIPTION	WEIGHT*
CJE688TG**	8 POSITION, 8 WIRE UNIVERSAL MODULE. WHITE WIRE CAP IS COLOR CODED FOR T568A AND T568B WIRING SCHEMES.	1.73 LB/100 PCS (785g/100 PCS)

\*WEIGHT IS APPROXIMATE  
\*\*JACK COLOR SUFFIX



NOTES:

- JACK MODULE USES SEALANT(S) TO PROTECT CONTACTS FROM CORROSION AND CONTAMINATION.
- WHITE WIRE CAP DESIGNATES CATEGORY 6 PERFORMANCE.
- TO DESIGNATE A JACK COLOR, ADD A TWO LETTER COLOR SUFFIX. SEE CURRENT CATALOG FOR AVAILABLE PART NUMBER SUFFIXES TO INDICATE COLOR AND OR PACKAGE QUANTITY.
- MATERIAL:  
MODULE HOUSING - PBT  
WIRE CAP - PC  
STRAIN RELIEF CLIP - PC
- ALL TX6 CAT6 8 POSITION, 8 WIRE CONNECTOR MODULES ARE UNIVERSAL IN DESIGN. THEY ACCEPT SIX AND EIGHT POSITION MODULAR PLUGS WITHOUT DAMAGE.
- DIMENSIONS IN PARENTHESES ARE IN METRIC.



MODEL FILENAME	M02115AA/00	SIZE	A
DRAWING FILENAME	10M168BB_DC02/00B		

TX6 PLUS CORROSIVE RESISTANT  
JACK MODULE CUSTOMER DRAWING



<p>THIRD ANGLE PROJECTION</p>	<p>ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED.</p> <p>DIMENSIONAL TOLERANCES ARE: (.X) ± (.XXX) ±.010(.3) (.XX) ±.03(.8) ANGLES ±</p>	I.I. NUMBER
		PRODUCT SPEC/ PKG SPEC
		ASSY METHOD/ TEST METHOD
		SCALE
DRAWN BY BJN	REVIEW DRAWING NUMBERS	PART NO. CJE688TG**
DATE 2-23-10	MAT'L	DRAWING NO. 10M168BB-02
CHK'D KAA		

REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP	OTH
I	6-4-10	BJN	KAA	B. UPDATED TITLE BLOCK A. UPDATED WEIGHT	10M168BB-02		PBD		
R	2-23-10	BJN	KAA	RELEASED TO PRODUCTION	10M168BB-02		PBD		