## PHYSICAL INFRASTRUCTURE SYSTEMS



С.

Fiber

Optic

Systems

D.

Power

over

Ethernet

E.

Zone Cabling

F. Wireless

G. Outlets

A. System

**Overview** 

## PanZone® NEMA 4X/IP66 Rated Wireless Access Point Enclosures

- NEMA 4X and IP66 rating protects against corrosion, windblown dust and rain, splashing water and hose-directed water
- Universal design accommodates the most popular Wireless Access Points including Cisco Aironet^ 1200, 1230, 1240, 1250, and 1300 Series
- Fiberglass construction and aluminum mounting plate allows quick and easy access point installation
- UL508A Listed and approved
- · Include pre-configured mounting template

- · Provisions for padlocks to protect against tampering and theft
- Optional NEMA 4X rated fittings available in various sizes
- Optional NEMA 4X drain and vent kit
- Connectivity accessory kit (included): 2-position outlet box, Mini-Com® TX6™ PLUS Jack Module, TX6™ PLUS Patch Cord, silicone sealant and grounding cable

Std. Pka.

· Shielded connectivity accessory kit also available

	2
	*





J. Overhead & Underfloor Routing

K. Surface Raceway

L. Cabinets, Racks & Cable Management

Μ. Grounding & Bonding

N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

Q.
Index

	<b>P</b> 21	ł.
	PZNWE12	
_		



PZNWE14

Part Number	Part Description	Qty.
PanZone <sup>®</sup> NE	MA 4X/IP66 Rated Wireless Access Point Enclosures	
PZNWE12	Wireless enclosure designed for Power over Ethernet applications. Includes UTP connectivity kit. External dimensions: 13.56"H x 13.47"W x 6.56"D (344.4mm x 342.1mm x 166.6mm). Internal dimensions: 11.70"H x 11.70"W x 6.29"D (297.2mm x 297.2mm x 159.8mm).	1
PZNWE12S	Wireless enclosure designed for Power over Ethernet applications. Includes shielded connectivity kit. External dimensions: 13.56"H x 13.47"W x 6.56"D (344.4mm x 342.1mm x 166.6mm). Internal dimensions: 11.70"H x 11.70"W x 6.29"D (297.2mm x 297.2mm x 159.8mm).	1
PZNWE14	Wireless enclosure designed for traditional AC power applications. Includes UTP connectivity kit. External dimensions: 15.50"H x 13.50"W x 6.25"D (393.7mm x 342.9mm x 158.8mm). Internal dimensions: 13.53"H x 11.55"W x 5.94"D (343.7mm x 293.4mm x 150.9mm).	1
PZNWE14S	Wireless enclosure designed for traditional AC power applications. Includes shielded connectivity kit. External dimensions: 15.50"H x 13.50"W x 6.25"D (393.7mm x 342.9mm x 158.8mm). Internal dimensions: 13.53"H x 11.55"W x 5.94"D (343.7mm x 293.4mm x 150.9mm).	1

## **NEMA 4X Rated Fittings and Accessories**

PZNF1	NEMA 4X rated compression fitting, ideal for cable diameters of .115" to .250" (2.82mm to 6.35mm).	1	
PZNF2	NEMA 4X rated compression fitting, ideal for cable diameters of .230" to .395" (5.84mm to 10.03mm).	1	
PZNF3	NEMA 4X rated compression fitting, ideal for cable diameters of .170" to .450" (4.32mm to 11.43).	1	
PZNDVK	NEMA 4X drain and vent kit.	1	

^Cisco and Aironet are registered trademarks of Cisco Systems, Inc.