

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

HSTT 12 - 48 0 2

COLOR  
 BLANK = BLACK 5 = GREEN  
 1 = BROWN 6 = BLUE  
 2 = RED 10 = WHITE  
 3 = ORANGE 45 = YELLOW/GREEN  
 4 = YELLOW C = CLEAR

QUANTITY PER CARTON (48 IN ONLY)  
 0 = 25pcs.  
 5 = 5pcs.  
 2 = 2pcs.

LENGTH IN"  
 INCHES FEET:  
 .5 M=1000  
 1 D=500  
 48 T=200  
 C=100  
 L=50  
 Q=25

TUBING SIZE - EXPANDED I.D.

TT = THIN WALL  
 TTV = THIN WALL VW-1 RATED



NOTES:

- SHRINK RATIO: 2:1
- MATERIAL: CROSSLINKED POLYOLEFIN
- "ALL WARRANTIES, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED. (USER IS RESPONSIBLE TO DETERMINE SUITABILITY OF PRODUCT FOR INTENDED USE.)"
- REELS OF PRODUCT ARE ALLOWED TO HAVE SPLICES.



|                 |   |   |   |   |   |   |
|-----------------|---|---|---|---|---|---|
| PACK CODE       | M | D | T | C | L | Q |
| ALLOWED SPLICES | 4 | 3 | 2 | 1 | 1 | 0 |

| PANDUIT PART NUMBER | Min. Exp. I.D In. (mm) | Max. Rec. I.D In. (mm) | RECOVERED WALL In. (mm) |
|---------------------|------------------------|------------------------|-------------------------|
| HSTT05              | .046 (1.2)             | .023 (.6)              | .016±.003 (.406±.076)   |
| HSTT06              | .063 (1.6)             | .031 (.8)              | .017±.003 (.432±.076)   |
| HSTT09              | .093 (2.4)             | .046 (1.2)             | .020±.003 (.508±.076)   |
| HSTT12              | .125 (3.2)             | .062 (1.6)             | .020±.003 (.508±.076)   |
| HSTT19              | .187 (4.8)             | .093 (2.4)             | .020±.003 (.508±.076)   |
| HSTT25              | .250 (6.4)             | .125 (3.2)             | .025±.003 (.635±.076)   |
| HSTT38              | .375 (9.5)             | .187 (4.8)             | .025±.003 (.635±.076)   |
| HSTT50              | .500 (12.7)            | .250 (6.4)             | .025±.003 (.635±.076)   |
| HSTT75              | .750 (19.1)            | .375 (9.5)             | .030±.003 (.762±.076)   |
| HSTT100             | 1.000 (25.4)           | .500 (12.7)            | .035±.005 (.889±.127)   |
| HSTT150             | 1.500 (38.1)           | .750 (19.1)            | .040±.006 (1.016±.152)  |
| HSTT200             | 2.000 (50.8)           | 1.000 (25.4)           | .045±.007 (1.143±.178)  |
| HSTT300             | 3.000 (76.2)           | 1.500 (38.1)           | .050±.008 (1.270±.203)  |
| HSTT400             | 4.000 (101.6)          | 2.000 (50.8)           | .055±.009 (1.397±.229)  |



| REV | DATE    | BY  | CHK | DESCRIPTION   | ECN      | R | CUST | SUP |
|-----|---------|-----|-----|---|----------|---|------|-----|
| 3   | 5/15/13 | LEF | VJS | ADDED NOTE #4 ALLOWED SPLICES PER REEL LENGTH                             | GB0239KH | 3 | RAMI |     |
| 2   | 2/21/12 | LEF |     | ADDED "CUSTOMER DRAWING" TO TITLE BLK REMOVED ALL TOLERANCES IN TITLE BLK | GB0239KH | 2 | RAMI |     |
| 1   | 10/5/11 | LEF |     | ADD COLORS 1 & 3 CHANGE METRIC (19.0 TO 19.1)                             | GB0239KH | 1 | RAMI |     |

DIMENSIONS IN BRACKETS ARE METRIC [mm]

CAD FILENAME/LAYERS G03597HN\_DC\_G00239KH\_PB\_HSTT\_03

**PANDUIT** CORP. TINLEY PARK, ILLINOIS

HSTT THIN WALL HEAT SHRINKABLE TUBING CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:  
 (.X) \_\_\_\_\_ (.XXX) \_\_\_\_\_  
 (.XX) \_\_\_\_\_ ANGLES \_\_\_\_\_

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY LGRAVITT MAT'L: SEE NOTES

DATE 5/12/03

CHK'D

SCALE NONE

DRAWING NO. GB0239KH DWG SIZE A