



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



1.44" [37] CT-2525CH, CT-2550CH & CT-2500CH (WITH LOCATOR)

1.25" [32] CT-2570CH (WITHOUT LOCATOR)



CT-2525CH
SHOWN ABOVE

NOTES, UNLESS OTHERWISE SPECIFIED:

These crimping heads are used with Panduit CT-2500 and CT-2500/E Battery Operated Crimping Tools.

Weight 1.74 lbs. (0,79 kg)

Dimensions: 5-1/16" L x 2-3/4" H x 1-7/16" W (with Locator)
[129 L x 70 H x 37 W] mm

CT-2525CH or CD-525	Crimping head or die insert for installing the following Panduit products: #26 – #22 AWG (0,14 – 0,5 mm ²) insulated terminals and splices, #22 – #10 AWG (0,5 – 6,0mm ²) fully insulated disconnects, insulated parallel splices; and specific #22 – #14 AWG (0,5 – 2,5mm ²) barrel insulated disconnects.
------------------------	---

CT-2550CH or CD-550	<p>Crimping head or die insert for installing the following Panduit products: #22 – #10 AWG (0,5 – 6,0mm²) insulated terminals and splices; and specific insulated disconnects. Reduced crimp effort advantage for #12 – #10 AWG (4,0 – 6,0mm²) terminations.</p>
------------------------	--

CT-2570CH or CD-570	Crimping head or die insert for installing most of the following Panduit products: #22 – #10 AWG (0,5 – 6,0mm ²) non-insulated terminals, disconnects; and specific non-insulated splices.
---------------------	---

CT-2500CH	Crimping head (frame only); to be used with crimping die inserts CD-525, CD-550 or CD-570 (<i>sold separately</i>).
-----------	---

The Crimping Head and/or Die Insert Installation Instructions can be found at www.panduit.com, search for CT-2525CH, CT-2550CH, CT-2570CH, CT-2500CH, CD-525, CD-550 or CD-570.

Dimensions in [brackets] are in millimeters.
All dimensions are for reference only.

F:\wrkgrp\rvusers\ENGR DOCS\CUSTOMER DRAWINGS\TP25387B01_03 CT-25XXCH CD.doc

										<div><div>PANDUIT</div><div>CORP. TINLEY PARK, ILLINOIS</div></div>			
										CD*CT-2525CH, CT-2550CH, CT-2570CH, CT-2500CH			
03	5-27-14	BLR	BJPU	ADD MM ² DIMS TO CT-2525CH / CT-2550CH	4752	---	ABJ			UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:		UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.	
02	1-28-14	BLR	BJPU	UPD BRANDING	4704	---	ABJ			(.x) ± --- (.xxx) ± --- (.xx) ± --- ANGLES ± ---			
01	4-04-08	BLR	BJPU	ADD CT-2500CH & DIE INSERTS	4290	---	JRWA			DRAWN BY: BLR	MATL: -----	SCALE NONE	
00	3-02-07	BLR	SRRE	RELEASED	4241	---	SZ			DATE: 3-02-07		DRAWING NO. TP25387B01	
REV	DATE	BY	CHK'D	DESCRIPTION	ECN	- R	CUST	SUP		CHK'D: SRRE		DWG B SIZE	