

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. TES:

1. VISIT OUR ON-LINE CATALOG AT
WWW.PANDUIT.COM FOR A CURRENT LIST
OF PRODUCTS APPLICABLE FOR USE
WITH THIS PART.

2. ACCESSORY COMPONENTS:
(2) #10-32 X 1/2" MOUNTING SCREWS
(2) #12-24 X 1/2" MOUNTING SCREWS

3. THE POWER STRIP SHALL HAVE THE FOLLOWING:
-TEN (10) - NEMA 5-20R OUTLETS
-ONE (1) 10-FOOT POWER CORD WITH NEMA L5-20P
20 AMP PLUG PANDUIT P/N WEIGHT 6.0 LBS/EACH CMRPSH20CMTL 2.7 Kg/EACH -ONE (1) 10-FOOT POWER CORD WITH NEMA L5-ZOP 20 AMP PLUG

4. SCROLLING POWER METER DISPLAYS POWER FACTOR THAT HELPS TO IDENTIFY IF A CIRCUIT IS WASTING ENERGY, WHICH CAN CAUSE SIGNIFICANT DAMAGE TO ELECTRONIC EQUIPMENT AND HIGHER ENERGY COSTS. ALSO DISPLAYED IS AMPS, VOLTS AND WATTS, THAT ASSISTS WITH POWER MANAGEMENT BY ALLOWING THE USER TO JUDGE THE REMAINING CAPACITY ON THE POWER STOLE REFORE ADDING A NEW DEVICE TO [44 POWER STRIP BEFORE ADDING A NEW DEVICE TO POWER METER 20 AMP CIRCUIT 5. DIMENSIONS IN PARENTHESES ARE METRIC (mm). - AMPS. BREAKER RESET VOLTS. WATTS. POWER ON LED & POWÉR FACTOR (SEE NOTE 4) FRONT VIEW POWER CORD 19.0 [483] 17.0 432 1.0 c-UL® LISTED 60950 4.5 [25] MODEL FILENAME 114 V10341DM/01.PRT TYP REF BACK VIEW CAD FILENAME/LAYERS V10341DM_DC/01A.PRT CORP. TINLEY PARK, ILLINOIS RU 19" HORIZONTAL POWER STRIP 20 AMP 125V (CMRPSH20CMTL) CUSTOMER DRAWING UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: UNLESS OTHERWISE SPECIFIED. |[METRIC - MILLIMETER] INCHES ANGLE X.X X.XX X.X ± 0.06 X. X.XX ± 0.03 X.X X.XXX ± 0.015 X.XX ALL DIMENSIONS ARE GIVEN ± 0.8 ± 0.4 IN INCHES, THIRD ANGLE PROJECTION. DRAWN BY SCALE MAT'L: NONE MRWA DATE DRAWING NO. COLD-ROLLED DWG OIAMRWAKE RELEASED TO PRODUCTION 3-25-11 V10341DM 3-25-11 STEEL CHK 'D V10341DM-DC KRKE DATE BY DESCRIPTION ECN - R SUP REV CHK CUST SIZE