

Thermomagnetic device circuit breaker - TMC 62C 06A - 0902218

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Thermomagnetic circuit breaker, two-pole, 6.0 A thermal trip. DIN rail mounted and UL 1077-recognized with optional auxiliary contact for either S or H remote signal. Protects wiring and equipment from overcurrent and short circuit faults.



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	6 pc
Weight per Piece (excluding packing)	273.1 g
Custom tariff number	85362010
Country of origin	Hungary

Technical data

Product type	Thermomagnetic device circuit breakers
Approval	CSA
	UL Recognized
	cUL Recognized
	cULus Recognized
Fuse type	circuit-breaker C
Mounting type	DIN rail: 35 mm
Nominal current I_N	6 A
Nominal voltage U_N	480 V AC
	240 V AC
	440 V AC
	125 V DC
Contact type	None
Number of positions	2

Thermomagnetic device circuit breaker - TMC 62C 06A - 0902218

Classifications

eCl@ss

eCl@ss 4.0	27141116
eCl@ss 4.1	27141116
eCl@ss 5.0	27141116
eCl@ss 5.1	27141116
eCl@ss 6.0	27141116
eCl@ss 7.0	27141116
eCl@ss 8.0	27141116

ETIM

ETIM 3.0	EC000899
ETIM 4.0	EC000899
ETIM 5.0	EC000899

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121411
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

Approvals

Approvals


Approvals

CSA / UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals


Approvals submitted

Approval details



Thermomagnetic device circuit breaker - TMC 62C 06A - 0902218

Approvals



Accessories

Accessories

Bridge

Wiring bridge - MPB 18/1- 3 - 2809212



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 3-pos.

Thermomagnetic device circuit breaker - TMC 6LOCKOUT - 0902467



Locking element for TMC 6 circuit breakers