

Socket - EMG 30-SD/US/15A - 5604253

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Rail-mounted single receptacle for mounting on 35 mm DIN rail per EN 60715. Housing color: black. Receptacle style: USA. Connection type: screw.

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	59.6 g
Custom tariff number	85369010
Country of origin	United States

Technical data

Dimensions

Width	30 mm
Height	75 mm
Depth	54 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
---------------------------------	------------------

General

Nominal voltage U_N	120 V AC
Nominal current I_N	15 A
For country-specific use in	USA
	Canada
	China
	Japan
	Mexico
	Peru
	Saudi Arabia
	Taiwan
	Thailand
	Phillipines
	Venezuela
	Vietnam
Color	black
Insulating material	PVC 94 V0

Socket - EMG 30-SD/US/15A - 5604253

Technical data

Connection data

Conductor cross section AWG min.	30
Conductor cross section AWG max.	12
Connection method	Screw connection

Classifications

eCl@ss

eCl@ss 4.0	27142305
eCl@ss 4.1	27142305
eCl@ss 5.0	27143412
eCl@ss 5.1	27143412
eCl@ss 6.0	27143412
eCl@ss 7.0	27440519
eCl@ss 8.0	27142305

ETIM

ETIM 3.0	EC001325
ETIM 4.0	EC001663
ETIM 5.0	EC001663

UNSPSC

UNSPSC 6.01	30211806
UNSPSC 7.0901	39121406
UNSPSC 11	39121406
UNSPSC 12.01	39121406
UNSPSC 13.2	39121406

Approvals

Approvals

Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

Socket - EMG 30-SD/US/15A - 5604253


Approvals

Approvals submitted

Approval details

UL Listed	
mm ² /AWG/kcmil	30-10
Nominal current I _N	15 A
Nominal voltage U _N	120 V

cUL Listed	
mm ² /AWG/kcmil	30-10
Nominal current I _N	15 A
Nominal voltage U _N	120 V

cULus Listed 
--