

## Thermomagnetic device circuit breaker - TMC 61C 40A - 0902137

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Thermomagnetic circuit breaker, one-pole, 40 A thermal trip. DIN rail mounted and UL 1077-recognized with optional auxiliary contact for either S or H remote signal. Protects wiring and equipment from overcurrent and short circuit faults.



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 12 pc    |
| Weight per Piece (excluding packing) | 148.7 g  |
| Custom tariff number                 | 85362010 |
| Country of origin                    | Hungary  |

### Technical data

|                       |  |
|-----------------------|--|
| Product type          | Thermomagnetic device circuit breakers |
| Approval              | CSA                                    |
|                       | UL Recognized                          |
|                       | cUL Recognized                         |
|                       | cULus Recognized                       |
| Fuse type             | circuit-breaker C                      |
| Mounting type         | DIN rail: 35 mm                        |
| Nominal current $I_N$ | 40 A                                   |
| Nominal voltage $U_N$ | 277 V AC                               |
|                       | 240 V AC                               |
|                       | 415 V AC                               |
|                       | 60 V DC                                |
| Contact type          | None                                   |
| Number of positions   | 1                                      |

# Thermomagnetic device circuit breaker - TMC 61C 40A - 0902137

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141116 |
| eCl@ss 4.1 | 27141116 |
| eCl@ss 5.0 | 27141116 |
| eCl@ss 5.1 | 27141116 |
| eCl@ss 6.0 | 27141116 |
| eCl@ss 7.0 | 27141116 |
| eCl@ss 8.0 | 27141116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000899 |
| ETIM 4.0 | EC000899 |
| ETIM 5.0 | EC000899 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211812 |
| UNSPSC 7.0901 | 39121411 |
| UNSPSC 11     | 39121411 |
| UNSPSC 12.01  | 39121411 |
| UNSPSC 13.2   | 39121411 |

## Approvals

### Approvals

---

#### Approvals

CSA / UL Recognized / cUL Recognized / cULus Recognized

---


#### Ex Approvals

---

#### Approvals submitted

---

#### Approval details

|   |
|---|
|  |
|---|

## Thermomagnetic device circuit breaker - TMC 61C 40A - 0902137

### Approvals



### Accessories

#### Accessories

#### Bridge

Wiring bridge - MPB 18/1- 3 - 2809212



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 3-pos.

---

Thermomagnetic device circuit breaker - TMC 6LOCKOUT - 0902467



Locking element for TMC 6 circuit breakers