


PCB terminal block - FFKDSA1/V1-5,08-8 BD:1-8QSO - 1711034

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, Nominal current: 15 A, Nom. voltage: 320 V, Pitch: 5.08 mm, Number of positions: 8, Connection method: Push-in spring connection, Mounting: Soldering, Color: green, The article can be aligned to create different nos. of positions!



Key Commercial Data

| | |
|------------------------|---|
| Packing unit | 50 STK |
| Minimum order quantity | 250 STK |
| GTIN |  4 055626 255835 |
| GTIN | 4055626255835 |
| Custom tariff number | 85369010 |
| Note | Made to Order (non-returnable) |

Technical data

Dimensions

| | |
|--------------------------|------------|
| Length | 12.7 mm |
| Pitch | 5.08 mm |
| Dimension a | 5.08 mm |
| Constructional height | 14 mm |
| Length of the solder pin | 3.4 mm |
| Pin dimensions | 0,5 x 1 mm |
| Hole diameter | 1.3 mm |

General

| | |
|--|-------|
| Insulating material group | I |
| Rated voltage (III/2) | 320 V |
| Nominal current I _N | 15 A |
| Flammability rating according to UL 94 | V0 |
| Number of positions | 8 |

Standards and Regulations

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|

PCB terminal block - FFKDSA1/V1-5,08-8 BD:1-8QSO - 1711034

Technical data

Environmental Product Compliance

| | |
|--|--|
| | No hazardous substances above threshold values |
|--|--|