



Cable Types		
	RG 58C/U (Black)	RG 142B/U (Tinted Brown)
Model	2256-C-XX	2256-X-XX
Capacitance pf/ft.	30.8	29.0
Nominal Impedance	50	50
Temp	+80°C	+200°C

MATERIALS:

Conn: 1st end – Type "N" male, See table above.

Finish: Body and Fitting, Tarnish resistant.

Center contact-Gold plated per requirements of MIL-C-39012.

Nominal Impedance: 50 Ohms.

Cable: See table above. Marking: "POMONA 2256-X-XX".

Conn: 2nd end – Same as first end.

RATINGS:

Operating Temperature: 2256-C-XX: +80°C (+176°F.) Max.

2256-X-XX: +200°C (+440°F.) Max.

Operating Voltage: 1000 VRMS Max.

ORDERING INFORMATION: Model 2256-X-XX

XX = Cable Lengths, Standard Length: 24" (610), 24" (610), 36" (914), 48" (1219) & 60" (1542).

Additional lengths can be quoted upon request.

Ordering Example: 2256-C-60 Indicates 60" in length

All dimensions are in inches. Tolerances (except noted): .xx = $\pm .02$ " (.51 mm), .xxx = $\pm .005$ " (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA