

6

5

4

3

2

1

MATERIAL SPECIFICATIONS:

Body & Housing: PA, UL-94V-0 rated, color black
Contacts: Brass, Gold plated

MECHANICAL SPECIFICATIONS:

Wire gauge: 0.25mm² / 24AWG
Cable Diameter: 3mm~ 5mm
Durability: 500 mating cycles min.

ELECTRICAL SPECIFICATIONS:

Rated current / voltage:
3 contact = 3A / 125V per contact
4 contact = 2.5A / 125V per contact
5 contact = 2A / 63V per contact
8 contact = 1A / 63V per contact

Contact resistance: 3 mohms max.

Rated impulse voltage:

3A & 2.5A = 1500V
2A & 1A = 800V


IEC/UL 61010-1 SPECIFICATIONS:

Material group: I, II
Overload category: II
Pollution degree: 2

ENVIRONMENTAL SPECIFICATIONS:

Degree of Protection: IP67
Operating Temperature: -25°C ~ +85°C

RoHS
COMPLIANT




ORDERING CODE:

PD-HEC3-MCC__-__
X1 X2

X1) No. of Contacts:
3, 4, 5 or 8

X2) Housing Color:
Black = B
Blue = BL
Red = R
Green = G

REVISIONS
CHANGE
DATE
APPR
CHK
CHK
APPR



CONTACT ARRANGEMENT

TOLERANCE UNLESS OTHERWISE SPECIFIED	
X	± 1
X.X	± 0.4
X.XX	± 0.13
DRAWN BY	PB
DATE:	7/31/15
CHECK BY	
DATE:	
APPR BY	
DATE:	

Power Dynamics, Inc.	
Phone: 973 560-0019 Whippany, New Jersey Fax: 973 560-0076	
PART: IP67 DUSTPROOF / WATERPROOF MALE SNAP LOCK CABLE CONNECTOR	
PD-HE3-MCC-X-X	
SHEET 1 of 1	
PART #:	
SIZE: A	ALL DIMENSIONS FOR REFERENCE ONLY DIMENSIONS ARE IN MILLIMETERS
SCALE: NTS	REV:

6

5

4

3

2

1