

MATERIAL SPECIFICATIONS:
 Housing: PA, UL-94V-0 rated, color black
 Contacts: CuZn, Silver plated



MECHANICAL SPECIFICATIONS:
 Contacts: 8 (4 Signal + 3 Power + PE)
 Durability: 1000 mating cycles min.
 Cable Diameter: 6 - 13mm / 9 - 17mm

ELECTRICAL SPECIFICATIONS:
 Rated current: 3A Signal max. / 25A Power max.
 Rated voltage: 60V Signal / 400V Power
 Contact resistance: 8mohms max.
 Rated impulse voltage: 5000V

IEC/UL 61010-1 SPECIFICATIONS:
 Material group: I, II
 Overload category: III
 Pollution degree: III

APPROVALS:  

ENVIRONMENTAL SPECIFICATIONS:
 Degree of Protection: IP68 / IPX9K
 Operating Temperature: -40°C ~ +85°C



**CONTACT ARRANGEMENT
 (MATING SIDE)**

POWER CONTACTS:
 1, 2, 3

SIGNAL CONTACTS:
 4, 5, 6, 7

NOTE:
 1. CONTACTS ORDERED SEPARATELY

MALE POWER CRIMP CONTACTS:

AWG	P/N
14	PD-HEC-MPC-14
16	PD-HEC-MPC-16

MALE SIGNAL CRIMP CONTACTS:

AWG	P/N
16	PD-HEC-MSC-16
18	PD-HEC-MSC-18
20	PD-HEC-MSC-20
26-22	PD-HEC-MSC-26

ACCESSORIES:

CRIMP TOOL FOR CONTACTS:
 P/N: PD-HEC-CT

SIGNAL CONTACT EXTRACTION TOOL:
 P/N: PD-HEC-SCET

POWER CONTACT EXTRACTION TOOL:
 P/N: PD-HEC-PCET

PROTECTION CAP:
 P/N: PD-HEC-MCC-CAP

TOLERANCE UNLESS OTHERWISE SPECIFIED	
X	± 1
X.X	± 0.4
X.XX	± 0.13

Power Dynamics, Inc.

Phone: 973 560-0019 Whippany, New Jersey Fax: 973 560-0076

**PART: HARSH ENVIRONMENT CONNECTOR
 MALE CABLE CONNECTOR**

DRAWN BY: PB	DATE: 7/28/14
CHECK BY:	DATE:
APPR BY:	DATE:

PD-HEC-MCC		SHEET 1 of 1
PART #: A	ALL DIMENSIONS FOR REFERENCE ONLY DIMENSIONS ARE IN MILLIMETERS	
SCALE: NTS		REV:

REV	DATE	CHANGE	CHK	CHK	APPR