

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

2N3668
2N3669
2N3670
2N4103

SILICON CONTROLLED RECTIFIER
16 AMPS
220 THRU 800 VOLTS
JEDEC TO-3 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N3668, 2N3669, 2N3670, 2N4103 types are hermetically sealed silicon SCR's designed for sensing circuit applications and control systems. Higher voltage devices and electrical selections are available on special order.

MAXIMUM RATINGS (T_C=25° unless otherwise noted)

	SYMBOL	2N3668	2N3669	2N3670	2N4103	UNIT
Peak Repetitive Off-State Voltage	V _{RRM}	100	200	400	600	V
Peak Repetitive Off-State Voltage	V _{DRM}	200	400	600	800	V
RMS On-State Current (T _C =90°C)	I _T (RMS)			16		A
Peak One Cycle Surge (60Hz, T _C =80°C)	I _{TSM}			200		A
Peak Gate Current	I _{GM}			4.0		A
Average Gate Power Dissipation	P _{G(AV)}			0.5		W
Operating and Storage Junction Temperature	T _J , T _{STG}		-40 TO +125			°C
Thermal Resistance	θ _{JC}			1.7		°C/W

ELECTRICAL CHARACTERISTICS (T_C=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
I _{RRM}	V _R =Rated V _{RRM} , T _C =100°C			1.0	mA
I _{DRM}	V _D =Rated V _{DRM} , T _C =100°C			2.0	mA
V _{TM}	I _T =25A			1.8	V
I _{GT}	V _D =7.0V	1.0		40	mA
V _{GT}	V _D =7.0V			2.0	V
I _H	R _G =1.0kΩ	0.5		50	mA
dv/dt	V _D =.67 x V _{DRM} , R _G =1.0kΩ, T _C =100°C	10	400		V/μs
t _{gd}	I _G =125mA, di _G /dt=1.25A/μs			500	ns
t _q	V _D =.67 x V _{DRM} , V _R =35V, I _T =10A, T _C =90°C			50	μs

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centalsemi.com

Worldwide Field Representatives:
www.centalsemi.com/wwreps

Worldwide Distributors:
www.centalsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centalsemi.com/terms