



Style A with leads



Style S with lugs



Style NV with lugs



Style C with leads



All Primaries 50/60 Hz.

| Sec. | STANCOR PART NUMBER | Primary Volts | Secondary | | Style | Insulation Test RMS Volts | Termination | | DIMENSIONS-INCHES | | | | Weight (lbs.) | Agency* Certification | |
|------|---------------------|---------------|-----------|------|-------|---------------------------|-------------|-------|-------------------|-------|------|--------|---------------|-----------------------|----|
| | | | | | | | | | Volts | Amps. | H | Case W | | | D |
| A | P-8629 | 117 | 2.5 | 1.0 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.38 | 2.00 | - | 0.4 | - |
| | P-4026 | 117 | 2.5 | 1.5 | A | 2500 | Leads | Leads | 1.75 | 2.88 | 1.63 | 2.38 | - | 0.7 | - |
| | P-6133 | 117 | 2.5 C.T. | 5.0 | S | 7500 | Leads | Leads | 2.75 | 3.13 | 2.25 | 2.81 | - | 1.5 | - |
| | P-6454 | 117/107 | 2.5 C.T. | 10.0 | S | 7500 | Leads | Leads | 3.25 | 3.63 | 1.88 | 3.13 | - | 2.5 | - |
| B | P-6467 | 117 | 5.0 C.T. | 3.0 | A | 2500 | Leads | Leads | 2.00 | 3.25 | 2.13 | 2.81 | - | 1.4 | - |
| | P-6135 | 117 | 5.0 C.T. | 10.0 | NV | 2500 | Leads | Leads | 3.13 | 2.50 | 2.50 | 2.00 | 2.06 | 3.0 | - |
| | P-8385 | 117 | 6.3 C.T. | 0.3 | A | 1500 | Leads | Leads | 1.25 | 2.13 | 1.38 | 1.75 | - | 0.3 | - |
| | P-6465 | 117 | 6.3 C.T. | 0.6 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.50 | 2.00 | - | 0.4 | UL |
| C | P-8705 | 230 | 6.3 C.T. | 0.6 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.50 | 2.00 | - | 0.4 | - |
| | P-8389 | 117 | 6.3 | 1.0 | A | 1500 | Leads | Leads | 1.75 | 2.88 | 1.63 | 2.38 | - | 0.6 | UL |
| | P-6134 | 117 | 6.3 C.T. | 1.2 | A | 3000 | Leads | Leads | 1.75 | 2.88 | 1.88 | 2.38 | - | 0.8 | UL |
| | P-8190 | 117 | 6.3 | 1.2 | A | 5000 | Leads | Leads | 2.00 | 3.25 | 1.88 | 2.81 | - | 1.0 | - |
| D | P-6466 | 117 | 6.3 C.T. | 3.0 | A | 2500 | Leads | Leads | 2.00 | 3.25 | 2.13 | 2.81 | - | 1.4 | - |
| | P-8648 | 117 | 6.3 C.T. | 4.0 | A | 1500 | Leads | Leads | 2.38 | 3.75 | 2.13 | 3.13 | - | 1.6 | - |
| | P-8649 | 117 | 6.3 C.T. | 5.0 | A | 1500 | Leads | Leads | 2.38 | 3.75 | 2.13 | 3.13 | - | 1.8 | - |
| | P-3064† | 117 | 6.3 C.T. | 6.0 | NV | 2500 | Lugs | Lugs | 3.13 | 2.50 | 2.38 | 2.00 | 2.00 | 2.4 | - |
| E | P-6456 | 117/107 | 6.3 C.T. | 6.0 | A | 2000 | Leads | Leads | 2.38 | 3.75 | 2.38 | 3.13 | - | 2.0 | - |
| | P-8651 | 117 | 6.3 C.T. | 8.0 | A | 1500 | Leads | Leads | 2.63 | 4.00 | 2.63 | 3.56 | - | 2.4 | - |
| | P-6464 | 117 | 6.3 C.T. | 10.0 | C | 2000 | Leads | Leads | 3.50 | 2.81 | 3.25 | 2.25 | 2.00 | 3.5 | - |
| | P-6308 | 117/107 | 6.3 C.T. | 10.0 | NV | 2500 | Leads | Leads | 3.50 | 2.81 | 2.63 | 2.25 | 2.00 | 3.4 | - |
| F | P-6309† | 117/107 | 6.3 C.T. | 20.0 | NV | 2500 | Leads | Leads | 4.69 | 3.75 | 3.50 | 3.00 | 2.47 | 6.7 | - |
| | P-5015 | 117 | 7.5 C.T. | 4.0 | NV | 2500 | Lugs | Lugs | 3.13 | 2.50 | 2.25 | 2.00 | 2.13 | 2.7 | - |
| | P-6138 | 117 | 7.5 C.T. | 8.0 | NV | 2500 | Leads | Leads | 3.88 | 3.13 | 3.38 | 2.50 | 2.22 | 4.7 | - |
| | P-8652 | 117 | 10.0 C.T. | 1.0 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.00 | 2.81 | - | 0.9 | - |
| G | P-8653 | 117 | 10.0 C.T. | 2.0 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.00 | 2.81 | - | 1.3 | - |
| | P-8380 | 117 | 10.0 C.T. | 3.0 | A | 1500 | Leads | Leads | 2.25 | 3.75 | 2.25 | 3.13 | - | 1.6 | - |
| | P-8654 | 117 | 10.0 C.T. | 4.0 | A | 1500 | Leads | Leads | 2.63 | 4.00 | 2.13 | 3.56 | - | 2.3 | - |
| | P-5016 | 117 | 10.0 C.T. | 4.0 | NV | 2500 | Lugs | Lugs | 3.44 | 2.81 | 2.50 | 2.25 | 2.00 | 3.3 | - |
| | P-6458 | 117/107 | 10.0 C.T. | 5.0 | NV | 2000 | Leads | Leads | 3.13 | 2.50 | 2.75 | 2.00 | 2.06 | 3.0 | - |

† Has Electrostatic Shield

* Agency Certification Note: UL Recognized (File E68100, Guide #XPTQ2)
UL Class 1

Single Secondary part numbers continued on page 48.
For outline drawings refer to page 62.



White-Rodgers • Emerson Electric Co.
9797 Reavis Road • St. Louis, MO 63123
(314) 865-8799 • Fax (314) 638-2400




STANCOR


POWER TRANSFORMERS

Single Secondary

Style A with leads



Style NV with lugs



Style C with leads




All Primaries 50/60 Hz.

| Sec. | STANCOR PART NUMBER | Primary Volts | Secondary Volts | Amps. | Style | Insulation Test RMS Volts | Termination | | DIMENSIONS-INCHES | | | | Weight (lbs.) | Agency* Certification | |
|------|---------------------|---------------|-----------------|-------|-------|---------------------------|-------------|-------|-------------------|------|------|--------|---------------|-----------------------|----|
| | | | | | | | | | Pri. | Sec. | H | Case W | | | D |
| | | | | | | | | | | | | MW | MD | | |
| A | P-8655 | 117 | 10.0 C.T. | 6.00 | NV | 1500 | Leads | Leads | 3.13 | 2.50 | 2.63 | 2.00 | 2.06 | 3.10 | - |
| | P-8656 | 117 | 10.0 C.T. | 8.00 | NV | 1500 | Leads | Leads | 3.50 | 2.81 | 3.00 | 2.25 | 2.28 | 4.10 | - |
| | P-6461 | 117 | 10.0 C.T. | 10.0 | C | 2000 | Leads | Leads | 3.88 | 3.18 | 3.88 | 2.50 | 2.75 | 5.00 | - |
| | P-8390 | 117 | 12.0 | 0.15 | A | 1500 | Leads | Leads | 1.25 | 2.13 | 1.25 | 1.75 | - | 0.25 | UL |
| B | P-8391 | 117 | 12.0 | 0.35 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.38 | 2.00 | - | 0.35 | - |
| | P-8392 | 117 | 12.0 | 0.70 | A | 1500 | Leads | Leads | 1.75 | 2.88 | 1.63 | 2.38 | - | 0.60 | UL |
| | P-8393 | 117 | 12.0 | 1.20 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 1.63 | 2.81 | - | 0.85 | - |
| | P-8657 | 117 | 12.0 | 2.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.13 | 2.81 | - | 1.30 | - |
| C | P-8658 | 117 | 12.0 | 4.00 | A | 1500 | Leads | Leads | 2.63 | 4.00 | 2.25 | 3.56 | - | 2.30 | - |
| | P-8659 | 117 | 12.0 | 6.00 | NV | 1500 | Leads | Leads | 3.50 | 2.88 | 2.63 | 2.25 | 2.13 | 3.40 | - |
| | P-8660 | 117 | 12.0 | 8.00 | NV | 1500 | Leads | Leads | 3.81 | 3.18 | 2.75 | 2.50 | 2.13 | 4.30 | - |
| | P-8384 | 117 | 12.6 C.T. | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 1.75 | 2.81 | - | 0.90 | - |
| D | P-8550 | 117 | 12.6 C.T. | 1.50 | A | 1500 | Leads | Leads | 2.00 | 3.31 | 2.00 | 2.81 | - | 1.30 | - |
| | P-8130 | 117 | 12.6 C.T. | 2.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.13 | 2.81 | - | 1.40 | UL |
| | P-8715 | 230 | 12.6 C.T. | 2.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.13 | 2.81 | - | 1.40 | - |
| | P-8358 | 117 | 12.6 C.T. | 3.00 | A | 1500 | Leads | Leads | 2.38 | 3.75 | 2.25 | 3.13 | - | 1.60 | - |
| E | P-8641 | 117 | 12.6 C.T. | 4.00 | A | 1500 | Leads | Leads | 2.62 | 4.00 | 2.38 | 3.56 | - | 2.30 | - |
| | P-8642 | 117 | 12.6 C.T. | 6.00 | C | 1500 | Leads | Leads | 3.88 | 3.13 | 3.38 | 2.50 | 2.22 | 3.80 | - |
| | P-8644 | 117 | 12.6 C.T. | 10.0 | C | 1500 | Leads | Leads | 4.25 | 3.44 | 3.38 | 2.75 | 2.69 | 6.30 | - |
| | P-8716 | 230 | 12.6 C.T. | 4.00 | A | 2500 | Leads | Leads | 2.63 | 4.00 | 2.38 | 3.56 | - | 2.30 | - |
| F | P-8577 | 115/230 | 14.0 C.T. | 0.25 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.50 | 2.00 | - | 0.30 | - |
| | P-8553 | 115 | 14.0 C.T. | 0.25 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.44 | 2.00 | - | 0.40 | - |
| | P-8555 | 115 | 14.0 C.T. | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 1.75 | 2.81 | - | 1.20 | - |
| | P-8556 | 115 | 14.0 C.T. | 2.00 | A | 1500 | Leads | Leads | 2.38 | 3.69 | 1.94 | 3.13 | - | 1.50 | - |
| G | P-8557 | 115 | 14.0 C.T. | 4.00 | NV | 1500 | Leads | Leads | 3.00 | 2.56 | 2.44 | 2.00 | 2.25 | 3.00 | - |
| | P-8558 | 115 | 14.0 C.T. | 6.00 | NV | 1500 | Leads | Leads | 3.50 | 2.81 | 2.88 | 2.25 | 2.38 | 4.00 | - |
| | P-8690 | 115 | 18.0 C.T. | 0.75 | A | 1500 | Leads | Leads | 2.00 | 3.31 | 2.00 | 2.81 | - | 1.30 | - |
| | P-8691 | 115 | 18.0 C.T. | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.31 | 2.13 | 2.81 | - | 1.50 | - |
| H | P-8692 | 115 | 18.0 C.T. | 1.50 | A | 1500 | Leads | Leads | 2.38 | 3.75 | 2.13 | 3.13 | - | 1.70 | - |
| | P-8693 | 115 | 18.0 C.T. | 2.00 | A | 1500 | Leads | Leads | 2.38 | 3.75 | 2.25 | 3.13 | - | 2.00 | - |
| | P-8500 | 115/230 | 20.0 C.T. | 0.05 | A | 2500 | Leads | Leads | 1.25 | 2.13 | 1.25 | 1.75 | - | 0.30 | - |
| | P-8504 | 115/230 | 20.0 C.T. | 0.25 | A | 2500 | Leads | Leads | 1.44 | 2.38 | 1.38 | 2.00 | - | 0.40 | - |
| I | P-8505 | 115/230 | 20.0 C.T. | 0.30 | A | 2500 | Leads | Leads | 1.44 | 2.38 | 1.38 | 2.00 | - | 0.60 | - |
| | P-8507 | 115/230 | 20.0 C.T. | 0.50 | A | 2500 | Leads | Leads | 1.75 | 2.88 | 1.63 | 2.38 | - | 0.80 | - |
| | P-8508 | 115/230 | 20.0 C.T. | 1.00 | A | 2500 | Leads | Leads | 2.00 | 3.25 | 2.25 | 2.81 | - | 1.40 | - |


* Agency Certification Note: UL Recognized (File E68100, Guide #XPT02)
UL Class 1

Single Secondary part numbers continued on page 49.
For outline drawings refer to page 62.


Style A with leads



Style NV with lugs



Style C with leads



All Primaries 50/60 Hz.

| Sec. | STANCOR PART NUMBER | Primary Volts | Secondary Volts | Amps. | Style | Insulation Test RMS Volts | Termination | | DIMENSIONS-INCHES | | | | | Weight (lbs.) | Agency* Certification |
|------|---------------------|---------------|-----------------|-------|-------|---------------------------|-------------|-------|-------------------|--------|------|----------|------|---------------|-----------------------|
| | | | | | | | Pri. | Sec. | H | Case W | D | Mounting | | | |
| | | | | | | | | | | | | MW | MD | | |
| A | P-8604 | 117 | 20.0 C.T. | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.13 | 2.81 | - | 1.40 | UL |
| | P-8559 | 115 | 20.0 C.T. | 2.00 | A | 1500 | Leads | Leads | 2.56 | 4.00 | 2.25 | 3.56 | - | 2.50 | - |
| | P-8560 | 115 | 20.0 C.T. | 4.00 | NV | 1500 | Leads | Leads | 3.50 | 2.81 | 3.06 | 2.25 | 2.06 | 4.00 | - |
| | P-8551 | 115 | 24.0 | 1.00 | A | 1500 | Leads | Leads | 1.94 | 3.25 | 2.13 | 2.81 | - | 1.40 | - |
| B | P-8694 | 115 | 24.0 | 2.00 | A | 1500 | Leads | Leads | 2.63 | 4.00 | 2.00 | 3.56 | - | 2.30 | - |
| | P-8394 | 117 | 24.0 C.T. | 0.085 | A | 1500 | Leads | Leads | 1.25 | 2.13 | 1.25 | 1.75 | - | 0.25 | - |
| | P-8720 | 230 | 24.0 C.T. | 0.085 | A | 1500 | Leads | Leads | 1.25 | 2.13 | 1.25 | 1.75 | - | 0.25 | - |
| | P-8395 | 117 | 24.0 C.T. | 0.20 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.38 | 2.00 | - | 0.35 | UL |
| C | P-8721 | 230 | 24.0 C.T. | 0.20 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.38 | 2.00 | - | 0.35 | - |
| | P-8578 | 115/230 | 24.0 C.T. | 0.20 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.50 | 2.00 | - | 0.30 | - |
| | P-8396 | 117 | 24.0 C.T. | 0.40 | A | 1500 | Leads | Leads | 1.75 | 2.88 | 1.63 | 2.38 | - | 0.60 | UL |
| | P-8722 | 230 | 24.0 C.T. | 0.40 | A | 1500 | Leads | Leads | 1.75 | 2.88 | 1.63 | 2.38 | - | 0.60 | - |
| D | P-8397 | 117 | 24.0 C.T. | 0.70 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 1.75 | 2.81 | - | 0.85 | UL |
| | P-8723 | 230 | 24.0 C.T. | 0.70 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 1.75 | 2.81 | - | 0.85 | - |
| | P-8661 | 117 | 24.0 C.T. | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.06 | 2.81 | - | 1.40 | UL |
| | P-8575 | 115/230 | 24.0 C.T. | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.06 | 2.81 | - | 1.30 | UL |
| E | P-8662 | 117 | 24.0 C.T. | 2.00 | A | 1500 | Leads | Leads | 2.62 | 4.00 | 2.38 | 3.56 | - | 2.30 | - |
| | P-8663 | 117 | 24.0 C.T. | 4.00 | NV | 1500 | Leads | Leads | 3.81 | 3.13 | 2.81 | 2.13 | 2.13 | 4.00 | UL |
| | P-8664 | 117 | 24.0 C.T. | 6.00 | NV | 1500 | Leads | Leads | 4.19 | 3.44 | 3.00 | 2.75 | 2.25 | 5.70 | - |
| | P-8665 | 117 | 24.0 C.T. | 8.00 | NV | 1500 | Leads | Leads | 4.19 | 3.44 | 3.38 | 2.75 | 2.75 | 7.30 | - |
| F | P-8695 | 115 | 24.0 C.T. | 10.0 | NV | 1500 | Leads | Leads | 4.31 | 3.44 | 3.50 | 2.75 | 3.13 | 8.00 | - |
| | P-8666 | 117 | 24.0 C.T. | 12.0 | NV | 1500 | Leads | Leads | 4.63 | 3.75 | 4.63 | 3.00 | 3.19 | 11.2 | UL |
| | P-6469 | 117 | 25.2 | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.13 | 2.81 | - | 1.40 | - |
| | P-8707 | 230 | 25.2 | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.13 | 2.81 | - | 1.40 | - |
| G | P-8180 | 117 | 25.2 C.T. | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.25 | 2.81 | - | 1.40 | - |
| | P-8357 | 117 | 25.2 C.T. | 2.00 | A | 1500 | Leads | Leads | 2.63 | 4.00 | 2.25 | 3.56 | - | 2.20 | UL |
| | P-8574 | 115/230 | 25.2 C.T. | 2.00 | A | 1500 | Leads | Leads | 2.63 | 4.00 | 2.25 | 3.56 | - | 2.20 | UL/CSA |
| | P-8388 | 117 | 25.2 C.T. | 2.80 | A | 1500 | Leads | Leads | 2.63 | 4.00 | 2.25 | 3.56 | - | 2.20 | - |
| H | P-8645 | 117 | 25.2 C.T. | 5.00 | C | 1500 | Leads | Leads | 4.25 | 3.44 | 3.88 | 2.75 | 2.69 | 6.00 | - |
| | P-8607† | 117 | 26.0 C.T. | 0.25 | A | 2500 | Leads | Leads | 1.75 | 2.88 | 1.75 | 2.38 | - | 0.70 | - |
| | P-8609 | 117 | 26.8 C.T. | 1.00 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.13 | 2.81 | - | 1.30 | - |
| | P-8600 | 117 | 28.0 C.T. | 0.085 | A | 1500 | Leads | Leads | 1.25 | 2.13 | 1.25 | 1.75 | - | 0.25 | - |
| I | P-8601 | 117 | 28.0 C.T. | 0.175 | A | 1500 | Leads | Leads | 1.38 | 2.38 | 1.50 | 2.00 | - | 0.35 | - |
| | P-8602 | 117 | 28.0 C.T. | 0.30 | A | 1500 | Leads | Leads | 1.63 | 2.88 | 1.63 | 2.38 | - | 0.60 | - |
| | P-8603 | 117 | 28.0 C.T. | 0.80 | A | 1500 | Leads | Leads | 2.00 | 3.25 | 2.13 | 2.81 | - | 1.00 | UL |

† Primary Tapped to Provide Secondary Voltages of 24.5 C.T., 27.5 C.T. or 29.0 C.T.

* Agency Certification Note: UL Recognized (File E68100, Guide #XPTQ2)
UL Class 1

Single Secondary part numbers continued on page 50.
For outline drawings refer to page 62.



White-Rodgers • Emerson Electric Co.
9797 Reavis Road • St. Louis, MO 63123
(314) 865-8799 • Fax (314) 638-2400



STANCOR 49