

Stancor® Low Boy™
Low Profile



All Dual Primaries are 115/230V 50/60Hz, 8 Pins

Sec.	STANCOR PART NUMBER	VA	Primary Winding	Rated Output						DIMENSIONS - INCHES						Weight (lbs.)	Agency* Certif.		
				AC/DC	Individual Volts	mA	Series Volts	mA	Parallel Volts	mA	H	W	L	MW	ML			A	B
A	LB-210	2.0	Dual	AC	-	-	10.0 C.T.	200	5.0	400	0.63	1.56	1.88	0.88	1.62	1.6	0.38	0.28	UL
	LB-310	3.0	Dual	AC	-	-	10.0 C.T.	300	5.0	600	0.63	1.56	1.88	0.88	1.62	1.6	0.38	0.28	UL
	LB-410	4.0	Dual	AC	-	-	10.0 C.T.	400	5.0	800	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-510	5.0	Dual	AC	-	-	10.0 C.T.	500	5.0	1000	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
B	LB-610	6.0	Dual	AC	-	-	10.0 C.T.	600	5.0	1200	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-1210	12.0	Dual	AC	-	-	10.0 C.T.	1200	5.0	2400	1.06	2.00	2.50	1.00	2.00	2.0	0.50	0.72	UL
	LB-412	4.0	Dual	AC	-	-	12.0 C.T.	333	6.0	667	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-512	5.0	Dual	AC	-	-	12.0 C.T.	417	6.0	833	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
C	LB-612	6.0	Dual	AC	-	-	12.6 C.T.	450	6.3	900	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-1212	12.0	Dual	AC	-	-	12.6 C.T.	900	6.3	1800	1.06	2.00	2.50	1.00	2.00	2.0	0.50	0.72	UL
	LB-215	2.0	Dual	AC	-	-	15.0 C.T.	150	7.5	300	0.63	1.56	1.88	0.88	1.62	1.6	0.38	0.28	UL
	LB-315	3.0	Dual	AC	-	-	15.0 C.T.	225	7.5	450	0.63	1.56	1.88	0.88	1.62	1.6	0.38	0.28	UL
D	LB-616	6.0	Dual	AC	-	-	16.0 C.T.	350	8.0	700	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-1216	12.0	Dual	AC	-	-	16.0 C.T.	700	8.0	1400	1.06	2.00	2.50	1.00	2.00	2.0	0.50	0.72	UL
	LB-420	4.0	Dual	AC	-	-	20.0 C.T.	200	10.0	400	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-520	5.0	Dual	AC	-	-	20.0 C.T.	250	10.0	500	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
E	LB-620	6.0	Dual	AC	-	-	20.0 C.T.	300	10.0	600	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-1220	12.0	Dual	AC	-	-	20.0 C.T.	600	10.0	1200	1.06	2.00	2.50	1.00	2.00	2.0	0.50	0.72	UL
	LB-424	4.0	Dual	AC	-	-	24.0 C.T.	167	12.0	333	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-524	5.0	Dual	AC	-	-	24.0 C.T.	208	12.0	417	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
F	LB-624	6.0	Dual	AC	-	-	24.0 C.T.	250	12.0	500	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-1224	12.0	Dual	AC	-	-	24.0 C.T.	500	12.0	1000	1.06	2.00	2.50	1.00	2.00	2.0	0.50	0.72	UL
	LB-634	6.0	Dual	AC	-	-	34.0 C.T.	170	17.0	340	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-1234	12.0	Dual	AC	-	-	34.0 C.T.	340	17.0	680	1.06	2.00	2.50	1.00	2.00	2.0	0.50	0.72	UL
G	LB-240	2.0	Dual	AC	-	-	40.0 C.T.	60	20.0	120	0.63	1.56	1.88	0.88	1.62	1.6	0.38	0.28	UL
	LB-640	6.0	Dual	AC	-	-	40.0 C.T.	150	20.0	300	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-1240	12.0	Dual	AC	-	-	40.0 C.T.	300	20.0	600	1.06	2.00	2.50	1.00	2.00	2.0	0.50	0.72	UL
	LB-256	2.0	Dual	AC	-	-	56.0 C.T.	45	28.0	90	0.63	1.56	1.88	0.88	1.62	1.6	0.38	0.28	UL
H	LB-656	6.0	Dual	AC	-	-	56.0 C.T.	100	28.0	200	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-1256	12.0	Dual	AC	-	-	56.0 C.T.	200	28.0	400	1.06	2.00	2.50	1.00	2.00	2.0	0.50	0.72	UL
	LB-288	2.0	Dual	AC	-	-	88.0 C.T.	28	44.0	56	0.63	1.56	1.88	0.88	1.62	1.6	0.38	0.28	UL
	LB-688	6.0	Dual	AC	-	-	88.0 C.T.	65	44.0	130	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
I	LB-1288	12.0	Dual	AC	-	-	88.0 C.T.	130	44.0	260	1.06	2.00	2.50	1.00	2.00	2.0	0.50	0.72	UL
	LB-2120	2.0	Dual	AC	-	-	120.0 C.T.	20	60.0	40	0.63	1.56	1.88	0.88	1.62	1.6	0.38	0.28	UL
	LB-4120	4.0	Dual	AC	-	-	120.0 C.T.	33	60.0	66	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-5120	5.0	Dual	AC	-	-	120.0 C.T.	41.7	60.0	83.3	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
J	LB-6120	6.0	Dual	AC	-	-	120.0 C.T.	50	60.0	100	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-12120	12.0	Dual	AC	-	-	120.0 C.T.	100	60.0	200	1.06	2.00	2.50	1.00	2.00	2.0	0.50	0.72	UL
	LB-2230	2.0	Dual	AC	-	-	230.0 C.T.	10	115.0	20	0.63	1.56	1.88	0.88	1.62	1.6	0.38	0.28	UL
	LB-6230	6.0	Dual	AC	-	-	230.0 C.T.	25	115.0	50	0.88	1.56	1.88	0.88	1.62	1.6	0.38	0.34	UL
	LB-12230	12.0	Dual	AC	-	-	230.0 C.T.	50	115.0	100	1.06	2.00	2.50	1.00	2.00	2.0	0.50	0.72	UL

* Agency Certification Note: UL Recognized (File E68100)

For schematic diagrams and outline drawing refer to page 28.



White-Rodgers • Emerson Electric Co.
9797 Reavis Road • St. Louis, MO 63123
(314) 865-8799 • Fax (314) 638-2400



STANCOR 27