


Control units Ø 16, Ø 22, and Ø 30 Emergency stop and Emergency switching off functions

Catalog

April 2015



How can you fit a 6000-page catalog in your pocket ?

Schneider Electric provides you with the complete set of industrial automation catalogs all on a handy USB key for PC or in an application for tablets



Digi-Cat, a handy USB key for PC



- > Convenient to carry
- > Always up-to-date
- > Environmentally friendly
- > Easy-to-share format



Contact your local representative to get your own Digi-Cat



e-Library, the app for tablets


If you have an iPad®:

- > Go to the App Store and search for e-Library
- > or scan the QR code



If you have an Android tablet:

- > Go to the Google Play Store™ and search for eLibrary
- > or scan the QR code



General contents

Ø 16, Ø 22, and Ø 30 Emergency stop and Emergency switching off functions

■ Presentation of Emergency stop and Emergency switching off functions

- Ø 16 XB6E and XB6 page 2
- Ø 22 XB4, XB5, and XB7 page 6
- Ø 30 9001K and SK page 26
- Magelis XBTGH page 28

■ References

- **Ø 16:** XB6E and XB6
 - XB6E monolithic page 3
 - XB6E accessories page 3
 - XB6 modular page 4
 - XB6 complete bodies and accessories page 5
- **Ø 22:** XB4
 - XB4 metal page 7
 - Body/contact assemblies and light blocks page 9
 - Circular yellow legends page 14
 - Accessories page 15
- **Ø 22:** XB5
 - XB5 plastic page 16
 - Body/contact assemblies and light blocks page 18
 - Circular yellow legends page 23
 - Accessories page 24
- **Ø 22:** XB7
 - XB7 plastic page 25
 - Accessories page 25
- **Ø 30:** 9001K and SK
 - 9001K metal and 9001SK plastic page 27
 - Accessories page 27
- Magelis XBTGH
 - Emergency stop function embedded on Magelis™ XBTGH
Advanced hand-held panel page 29
- **Product reference index** page 30

Control units Ø 16 plastic

Harmony XB6E monolithic and XB6 modular
Emergency stop pushbuttons

Presentation

The Ø 16 mm/0.630 in. Harmony XB6 and XB6E plastic range of Emergency stop pushbuttons is compact and thus suitable for installation on small machines and control panels. Their reduced diameter makes them suitable for applications where mounting space is less. Designed for control of machines and installations, these functions meet the requirements of majority of industrial applications.

- This range includes:
 - Ø 32 mm/1.260 in. Emergency stop trigger action pushbuttons for Start/Stop control of machines and installations, adjustment and parametering (contact functions),
 - Ø 32 mm/1.260 in. Illuminated Emergency stop pushbuttons for control and signaling (contact functions and signaling functions),
 - Fast connector sockets with push-in technology,
 - Various accessories.

Installation

- Harmony XB6 and XB6E products are both simple and quick to install:
 - Mounting by single installer (self-maintaining of the head in its cut-out)
 - Clip-together component system (head, body, contact blocks and LED)
- Type of connection:
 - For XB6 and XB6E: faston connector
 - For XB6E: fast connector socket

Environment

The performance features of these range meet the most demanding international standards and approvals:

- Degrees of protection:
 - For XB6 and XB6E: IP 65 conforming to standard IEC 60529
 - For XB6: NEMA type 4, 4X and 13 conforming to standard UL 50 and CSA C22-2 n° 94 (except key switches)
- International standards:
 - For XB6 and XB6E: EN/IEC 60947-5-5
 - For XB6: conform to standards EN/IEC 60204-1 and EN/ISO 13850, to Machinery Directive 98/37/EC and to standard EN/IEC 60947-5-5
- Product certifications:
 - For XB6E: UR, CCC,
 - For XB6: UL, CSA, CCC, GOST

Control units Ø 16 plastic

Harmony XB6E monolithic

Emergency stop pushbuttons and accessories




XB6ETI522P




XB6ETN521P

Emergency stop mushroom head pushbutton

Illuminated

Shape of head	Type of push	Type of contacts	Reference		Weight kg/lb
			With 12 V LED	With 24 V LED	
Circular, Ø 32 mm /1.260 in.	Trigger action, turn to release, pull to release	 N/C			0.027/0.060
			XB6ETI522P	XB6ETI523P	

Non-illuminated

Shape of head	Type of push	Type of contacts	Reference	Weight kg/lb
Circular, Ø 32 mm /1.260 in.	Trigger action, turn to release, pull to release	 N/C		0.027/0.060
			XB6ETN521P	

Accessories

Labels for Emergency stop mushroom head pushbutton

Shape	Color	Marking	Sold in lots of	Reference	Weight kg/lb
Circular	Yellow	EMERGENCY STOP	10	ZB6Y56	0.010/0.022

Control units Ø 16 plastic

Harmony XB6 modular

Emergency stop pushbuttons and circular legends



PF514166
XB6AS8349B



PF514167
XB6AS9349B



110770
ZB6AS834





110771
ZB6AS934





DG12,1438
ZB6Y7130



Emergency stop trigger action and mechanical latching pushbuttons

Shape of head	Type of reset	Type of contacts	Diameter of push mm/in.	Color	Reference	Weight kg/lb
		 N/O  N/C				

Complete units


	Turn to release	1	2	30/1.181	Red	XB6AS8349B (ZB6Z4B + ZB6AS834)	0.041/0.090
	Key release (key n° 200)	1	2	30/1.181	Red	XB6AS9349B (ZB6Z4B + ZB6AS934)	0.056/0.123

Heads only

	Turn to release			30/1.181	Red	ZB6AS834	0.035/0.077
	Key release (key n° 200)			30/1.181	Red	ZB6AS934	0.050/0.110

Circular legends for Emergency Stop mushroom head pushbuttons (yellow)


Diameter mm/in.	Marking on yellow background	Reference	Weight kg/lb
45/1.772	Without (1)	ZB6Y7001	0.001/0.002
	ARRET D'URGENCE (1)	ZB6Y7130	0.001/0.002
	EMERGENCY STOP (1)	ZB6Y7330	0.001/0.002
	PARADA EMERGENCIA (1)	ZB6Y7430	0.001/0.002
	ARRESTO EMERGENZA (1)	ZB6Y7630	0.001/0.002
	NOT-HALT (1)	ZB6Y7230	0.001/0.002

(1) For complying with EN/ISO 13850 standard, paragraph 4.4.6., Emergency Stop function logo  has been added.

Control units Ø 16 plastic

Harmony XB6 modular

Complete bodies and accessories

PF514173
ZB6Z1B101488
ZB6Y009101503
ZB6Y011101502
ZB6Y010107422
ZB6Y003107380
ZB6Y005

Complete bodies

Description	Supply voltage V	Type of contacts		Reference	Weight kg/lb
		N/O	N/C		
Faston connectors					
Direct supply	≤ 250	1	–	ZB6Z1B	0.004/0.009
Fixing collar + contact block		–	1	ZB6Z2B	0.004/0.009
		2	–	ZB6Z3B	0.006/0.013
		–	2	ZB6Z4B	0.006/0.013
		1	1	ZB6Z5B	0.006/0.013

Accessories

Description	Application	Sold in lots of	Reference	Weight kg/lb	
Body accessories					
Body/fixing collar	For mounting contact blocks and light source	10	ZB6Y009	0.002/0.004	
Body bracket (fixing screws included)	Printed circuit board mounting	4	ZB6Y011	0.010/0.022	
Mounting accessories					
Plug-in socket adapter	Printed circuit board mounting	10	ZB6Y010	0.004/0.009	
Dummy contact block housing (without contacts)	Printed circuit board mounting	Without pins for printed circuit	10	ZB6Y006	0.001/0.002
		With pins for printed circuit	10	ZB6Y006A	0.001/0.002
Adapter for XAL control station (Ø 22 mm / 0.866 in. to Ø 16 mm / 0.630 in. reducer)	Ø 16/0.630 in. circular, square or rectangular units	5	ZB6Y006A	0.001/0.002	
Miscellaneous accessories					
Anti-rotation plate	Selector switches, Emergency stop buttons	10	ZB6Y003	0.001/0.002	
Nut	Securing head on support	10	ZB6Y002	0.001/0.002	
Dismantling tool	Removal of contact blocks from body/fixing collar	5	ZB6Y018	0.005/0.011	
Extractor	Removal of pushbutton caps	5	ZB6Y016	0.010/0.022	
Bezel tightening tool + bulb extractor	Tightening and slackening the bezel and changing bulbs	2	ZB6Y905	0.006/0.013	
Metal assembly tool	Tightening of fixing nut	1	ZB6Y906	0.022/0.049	
Dismantling tool kit, comprising 3 tools	Removal of contacts, fixing nuts and pushbutton caps	1	ZB6Y019	0.030/0.066	
Female Faston connector	–	100	ZB6Y004	0.002/0.004	
Blanking plug	–	10	ZB6Y005	0.001/0.002	

Presentation

The Ø 22 mm/0.866 in. Harmony XB4 metal, XB5 plastic, and XB7 plastic range of Emergency stop and Emergency switching off functions combines simplicity of installation, flexibility, robustness, ergonomics and reliability. Designed for control of machines and installations, these functions meet the requirements of majority of industrial applications.

Following are broad and comprehensive offer under this range:

- Emergency stop trigger action and mechanically latching pushbuttons (conforming to standards EN/IEC 60204-1 and EN/ISO 13850)
- Emergency switching off mechanically latching pushbuttons (conforming to standard IEC 60364-5-53)
- Legends and legend holders
- Accessories and spare parts

Installation

- These products are both simple and quick to install:
 - Mounting by single installer (self-maintaining of the head in its cut-out)
 - Clip-together component system (head, body, contact blocks and LED)
 - Fixing by a single locking screw
 - Anti-loosening system for screw clamp terminals of contact blocks.
- Various types of connection are available:
 - Screw clamp terminal connector
 - Spring clamp terminal connector
 - Faston connector
 - Plug-in connector

Environment

The performance features of these range meet the most demanding international standards and approvals:

- Degrees of protection:

The range includes products for use in difficult industrial environments, due to:

 - Their high degree of protection for harsh environments (IP 66 / IP 69K with bellows)
 - Their resistance to high pressure cleaning
 - Their "all climates" TH compatibility
 - A wide choice of contact blocks with various breaking capacities (low, standard or high power switching)
 - For XB7: IP 65 for Emergency stop pushbuttons
- International standards:
 - Emergency stop function: Mushroom head Emergency stop trigger action and mechanical latching pushbuttons conform to standards EN/IEC 60204-1 and EN/ISO 13850, to Machinery Directive 2006/42/EC and to standard EN/IEC 60947-5-5.
 - Emergency switching off function: Mushroom head switching off mechanical latching pushbuttons conform to standards IEC 60364-5-53 and EN/IEC 60947-5-5.

For XB7,

 - Emergency stop function: EN/IEC 60947-5-5, EN/ISO 13850 and EN/IEC 60204-1
 - Emergency switching off function: EN/IEC 60364-5-53
- Product certifications:
 - UL 508, CSA C22-2 n° 14, and GB 14048.5
 - International certifications: UL, CSA, CCC, EAC
 - Marine certifications for XB4 and XB5: BV, RINA, LROS, DNV, GL

Please consult our Customer Care Centre for a full explanation of these standards and directives.

Control units Ø 22



Harmony XB4, metal

Emergency stop and Emergency switching off functions




Conforming to EN/IEC 60204-1, 60364-5-53,

EN/ISO 13850 and Machinery Directive 2006/42/EC




Emergency stop and switching off pushbuttons with trigger action and mechanical latching (1) (2) Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Type of reset	Type of contact		Push		Reference	Weight kg/lb
				Ø mm/in.	Color		
		N/O	N/C				

Complete units

	Push-pull	–	1	40/1.575	Red	XB4BT842 (ZB4BZ105 + ZB4BT84)	0.125/0.276
		1	1	40/1.575	Red	XB4BT845 (ZB4BZ105 + ZB4BT84)	0.136/0.300
	Turn to release	–	1	40/1.575	Red	XB4BS8442 (ZB4BZ102 + ZB4BS844)	0.118/0.260
		1	1	40/1.575	Red	XB4BS8445 (ZB4BZ105 + ZB4BS844)	0.130/0.287
		–	2	40/1.575	Red	XB4BS8444 (ZB4BZ104 + ZB4BS844)	0.130/0.287
		1	2	40/1.575	Red	XB4BS84441 (ZB4BZ141 + ZB4BS844)	0.140/0.309
	Key release (key n° 455) (3)	1	1	40/1.575	Red	XB4BS9445 (ZB4BZ105 + ZB4BS944)	0.170/0.375


Heads only

	Push-pull			30/1.181	Red	ZB4BT844	0.078/0.172
				40/1.575	Red	ZB4BT84	0.078/0.172
				60/2.362	Red	ZB4BX84	0.098/0.216
	Turn to release			30/1.181	Red	ZB4BS834	0.068/0.150
				40/1.575	Red	ZB4BS844	0.073/0.161
				60/2.362	Red	ZB4BS864	0.093/0.205
				30/1.181	Red	ZB4BS934	0.094/0.207
	Key release (key n° 455) 2 keys included with head (5) (3)			40/1.575	Red	ZB4BS944 (4)	0.098/0.216
				60/2.362	Red	ZB4BS964	0.118/0.260

Illuminated Emergency switching off function only, mechanical latching pushbuttons (1) Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Type of reset	Push		Reference	Weight kg/lb
		Ø mm/in.	Color		


Heads only (6)

	Push-pull	40/1.575	Red	ZB4BW643	0.051/0.112
---	-----------	----------	-----	-----------------	-------------

Protected LED

(1) Recommended maximum number of contacts constituting the body (fixing collar + contact) associated with the head, see page 12 of Harmony XB4 catalog DIA5ED21212EN.

(2) It is recommended that a legend or yellow background is used.

(3) The symbol  indicates key withdrawal position(s).

(4) Other key numbers:

- key n° 421E: add suffix **12** to the reference.- key n° 458A: add suffix **10** to the reference.- key n° 520E: add suffix **14** to the reference.- key n° 3131A: add suffix **20** to the reference.- key n° 4A185: add suffix **D** to the reference.Example: To order a Ø 40 mm/1.575 in. red mushroom head for a trigger action and mechanical latching Emergency stop pushbutton, with release by key n° 421E, the reference becomes: **ZB4BS94412**.

(5) For specific keys with other numbers, please consult our Customer Care Centre.


(6) Only for use with bodies comprising a light source with integral LED.

Control units Ø 22

Harmony XB4, metal

Emergency stop and Emergency switching off functions


Circular yellow legends for Emergency stop



ZBY9121



ZBY9420



ZBZ28

Circular yellow legends for Emergency stop (1)

Description	Marking	Color	Sold in lots of	Reference	Weight kg/lb
Ø 60 mm/2.362 in. legend for Emergency stop function	–	Yellow	5	ZBY9121	0.007/0.015
	EMERGENCY STOP	Yellow	5	ZBY9320	0.007/0.015
	ARRET D'URGENCE	Yellow	5	ZBY9120	0.007/0.015
	NOT HALT	Yellow	5	ZBY9220	0.007/0.015
	PARADA DE EMERGENCIA	Yellow	5	ZBY9420	0.007/0.015
	ARRESTO DI EMERGENZA	Yellow	5	ZBY9620	0.007/0.015

Bellows for harsh environments (IP 69K) (2)


For use in	Material	For use with	Color	Sold in lots of	Unit reference	Weight kg/lb
Environments subject to humidity, dust, high pressure, cleaning, etc.	Silicone	Emergency stop / Switching off function	Yellow	2	ZBZ28	0.009/0.020
		Other functions	Black	2	ZBZ58	0.009/0.020

Heads with black metal bezel

To order, add a figure 7 to the references selected above.
Example: ZB4BT844 becomes ZB4BT8447.

(1) Other legend models for Emergency stop and Emergency switching off function see page 15.


(2) Not compatible with Ø 30 mm/1.181 in. pushbutton.



ZB4BZ009



ZBE101




ZBE203




ZB4BZ101



ZBE201




ZB4BZ106



ZBE501



ZB2BE101





ZBZ001

Body/fixing collar



For use with	Sold in lots of	Unit reference	Weight kg/lb
Electrical block (contact or light)	10	ZB4BZ009	0.038/0.084

Contact functions (1)





Screw clamp terminal connections (Schneider Electric anti-loosening system)

Description	Type of contact	Description			Sold in lots of	Unit reference	Weight kg/lb
			N/O	N/C			

Contacts for standard applications

Contact blocks	Single	Double	Single with body/fixing collar			Sold in lots of	Unit reference	Weight kg/lb
	1	–	1	–	5	ZBE101	0.011/0.024	
	–	1	–	–	5	ZBE102	0.011/0.024	
	2	–	–	–	5	ZBE203	0.020/0.044	
	–	2	–	–	5	ZBE204	0.020/0.044	
	1	1	–	1	5	ZBE205	0.020/0.044	
	1	–	1	–	1	ZB4BZ101	0.053/0.117	
	–	1	–	–	1	ZB4BZ102	0.053/0.117	
	2	–	–	–	1	ZB4BZ103	0.062/0.137	
	–	2	–	–	1	ZB4BZ104	0.062/0.137	
	1	1	–	1	1	ZB4BZ105	0.062/0.137	
	1	2	–	–	1	ZB4BZ141	0.072/0.159	

Contacts for specific applications

Low power switching	Single	Standard			Sold in lots of	Unit reference	Weight kg/lb		
	1	–	–	–	5	ZBE1016	0.012/0.026		
	–	1	–	–	5	ZBE1026	0.012/0.026		
	1	Dusty environment(2) (IP 5X, 50 µm dust)	–	–	5	ZBE1016P	0.012/0.026		
	–	–	–	–	5	ZBE1026P	0.012/0.026		
Staggered contacts	Single	Early make N/O			5	ZBE201	0.011/0.024		
		Late break N/C			5	ZBE202	0.011/0.024		
	Single with body/fixing collar	Overlapping N/O+N/C		1	1	5	ZB4BZ106	0.062/0.137	
		Staggered N/O+N/O		2	–	5	ZB4BZ107	0.062/0.137	
High power switching	Single	Standard (3)			1	1	ZBE501	0.020/0.044	
					–	1	1	ZBE502	0.020/0.044
					2	–	1	ZBE503	0.032/0.071
					–	2	1	ZBE504	0.032/0.071
					1	1	1	ZBE505	0.032/0.071
Additional contact blocks for high power switching	Single	Standard (4)			1	–	1	ZB2BE101	0.020/0.044
					–	1	1	ZB2BE102	0.020/0.044

Clip-on legend holder, sheet of blank legends and labelling software

Description	Sold in lots of	Unit reference	Weight kg/lb
Clip-on legend-holder for electrical blocks with screw clamp terminal connections(5). For identification of an XB4Bcontrol or signaling unit	10	ZBZ001	0.001/0.002
Sheet of 50 blank legends for legend holder ZBZ001	10	ZBY001	0.023/0.051
"SIS Label" labelling software for legend design (ZBY001 legends)(for design of legends in English, French, German, Italian, Spanish)	1	XBY2U	0.100/0.220

(1) The contact blocks enable variable composition of body/contact assemblies. Maximum number of rows possible: 3. Either 3 rows of 3 single contacts or 1 row of 3 double contacts + 1 row of 3 single contacts (double contacts occupy the first 2 rows). Maximum number of contacts is specified on page 12 of DIA5ED2121212EN, Harmony XB4 catalog.

(2) It is not possible to fit an additional contact block on the back of these contact blocks.

(3) It is not possible to use these contacts with light blocks.


(4) To be fitted on the back of ZBE50● contacts.

(5) This legend holder is not compatible with high power switching contacts.

Control units Ø 22


Harmony XB4, metal

Light blocks - "Test light" - Protection



Light blocks					
Description	Supply voltage V	Color of light source	Sold in lots of	Unit reference	Weight kg/lb
Light blocks with screw clamp terminal connections (Schneider Electric anti-loosening system)					
Integral LED (to combine with heads for integral LED)	~ 12 (50/60 Hz)	White	5	ZBVJ1	0.017/0.037
		Green	5	ZBVJ3	0.017/0.037
		Red	5	ZBVJ4	0.017/0.037
		Orange	5	ZBVJ5	0.017/0.037
		Blue	5	ZBVJ6	0.017/0.037
		White	5	ZBVB1	0.017/0.037
	~ 24 (50/60 Hz)	Green	5	ZBVB3	0.017/0.037
		Red	5	ZBVB4	0.017/0.037
		Orange	5	ZBVB5	0.017/0.037
		Blue	5	ZBVB6	0.017/0.037
		White	5	ZBVBG1	0.017/0.037
		Green	5	ZBVBG3	0.017/0.037
	~ 24...120 (50/60 Hz)	Red	5	ZBVBG4	0.017/0.037
		Orange	5	ZBVBG5	0.017/0.037
		Blue	5	ZBVBG6	0.017/0.037
		White	5	ZBVG1	0.017/0.037
		Green	5	ZBVG3	0.017/0.037
		Red	5	ZBVG4	0.017/0.037
~ 110...120 (50/60 Hz)	Orange	5	ZBVG5	0.017/0.037	
	Blue	5	ZBVG6	0.017/0.037	
	White	5	ZBVM1	0.017/0.037	
	Green	5	ZBVM3	0.017/0.037	
	Red	5	ZBVM4	0.017/0.037	
	Orange	5	ZBVM5	0.017/0.037	
~ 230...240 (50/60 Hz)	Blue	5	ZBVM6	0.017/0.037	

Flashing light blocks with screw clamp terminal connections (Schneider Electric anti-loosening system)					
Integral LED (to combine with heads for integral LED)	~ 24 (50/60 Hz)	White	5	ZBV18B1	0.017/0.037
		Green	5	ZBV18B3	0.017/0.037
		Red	5	ZBV18B4	0.017/0.037
		Orange	5	ZBV18B5	0.017/0.037
		Blue	5	ZBV18B6	0.017/0.037
		White	5	ZBV18G1	0.017/0.037
	~ 110...120 (50/60 Hz)	Green	5	ZBV18G3	0.017/0.037
		Red	5	ZBV18G4	0.017/0.037
		Orange	5	ZBV18G5	0.017/0.037
		Blue	5	ZBV18G6	0.017/0.037
		White	5	ZBV18M1	0.017/0.037
		Green	5	ZBV18M3	0.017/0.037
	~ 230...240 (50/60 Hz)	Red	5	ZBV18M4	0.017/0.037
		Orange	5	ZBV18M5	0.017/0.037
		Blue	5	ZBV18M6	0.017/0.037



For use with	Supply voltage V	Description	Reference	Weight kg/lb
Transformer blocks for 24 V light blocks (1)				
Light blocks with integral LED	~ 400 V - 50Hz	Transformer 400 V - 24 V ~	ZBV5B (2)	0.090/0.198
Blocks for "test light" function				
Light blocks	~ 12 and 24 ~ 24...120	Single module, 1 connecting wire	ZBZG156 (3)	0.010/0.022
Light blocks with integral LED	~ 48...230	Double module, with connecting wires	ZBZG156 (3)	0.010/0.022

LED suppressors				
For use with	Supply voltage V	Level of protection	Reference	Weight kg/lb
Light blocks with integral LED fitted with screw clamp terminal connections	~ 120	25...120 VA	ZBZVG	0.010/0.022
	~ 230	30...230 VA	ZBZVM	0.010/0.022

(1) To be used with 2 dummy contact blocks **ZBE000**.
 (2) To order ~ 440...460 V - 60 Hz transformer blocks, please replace "5" in the reference by "8": **ZBV5B** becomes **ZBV8B**. To order ~ 550...600 V - 60 Hz transformer blocks, please replace "5" by "9": **ZBV5B** becomes **ZBV9B**.
 (3) Block for use with ~ light blocks with integral LED types **ZBVJ●**, **ZBVB●**, **ZBVBG●** or with direct supply light block for BA 9s bulb, **ZBV6**.
 (4) Block for use ~ light blocks integral LED types **ZBVG●**, **ZBVM●**, see connection on Schneider Electric website, Harmony XB4.

Control units Ø 22

Harmony XB4, metal


Body/contact assemblies - Spring clamp terminal connections




ZB4BZ009




ZBE1015




ZB4BZ1015



ZBVB35



ZBZ001



XBY2U

Body/fixing collar

For use with	Sold in lots of	Unit reference	Weight kg/lb
Electrical block (contact or light)	10	ZB4BZ009	0.038/0.084

Contact functions Spring clamp terminal connections (1)

Description	Type of contact	Symbol		Sold in lots of	Unit reference	Weight kg/lb
		N/O	N/C			

Contacts for standard applications

Contact blocks	Type of contact	N/O	N/C	Sold in lots of	Unit reference	Weight kg/lb
Contact blocks	Single	1	–	4	ZBE1015	0.011/0.024
		–	1	4	ZBE1025	0.011/0.024
Contact blocks	Single with body/fixing collar	1	–	1	ZB4BZ1015	0.053/0.117
		–	1	1	ZB4BZ1025	0.053/0.117
		2	–	1	ZB4BZ1035	0.062/0.137
		–	2	1	ZB4BZ1045	0.062/0.137
		1	1	1	ZB4BZ1055	0.062/0.137

Light blocks Spring clamp terminal connections (1)

Description	Supply voltage V	Color of light source	Sold in lots of	Unit reference	Weight kg/lb
Integral LED (to combine with heads for integral LED)	~ 12 (50/60 Hz)	White	4	ZBVJ15	0.016/0.035
		Green	4	ZBVJ35	0.016/0.035
		Red	4	ZBVJ45	0.016/0.035
		Orange	4	ZBVJ55	0.016/0.035
		Blue	4	ZBVJ65	0.016/0.035
	~ 24 (50/60 Hz)	White	4	ZBVB15	0.016/0.035
		Green	4	ZBVB35	0.016/0.035
		Red	4	ZBVB45	0.016/0.035
		Orange	4	ZBVB55	0.016/0.035
		Blue	4	ZBVB65	0.016/0.035
~ 110...120 (50/60 Hz)	White	4	ZBVG15	0.016/0.035	
	Green	4	ZBVG35	0.016/0.035	
	Red	4	ZBVG45	0.016/0.035	
	Orange	4	ZBVG55	0.016/0.035	
	Blue	4	ZBVG65	0.016/0.035	
~ 230...240 (50/60 Hz)	White	4	ZBVM15	0.016/0.035	
	Green	4	ZBVM35	0.016/0.035	
	Red	4	ZBVM45	0.016/0.035	
	Orange	4	ZBVM55	0.016/0.035	
	Blue	4	ZBVM65	0.016/0.035	
Integral LED + body/fixing collar	~ 110...120 (50/60 Hz)	Green	4	ZB4BVG35	0.053/0.117
		Red	4	ZB4BVG45	0.053/0.117



Sheet of 50 blank legends

For use with	Sold in lots of	Unit reference	Weight kg/lb
Legend holder ZBZ001	10	ZBY001	0.023/0.051



“SIS Label” labelling software (for legends ZBY001)

For legend design for English, French, German, Italian, Spanish	Sold in lots of	Unit reference	Weight kg/lb
	10	XBY2U	0.100/0.220



(1) It is not possible to fit an additional block on the back of these contact or light blocks.

Contact functions (1)**Faston connectors (Ø 6.35 or 2 x 2.8 mm/0.250 or 2 x 0.110 in.)**

(Schneider Electric anti-loosening system)



Description	Type of contact			Sold in lots of	Unit reference	Weight kg/lb
-------------	-----------------	---	---	-----------------	----------------	--------------

Contacts for standard applications

Description	Type of contact			Sold in lots of	Unit reference	Weight kg/lb
Contact blocks	Single	1	–	5	ZBE1013	0.011/0.024
		–	1	5	ZBE1023	0.011/0.024
	Double	2	–	5	ZBE2033	0.020/0.044
		–	2	5	ZBE2043	0.020/0.044
Single with body/fixing collar		1	1	5	ZBE2053	0.020/0.044
		1	–	1	ZB4BZ1013 (2)	0.053/0.117
		–	1	1	ZB4BZ1023 (2)	0.053/0.117
		2	–	1	ZB4BZ1033	0.062/0.137
		–	2	1	ZB4BZ1043	0.062/0.137
		1	1	1	ZB4BZ1053	0.062/0.137

Application	Type of contact	Description			Sold in lots of	Unit reference	Weight kg/lb
-------------	-----------------	-------------	---	---	-----------------	----------------	--------------

Contacts for specific applications

Low power switching	Single	Standard	1	–	5	ZBE10163 (2)	0.012/0.026
			–	1	5	ZBE10263 (2)	0.012/0.026
		Dusty environments (3) (IP 5X, 50 µm dust)	1	–	5	ZBE1016P3 (2)	0.012/0.026
			–	1	5	ZBE1026P3 (2)	0.012/0.026
Staggered contacts	Single	Early make 	1	–	5	ZBE2013 (2)	0.011/0.024
		Late break 	–	1	5	ZBE2023 (2)	0.011/0.024
High power switching	Single	Standard (4)	1	–	1	ZBE5013	0.021/0.046
			–	1	1	ZBE5023	0.021/0.046
			2	–	1	ZBE5033	0.033/0.073
			–	2	1	ZBE5043	0.033/0.073
		1	1	1	ZBE5053	0.033/0.073	

Clip-on legend holder for electrical blocks with screw clamp terminal connections (5)

For use with	Sold in lots of	Unit reference	Weight kg/lb
Identification of an XB4B control or signaling unit	10	ZBZ001	0.001/0.002

Sheet of 50 blank legends

Legend holder ZBZ001	10	ZBY001	0.023/0.051
----------------------	----	--------	-------------

“SIS Label” labelling software (for legends ZBY001)

For legend design for English, French, German, Italian, Spanish	1	XBY2U	0.100/0.220
---	---	-------	-------------


- (1) The contact blocks enable variable composition of body/contact assemblies. Maximum number of rows possible: 3. Either 3 rows of 3 single contacts or 1 row of 3 double contacts + 1 row of 3 single contacts (double contacts occupy the first 2 rows).
- (2) To order products with screw clamp terminal connections for lugs, replace the 3 at the end of the reference with a 9. Example: ZBE1013 becomes ZBE1019.
- (3) It is not possible to fit an additional contact block on the back of these contact blocks.
- (4) It is not possible to use these contacts with light blocks.
- (5) This legend holder is not compatible with high power switching contact blocks.




ZBE1023




ZBE2043




ZB4BZ1043




ZBE5043



ZBZ001




XBY2U



ZB4BZ009




ZBE1014



ZBE1024




ZB4BZ1014



ZB4BZ1024



ZBVB14



APE1C2250

Body/fixing collar

For use with	Sold in lots of	Unit reference	Weight kg/lb
Electrical block (contact or light)	10	ZB4BZ009	0.038/0.084

Contact functions Plug-in connector (1)

Description	Type of contact	N/O	N/C	Sold in lots of	Unit reference	Weight kg/lb	
Contacts for standard applications							
Contact blocks	Single	1	–	5	ZBE1014	0.011/0.024	
		–	1	5	ZBE1024	0.011/0.024	
	Single with body/fixing collar	1	–	1	ZB4BZ1014	0.050/0.110	
		–	1	1	ZB4BZ1024	0.050/0.110	
		2	–	–	1	ZB4BZ1034	0.058/0.128
			–	2	1	ZB4BZ1044	0.058/0.128
		1	1	1	1	ZB4BZ1054	0.058/0.128
			1	2	1	ZB4BZ1414	0.064/0.141

Light blocks Plug-in connector

Description	Supply voltage V	Color of light source	Sold in lots of	Unit reference	Weight kg/lb
Integral LED (to combine with heads for integral LED)	≈ 24 (50/60 Hz)	White	5	ZBVB14	0.016/0.035
		Green	5	ZBVB34	0.016/0.035
		Red	5	ZBVB44	0.016/0.035
		Orange	5	ZBVB54	0.016/0.035
		Blue	5	ZBVB64	0.016/0.035
		~ 110...120 (50/60 Hz)	White	5	ZBVG14
	Green		5	ZBVG34	0.016/0.035
	Red		5	ZBVG44	0.016/0.035
	Orange		5	ZBVG54	0.016/0.035
	Blue		5	ZBVG64	0.016/0.035
	~ 230...240 (50/60 Hz)		White	5	ZBVM14
		Green	5	ZBVM34	0.016/0.035
Red		5	ZBVM44	0.016/0.035	
Orange		5	ZBVM54	0.016/0.035	
Blue		5	ZBVM64	0.016/0.035	

Connecting cables and connector

Description	Number of connectors	Wire c. s. a. mm ² /AWG	Length Ø mm/in.	Sold in lots of	Unit reference	Weight kg/lb
Cables with connectors 2-pin, Ø 5.08 mm/0.200 in. pitch	1	0.75/19	500/19.685	8	APE1C2150	0.120/0.265
	2	0.75/19	500/19.685	8	APE1C2250	0.180/0.397
Spring terminal connector 2-pin, Ø 5.08 mm/0.200 in. pitch	–	0.2 to 0.5/25 – to 14	–	10	APE1PRE21	0.003/0.007


(1) It is not possible to fit an additional contact block on the back of these contact blocks.

Circular yellow legends for mushroom head pushbuttons					
Diameter mm/in.	Conforming to standards	Marking on Yellow background	Sold in lots of	Unit Reference	Weight kg/lb
Used for "Emergency stop" function (1)					
90/3.543	EN/IEC 60204-1 and EN/ISO 13850	–	10	ZBY8140	0.008/0.018
		ARRET D'URGENCE	10	ZBY8130	0.008/0.018
		EMERGENCY STOP	10	ZBY8330	0.008/0.018
		NOT-HALT	10	ZBY8230	0.008/0.018
		PARADA DE EMERGENCIA	10	ZBY8430	0.008/0.018
		ARRESTO DE EMERGENZA	10	ZBY8630	0.008/0.018
Used for "Emergency switching off" function					
60/2.362	EN/IEC 60204-1	–	10	ZBY9101	0.004/0.009
		COUPURE D'URGENCE	10	ZBY9160	0.004/0.009
		EMERGENCY SWITCHING OFF	10	ZBY9360	0.004/0.009
		NOT-AUS	10	ZBY9260	0.004/0.009
		DESCONEXION DE EMERGENCIA	10	ZBY9460	0.004/0.009
		INTERRUZIONE DI EMERGENZA	10	ZBY9660	0.004/0.009
90/3.543	EN/IEC 60204-1	–	10	ZBY8101	0.008/0.018
		COUPURE D'URGENCE	10	ZBY8160	0.008/0.018
		EMERGENCY SWITCHING OFF	10	ZBY8360	0.008/0.018
		NOT-AUS	10	ZBY8260	0.008/0.018
		DESCONEXION DE EMERGENCIA	10	ZBY8460	0.008/0.018
		INTERRUZIONE DI EMERGENZA	10	ZBY8660	0.008/0.018




ZBY9160

(1) For complying with EN/ISO 13850 standard, paragraph 4.4.6., Emergency Stop function logo  has been added.




Accessories for mushroom head pushbuttons


Description	Exclusive use with the following Ø 40 mm/1.575 in. trigger action pushbuttons	Color	Reference	Weight kg/lb
Padlocking kit (1) (2) For Emergency stop (3) and Emergency switching off function (4), (padlockable)	XB4BS844●, XB4BS9445, ZB4BS844, ZB4BS944●.	Yellow	ZBZ3605	0.045/0.099
Metal guards For Emergency stop (3) function Padlockable (2)	XB4BT8●, XB4BS8●, XB4BS9●, ZB4BT8●, ZB4BS8●, ZB4BS9●.	Chromium plated	ZBZ1600	0.046/0.101
		Black	ZBZ1602	0.046/0.101
		Red	ZBZ1604	0.046/0.101
		Blue	ZBZ1606	0.046/0.101



Description	Marking	Color	Reference	Weight kg/lb
Ø 60 mm/2.362 in. legend for padlocking device ZBZ3605 For Emergency stop function (3)	Without	Yellow	ZBY9140T	0.004/0.009
	ARRET D'URGENCE	Yellow	ZBY9130T	0.004/0.009
	EMERGENCY STOP	Yellow	ZBY9330T	0.004/0.009
	NOT-HALT	Yellow	ZBY9230T	0.004/0.009
Ø 60 mm/2.362 in. legend for padlocking device ZBZ3605 For Emergency switching off function (4)	Without	Yellow	ZBY9101T	0.004/0.009
	COUPURE D'URGENCE	Yellow	ZBY9160T	0.004/0.009
	EMERGENCY SWITCHING OFF	Yellow	ZBY9360T	0.004/0.009
	NOT-AUS	Yellow	ZBY9260T	0.004/0.009



Description	Marking	Color	Sold in lots of	Reference	Weight kg/lb
Ø 60 mm/2.362 in. legend for Emergency stop function	–	Yellow	5	ZBY9121	0.007/0.015
	EMERGENCY STOP	Yellow	5	ZBY9320	0.007/0.015
	ARRET D'URGENCE	Yellow	5	ZBY9120	0.007/0.015
	NOT HALT	Yellow	5	ZBY9220	0.007/0.015
	PARADA DE EMERGENCIA	Yellow	5	ZBY9420	0.007/0.015
	ARRESTO DI EMERGENZA	Yellow	5	ZBY9620	0.007/0.015



Other accessories

Description	For use with	Color	Reference	Weight kg/lb
Plastic guard	Selector switches and key switches	Black	ZBZ2102	0.005/0.011
Padlockable flaps	Pushbuttons	Black	ZB4BZ62	0.076/0.168
		Red	ZB4BZ64	0.076/0.168
		Yellow	ZB4BZ65	0.076/0.168
		Blue	ZB4BZ66	0.076/0.168



- (1) Standard circular legends are not compatible with this product. Use special legends **ZBY9●●●T**.
- (2) No isolation function is possible when this guard is fitted.
- (3) Ensures conformity with standards EN/IEC 60204-1 and EN/ISO 13850.
- (4) Ensures conformity with standard EN/IEC 60204-1.
- (5) Only when mounted on control stations. Use legends **ZBY9●●●T**.

Control units Ø 22

Harmony XB5, plastic



Emergency stop and Emergency switching off functions





Conforming to EN/IEC 60204-1, 60364-5-53,





EN/ISO 13850 and Machinery Directive 2006/42/EC

Emergency stop and switching off pushbuttons with trigger action and mechanical latching (1) (2)

Screw clamp terminal connections (Schneider Electric anti-loosening system)


Shape of head	Type of reset	Type of contact		Push		Reference	Weight kg/lb
				Ø mm/in.	Color		

Complete units							
	Push-pull	–	1	40/1.575	Red	XB5AT842 (ZB5AZ102 + ZB5AT84)	0.065/0.143
		1	1	40/1.575	Red	XB5AT845 (ZB5AZ105 + ZB5AT84)	0.076/0.168
	Turn to release	–	1	40/1.575	Red	XB5AS8442 (ZB5AZ102 + ZB5AS844)	0.060/0.132
		1	1	40/1.575	Red	XB5AS8445 (ZB5AZ105 + ZB5AS844)	0.072/0.159
		–	2	40/1.575	Red	XB5AS8444 (ZB5AZ104 + ZB5AS844)	0.072/0.159
	Key release (key n° 455)(3)	–	1	40/1.575	Red	XB5AS9442 (ZB5AZ102 + ZB5AS944)	0.075/0.165
			1	1	40/1.575	Red	XB5AS9445 (ZB5AZ105 + ZB5AS944)


Heads only							
	Push-pull			30/1.181	Red	ZB5AT844	0.049/0.108
				40/1.575	Red	ZB5AT84	0.049/0.108
				60/2.362	Red	ZB5AX84	0.067/0.148
	Turn to release			30/1.181	Red	ZB5AS834	0.042/0.002
				40/1.575	Red	ZB5AS844	0.046/0.002
	Key release (key n° 455) (2 keys included with head) (5)(3)			30/1.181	Red	ZB5AS934	0.068/0.003
				40/1.575	Red	ZB5AS944 (4)	0.071/0.003
				60/2.362	Red	ZB5AS964	0.092/0.004
				40/1.575	Red	ZB5AS944D	0.071/0.003
	Key release (key n° 4A185) (5)			40/1.575	Red	ZB5AS944D	0.071/0.003

Illuminated Emergency stop and Emergency switching off functions, mechanical latching pushbuttons with mechanical state indicator (1)

For elevator inspection box applications


Shape of head	Type of reset	Push Ø mm/in.	Color	Unit reference	Weight kg/lb
		40/1.575	Red	ZB5AT8643M	0.034/0.075


Heads only (6)

 **Protected LED**
Push-pull (7)
For Emergency stop and Emergency switching off function

Illuminated Emergency switching off function only, mechanical latching pushbuttons (1)


Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Type of reset	Push Ø mm/in.	Color	Reference	Weight kg/lb
	Turn to release	40/1.575	Red	ZB5AW743	0.022/0.049

 **Protected LED**

(1) Recommended maximum number of contacts constituting the body (fixing collar and contact) associated with the head, see page 12 of Harmony XB5 catalog DIA5ED2121213EN.

(2) It is recommended that a legend or yellow background is used.

(3) The symbol  indicates key withdrawal position(s).

(4) Other key numbers:
 - key n° 421E: add suffix **12** to the reference.
 - key n° 458A: add suffix **10** to the reference.
 - key n° 520E: add suffix **14** to the reference.
 - key n° 3131A: add suffix **20** to the reference.
 - key n° 4A185: add suffix **D** to the reference.
 Example: To order a Ø 40 mm/1.575 in. red mushroom head for a trigger action and mechanical latching Emergency stop pushbutton, with release by key n° 421E, the reference becomes: **ZB5AS94412**.




(5) For specific keys with other numbers, please consult our Customer Care Centre.

(6) Only for use with bodies comprising a light source with integral LED.

(7) Cannot be used with metal guards **ZBZ160**.

General safe stops

General safe stops are used to stop the operation of a machine in a safe manner. These devices cannot be used as Emergency stop and must not be associated with a Yellow background. The general safe stop are made with Yellow bezel and Black head.

Shape of head	Type of reset	Push		Reference	Weight kg/lb
		Ø (mm)/in.	Color		
	Push-pull	40/1.575	Black	ZB5AT82Y	0.050/0.110
	Turn to release	40/1.575	Black	ZB5AS842Y	0.046/0.101
	Key release (key n° 455) 2 keys included with head) (2)	40/1.575	Black	ZB5AS942Y	0.071/0.157


Circular yellow legends for Emergency stop (1)

Description	Marking	Color	Sold in lots of	Reference	Weight kg/lb
Ø 60 mm/2.362 in. legend for Emergency stop function	-	Yellow	5	ZBY9121	0.007/0.015
	EMERGENCY STOP	Yellow	5	ZBY9320	0.007/0.015
	ARRET D'URGENCE	Yellow	5	ZBY9120	0.007/0.015
	NOT HALT	Yellow	5	ZBY9220	0.007/0.015
	PARADA DE EMERGENCIA	Yellow	5	ZBY9420	0.007/0.015
	ARRESTO DI EMERGENZA	Yellow	5	ZBY9620	0.007/0.015

Bellows for harsh environments (IP 69K) (3)

Description	Material	For use with	Color	Sold in lots of	Unit reference	Weight kg/lb
For use in environments subject to humidity, dust, high pressure cleaning, etc.	Silicone	Emergency stop / Switching off function	Yellow	2	ZBZ28	0.009/0.020
		Other functions	Black	2	ZBZ58	0.009/0.020


(1) Other legend models for Emergency stop and Emergency switching off function, see page 58 of catalog DIA5D2121212EN

(2) The symbol  indicates key withdrawal position(s).

(3) Not compatible with Ø 30 mm/1.181 in. pushbuttons.



ZB5AT82Y



ZB5AS942Y



ZBY9121



ZBY9420



ZBZ28

Control units Ø 22

Harmony XB5, plastic


Body/contact assemblies - Screw clamp terminal connections




ZB5AZ009




ZBE101




ZBE203




ZB5AZ101




ZBE201




ZB5AZ107



ZBE501



ZB2BE101



ZBZ001

Body/fixing collar

For use with	Sold in lots of	Unit reference	Weight kg/lb
Electrical block (contact or light)	10	ZB5AZ009	0.006/0.013

Contact functions (1) Screw clamp terminal connections (Schneider Electric anti-loosening system)

Application	Type of contact	Description			Sold in lots of	Unit reference	Weight kg/lb
			N/O	N/C			

Contacts for standard applications							
Contacts for standard applications	Single	Contact blocks					
			1	–	5	ZBE101	0.011/0.024
			–	1	5	ZBE102	0.011/0.024
	Double		2	–	5	ZBE203	0.020/0.044
			–	2	5	ZBE204	0.020/0.044
			1	1	5	ZBE205	0.020/0.044
	Single with body/fixing collar		1	–	1	ZB5AZ101	0.021/0.046
			–	1	1	ZB5AZ102	0.021/0.046
			2	–	1	ZB5AZ103	0.030/0.066
			–	2	1	ZB5AZ104	0.030/0.066
			1	1	1	ZB5AZ105	0.030/0.066
			1	2	1	ZB5AZ141	0.040/0.088

Contacts for specific applications								
Low power switching	Single	Standard	1	–	5	ZBE1016	0.012/0.026	
			–	1	5	ZBE1026	0.012/0.026	
		Dusty environment(2) (IP 5X, 50 µm dust)	1	–	5	ZBE1016P	0.012/0.026	
			–	1	5	ZBE1026P	0.012/0.026	
Staggered contacts	Single	Early make N/O	1	–	5	ZBE201	0.011/0.024	
			–	1	5	ZBE202	0.011/0.024	
		Late break N/C	–	1	5	ZBE202	0.011/0.024	
			1	1	5	ZB4BZ106	0.062/0.137	
		Single with body/fixing collar	Overlapping N/O+N/C	1	1	5	ZB4BZ106	0.062/0.137
			Staggered N/O+N/O	2	–	5	ZB4BZ107	0.062/0.137
High power switching	Single	Standard (3)	1	–	1	ZBE501	0.020/0.044	
			–	1	1	ZBE502	0.020/0.044	
			2	–	1	ZBE503	0.032/0.071	
			–	2	1	ZBE504	0.032/0.071	
			1	1	1	ZBE505	0.032/0.071	
			1	–	1	ZB2BE101	0.020/0.044	
Additional contact blocks for high power switching	Single	Standard (4)	–	1	1	ZB2BE102	0.020/0.044	

Clip-on legend holder, sheet of blank legends and labelling software


Description	Sold in lots of	Unit reference	Weight kg/lb
Clip-on legend-holder for electrical blocks with screw clamp terminal connections(5). For identification of an XB4B control or signaling unit	10	ZBZ001	0.001/0.002
Sheet of 50 blank legends for legend holder ZBZ001	10	ZBY001	0.023/0.051
“SIS Label” labelling software for legend design (ZBY001 legends)(for design of legends in English, French, German, Italian, Spanish)	1	XBY2U	0.100/0.220

(1) The contact blocks enable variable composition of body/contact assemblies. Maximum number of rows possible: 3. Either 3 rows of 3 single contacts or 1 row of 3 double contacts + 1 row of 3 single contacts (double contacts occupy the first 2 rows). Maximum number of contacts is specified on page 12 of Harmony XB5 catalog DIA5ED2121213EN.
 (2) It is not possible to fit an additional contact block on the back of these contact blocks.
 (3) It is not possible to fit an additional contact block on the back of these contact blocks or to use these contacts with light blocks.
 (4) To be fitted on the back of ZBE501 contacts.
 (5) This legend holder is not compatible with high power switching contacts.

Control units Ø 22

Harmony XB5, plastic

Light blocks - "Test light" - Protection



ZBVB1

Light blocks					
Description	Supply voltage V	Color of light source	Sold in lots of	Unit reference	Weight kg/lb
Light blocks with screw clamp terminal connections (Schneider Electric anti-loosening system)					
Integral LED (to combine with heads for integral LED)	~ 12 (50/60 Hz)	White	5	ZBVJ1	0.017/0.037
		Green	5	ZBVJ3	0.017/0.037
		Red	5	ZBVJ4	0.017/0.037
		Orange	5	ZBVJ5	0.017/0.037
		Blue	5	ZBVJ6	0.017/0.037
		~ 24 (50/60 Hz)	White	5	ZBVB1
	Green		5	ZBVB3	0.017/0.037
	Red		5	ZBVB4	0.017/0.037
	Orange		5	ZBVB5	0.017/0.037
	Blue		5	ZBVB6	0.017/0.037
	~ 24...120 (50/60 Hz)		White	5	ZVBVG1
		Green	5	ZVBVG3	0.017/0.037
Red		5	ZVBVG4	0.017/0.037	
Orange		5	ZVBVG5	0.017/0.037	
Blue		5	ZVBVG6	0.017/0.037	
~ 110...120 (50/60 Hz)		White	5	ZBVG1	0.017/0.037
	Green	5	ZBVG3	0.017/0.037	
	Red	5	ZBVG4	0.017/0.037	
	Orange	5	ZBVG5	0.017/0.037	
	Blue	5	ZBVG6	0.017/0.037	
	~ 230...240 (50/60 Hz)	White	5	ZBVM1	0.017/0.037
Green		5	ZBVM3	0.017/0.037	
Red		5	ZBVM4	0.017/0.037	
Orange		5	ZBVM5	0.017/0.037	
Blue		5	ZBVM6	0.017/0.037	

Flashing light blocks with screw clamp terminal connections					
(Schneider Electric anti-loosening system)					
Description	Supply voltage V	Color of light source	Sold in lots of	Unit reference	Weight kg/lb
Integral LED (to combine with heads for integral LED)	~ 24 (50/60 Hz)	White	5	ZBV18B1	0.017/0.037
		Green	5	ZBV18B3	0.017/0.037
		Red	5	ZBV18B4	0.017/0.037
		Orange	5	ZBV18B5	0.017/0.037
		Blue	5	ZBV18B6	0.017/0.037
		~ 110...120 (50/60 Hz)	White	5	ZBV18G1
	Green		5	ZBV18G3	0.017/0.037
	Red		5	ZBV18G4	0.017/0.037
	Orange		5	ZBV18G5	0.017/0.037
	Blue		5	ZBV18G6	0.017/0.037
	~ 230...240 (50/60 Hz)		White	5	ZBV18M1
		Green	5	ZBV18M3	0.017/0.037
Red		5	ZBV18M4	0.017/0.037	
Orange		5	ZBV18M5	0.017/0.037	
Blue		5	ZBV18M6	0.017/0.037	



ZBV5B



ZBZG156



ZBZM156



ZBZVG

For use with	Supply voltage V	Description	Reference	Weight kg/lb
Transformer blocks for 24 V light blocks (1)				
Light blocks with integral LED	~ 400 V - 50Hz	Transformer 400 V - 24 V ~	ZBV5B (2)	0.090/0.198
Blocks for "test light" function				
Light blocks	~ 12 and 24 ~ 24...120	Single module, 1 connecting wire	ZBZG156 (3)	0.010/0.022
Light blocks with integral LED	~ 48...230	Double module, with connecting wires	ZBZG156 (3)	0.010/0.022

LED suppressors				
For use with	Supply voltage V	Level of protection	Reference	Weight kg/lb
Light blocks with integral LED fitted with screw clamp terminal connections	~ 120	25...120 VA	ZBZVG	0.010/0.022
	~ 230	30...230 VA	ZBZVM	0.010/0.022

(1) To be used with 2 dummy contact blocks ZBE000.
 (2) To order ~ 440...460 V - 60 Hz transformer blocks, please replace "5" in the reference by "8": ZBV5B becomes ZBV8B.
 To order ~ 550...600 V - 60 Hz transformer blocks, please replace "5" by "9": ZBV5B becomes ZBV9B.
 (3) Block for use with ~ light blocks with integral LED types ZBVJ●, ZBVB●, ZVBVG● or with direct supply light block for BA 9s bulb, ZBV6.
 (4) Block for use ~ light blocks integral LED types ZBVG●, ZBVM●, see connection on Schneider Electric website, Harmony XB5.

Control units Ø 22

Harmony XB5, plastic
Body/contact assemblies - Spring clamp terminal connections

814586





ZB5AZ009

Body/fixing collar				
For use with	Sold in lots of	Unit reference	Weight kg/lb	
Electrical block (contact or light)	10	ZB5AZ009	0.006/0.013	

PF10777



ZBE1015

Contact functions Spring clamp terminal connections (1)						
Description	Type of contact			Sold in lots of	Unit reference	Weight kg/lb
Contacts for standard applications						
Contact blocks	Single	1	–	4	ZBE1015	0.011/0.024
		–	1	4	ZBE1025	0.011/0.024
	Single with body/fixing collar	1	–	1	ZB5AZ1015	0.021/0.046
		–	1	1	ZB5AZ1025	0.021/0.046
		2	–	1	ZB5AZ1035	0.030/0.066
	–	2	1	ZB5AZ1045	0.030/0.066	
	1	1	1	ZB5AZ1055	0.030/0.066	

PF10781



ZB5AZ1015

Light blocks Spring clamp terminal connections (1)					
Description	Supply voltage V	Color of light source	Sold in lots of	Unit reference	Weight kg/lb
Integral LED (to combine with heads for integral LED)	~ 12 (50/60 Hz)	White	4	ZBVJ15	0.016/0.035
		Green	4	ZBVJ35	0.016/0.035
		Red	4	ZBVJ45	0.016/0.035
		Orange	4	ZBVJ55	0.016/0.035
		Blue	4	ZBVJ65	0.016/0.035
		~ 24 (50/60 Hz)	White	4	ZBVB15
	Green		4	ZBVB35	0.016/0.035
	Red		4	ZBVB45	0.016/0.035
	Orange		4	ZBVB55	0.016/0.035
	Blue		4	ZBVB65	0.016/0.035
	~ 110...120 (50/60 Hz)		White	4	ZBVG15
		Green	4	ZBVG35	0.016/0.035
Red		4	ZBVG45	0.016/0.035	
Orange		4	ZBVG55	0.016/0.035	
Blue		4	ZBVG65	0.016/0.035	
~ 230...240 (50/60 Hz)		White	4	ZBVM15	0.016/0.035
	Green	4	ZBVM35	0.016/0.035	
	Red	4	ZBVM45	0.016/0.035	
	Orange	4	ZBVM55	0.016/0.035	
	Blue	4	ZBVM65	0.016/0.035	




PF08071



ZBVB35

814262



ZBZ001

Sheet of 50 blank legends				
For use with	Sold in lots of	Unit reference	Weight kg/lb	
Legend holder ZBZ001	10	ZBY001	0.023/0.051	

540548



XBY2U

"SIS Label" labelling software (for legends ZBY001)				
For legend design for English, French, German, Italian, Spanish	Sold in lots of	Unit reference	Weight kg/lb	
	10	XBY2U	0.100/0.220	


(1) It is not possible to fit an additional block on the back of these contact or light blocks.




ZBE1023




ZBE2043




ZB4BZ1043



ZBE5043



ZBZ001





XBY2U






Contact functions (1)

Faston connectors (Ø 6.35 or 2 x 2.8 mm/0.250 or 2 x 0.110 in.)

Contacts for standard applications

Description	Type of contact			Sold in lots of	Unit reference	Weight kg/lb
Contact blocks	Single	1	–	5	ZBE1013	0.011/0.024
		–	1	5	ZBE1023	0.011/0.024
	Double	2	–	5	ZBE2033	0.020/0.044
		–	2	5	ZBE2043	0.020/0.044
		1	1	5	ZBE2053	0.020/0.044
		1	–	1	ZB5AZ1013 (2)	0.021/0.046
	Single with body/fixing collar	–	1	1	ZB5AZ1023 (2)	0.021/0.046
		2	–	1	ZB5AZ1033	0.030/0.066
		–	2	1	ZB5AZ1043	0.030/0.066
		1	1	1	ZB5AZ1053	0.030/0.066

Contacts for specific applications

Application	Type of contact	Description			Sold in lots of	Unit reference	Weight kg/lb
Low power switching	Single	Standard	1	–	5	ZBE10163 (2)	0.012/0.026
			–	1	5	ZBE10263 (2)	0.012/0.026
		Dusty environments (3) (IP 5X, 50 µm dust)	1	–	5	ZBE1016P3 (2)	0.012/0.026
			–	1	5	ZBE1026P3 (2)	0.012/0.026
Staggered contacts	Single	Early make 	1	–	5	ZBE2013 (2)	0.011/0.024
		Late break 	–	1	5	ZBE2023 (2)	0.011/0.024
		N/O 	–	–	–	–	–
High power switching	Single	Standard (4)	1	–	1	ZBE5013	0.021/0.046
			–	1	1	ZBE5023	0.021/0.046
			2	–	1	ZBE5033	0.033/0.073
			–	2	1	ZBE5043	0.033/0.073
			1	1	1	ZBE5053	0.033/0.073

Clip-on legend holder for electrical blocks with screw clamp terminal connections (5)

For use with	Sold in lots of	Unit reference	Weight kg/lb
Identification of an XB5A control or signaling unit	10	ZBZ001	0.001/0.002

Sheet of 50 blank legends

Legend holder ZBZ001	10	ZBY001	0.023/0.051
----------------------	----	--------	-------------

“SIS Label” labelling software (for legends ZBY001)

For legend design for English, French, German, Italian, Spanish	1	XBY2U	0.100/0.220
---	---	-------	-------------

- (1) The contact blocks enable variable composition of body/contact assemblies. Maximum number of rows possible: 3. Either 3 rows of 3 single contacts or 1 row of 3 double contacts + 1 row of 3 single contacts (double contacts occupy the first 2 rows).
- (2) To order products with screw clamp terminal connections for lugs, replace the 3 at the end of the reference with a 9. Example: ZBE1013 becomes ZBE1019.
- (3) It is not possible to fit an additional contact block on the back of these contact blocks.
- (4) It is not possible to use these contacts with light blocks.
- (5) This legend holder is not compatible with high power switching contacts.

Control units Ø 22

Harmony XB5, plastic

Body/contact assemblies - Plug-in connector

814888



ZB5AZ009

101262



ZBE1014

101265




ZBE1024

814808



ZB5AZ1014

814410




ZB5AZ1024

101270



ZBVB14

530719



APE1C2250

Body/fixing collar

For use with	Sold in lots of	Unit reference	Weight kg/lb
Electrical block (contact or light)	10	ZB5AZ009	0.006/0.013

Contact functions Plug-in connector (1)

Description	Type of contact	Symbol		Sold in lots of	Unit reference	Weight kg/lb
		N/O	N/C			
Contacts for standard applications						
Contact blocks	Single	1	–	5	ZBE1014	0.011/0.024
		–	1	5	ZBE1024	0.011/0.024
	Single with body/fixing collar	1	–	1	ZB5AZ1014	0.018/0.040
		–	1	1	ZB5AZ1024	0.018/0.040
		2	–	1	ZB5AZ1034	0.026/0.057
		–	2	1	ZB5AZ1044	0.026/0.057
		1	1	1	ZB5AZ1054	0.026/0.057
		1	2	1	ZB5AZ1414	0.036/0.079

Light blocks Plug-in connector

Description	Supply voltage V	Color of light source	Sold in lots of	Unit reference	Weight kg/lb
Integral LED (to combine with heads for integral LED)	~ 24 (50/60 Hz)	White	5	ZBVB14	0.016/0.035
		Green	5	ZBVB34	0.016/0.035
		Red	5	ZBVB44	0.016/0.035
		Orange	5	ZBVB54	0.016/0.035
		Blue	5	ZBVB64	0.016/0.035
	~ 110...120 (50/60 Hz)	White	5	ZBVG14	0.016/0.035
		Green	5	ZBVG34	0.016/0.035
		Red	5	ZBVG44	0.016/0.035
		Orange	5	ZBVG54	0.016/0.035
		Blue	5	ZBVG64	0.016/0.035
~ 230...240 (50/60 Hz)	White	5	ZBVM14	0.016/0.035	
	Green	5	ZBVM34	0.016/0.035	
	Red	5	ZBVM44	0.016/0.035	
	Orange	5	ZBVM54	0.016/0.035	
	Blue	5	ZBVM64	0.016/0.035	

Connecting cables and connector

Description	Number of connectors	Wire c. s. a. mm ² /AWG	Length Ø mm/in.	Sold in lots of	Unit reference	Weight kg/lb
Cables with connectors 2-pin, Ø 5.08 mm/0.200 in. pitch	1	0.75/19	500/ 19.685	8	APE1C2150	0.120/0.265
	2	0.75/19	500/ 19.685	8	APE1C2250	0.180/0.397
Spring terminal connector 2-pin, Ø 5.08 mm/0.200 in. pitch	–	0.2 to 0.5/ – 25 to 14		10	APE1PRE21	0.003/0.007

(1) It is not possible to fit an additional contact block on the back of these contact blocks.

PF514403



ZBY9130

DF539842




ZBY9160

Circular yellow legends for mushroom head pushbuttons


Diameter mm/in.	Conforming to standards	Marking on Yellow background	Sold in lots of	Unit Reference	Weight kg/lb
Used for "Emergency stop" function (1)					
90/3.543	EN/IEC 60204-1 and EN/ISO 13850	–	10	ZBY8140	0.008/0.018
		ARRET D'URGENCE	10	ZBY8130	0.008/0.018
		EMERGENCY STOP	10	ZBY8330	0.008/0.018
		NOT-HALT	10	ZBY8230	0.008/0.018
		PARADA DE EMERGENCIA	10	ZBY8430	0.008/0.018
		ARRESTO DE EMERGENZA	10	ZBY8630	0.008/0.018
Used for "Emergency switching off" function					
60/2.362	EN/IEC 60204-1	–	10	ZBY9101	0.004/0.009
		COUPURE D'URGENCE	10	ZBY9160	0.004/0.009
		EMERGENCY SWITCHING OFF	10	ZBY9360	0.004/0.009
		NOT-AUS	10	ZBY9260	0.004/0.009
		DESCONEXION DE EMERGENCIA	10	ZBY9460	0.004/0.009
		INTERRUZIONE DI EMERGENZA	10	ZBY9660	0.004/0.009
90/3.543	EN/IEC 60204-1	–	10	ZBY8101	0.008/0.018
		COUPURE D'URGENCE	10	ZBY8160	0.008/0.018
		EMERGENCY SWITCHING OFF	10	ZBY8360	0.008/0.018
		NOT-AUS	10	ZBY8260	0.008/0.018
		DESCONEXION DE EMERGENCIA	10	ZBY8460	0.008/0.018
		INTERRUZIONE DI EMERGENZA	10	ZBY8660	0.008/0.018

(1) For complying with EN/ISO 13850 standard, paragraph 4.4.6., Emergency Stop function logo  has been added.



Accessories for mushroom head pushbuttons


Description	Exclusive use with the following Ø 40 mm/1.575 in. trigger action pushbuttons	Color	Reference	Weight kg/lb
Padlocking kit (1) (2) For Emergency stop (3) and Emergency switching off function (4), (padlockable)	XB5AS844●, XB5AS944●, ZB5AS844, ZB5AS944●	Yellow	ZBZ3605	0.045/0.099
Metal guards For Emergency stop (3) function Padlockable (2)	XB5AT8●, XB5AS8●, XB5AS9●, ZB5AT8●, ZB5AS8●, ZB5AS9●	Chromium plated	ZBZ1600	0.046/0.101
		Black	ZBZ1602	0.046/0.101
		Red	ZBZ1604	0.046/0.101
		Blue	ZBZ1606	0.046/0.101



Description	Marking	Color	Reference	Weight kg/lb
Ø 60 mm/2.362 in. legend for padlocking device ZBZ3605 For Emergency stop function (3)	Without	Yellow	ZBY9140T	0.004/0.009
	ARRET D'URGENCE	Yellow	ZBY9130T	0.004/0.009
	EMERGENCY STOP	Yellow	ZBY9330T	0.004/0.009
	NOT-HALT	Yellow	ZBY9230T	0.004/0.009
Ø 60 mm/2.362 in. legend for padlocking device ZBZ3605 For Emergency switching off function (4)	Without	Yellow	ZBY9101T	0.004/0.009
	COUPURE D'URGENCE	Yellow	ZBY9160T	0.004/0.009
	EMERGENCY SWITCHING OFF	Yellow	ZBY9360T	0.004/0.009
	NOT-AUS	Yellow	ZBY9260T	0.004/0.009



Description	Marking	Color	Sold in lots of	Reference	Weight kg/lb
Ø 60 mm/2.362 in. legend for Emergency stop function	-	Yellow	5	ZBY9121	0.007/0.015
	EMERGENCY STOP	Yellow	5	ZBY9320	0.007/0.015
	ARRET D'URGENCE	Yellow	5	ZBY9120	0.007/0.015
	NOT HALT	Yellow	5	ZBY9220	0.007/0.015
	PARADA DE EMERGENCIA	Yellow	5	ZBY9420	0.007/0.015
	ARRESTO DI EMERGENZA	Yellow	5	ZBY9620	0.007/0.015



Other accessories

Description	For use with	Color	Reference	Weight kg/lb
Plastic guard	Selector switches and key switches	Black	ZBZ2102	0.005/0.011
Padlockable flaps	Pushbuttons	Black	ZB4BZ62	0.076/0.168
		Red	ZB4BZ64	0.076/0.168
		Yellow	ZB4BZ65	0.076/0.168
		Blue	ZB4BZ66	0.076/0.168



(1) Standard circular legends are not compatible with this product. Use special legends **ZBY9●●●T**.

(2) No isolation function is possible when this guard is fitted.

(3) Ensures conformity with standards EN/IEC 60204-1 and EN/ISO 13850.

(4) Ensures conformity with standard EN/IEC 60204-1.






(5) Only when mounted on control stations. Use legends **ZBY9●●●T**.

PF100411



XB7NS842

Emergency stop and emergency switching off function with mechanical latching

Shape of head	Type of push	Standards			Sold in lots of	Unit reference	Weight kg/lb
Contacts for standard applications							
	Turn to release	EN/IEC 60204-1, EN/ISO 13850, EN/IEC 60947-5-5, Machinery directive 2006/42/EC and UL	–	1	10	XB7NS8442	0.045/0.099
			1	1	10	XB7NS8445	0.045/0.099
			–	2	10	XB7NS8444	0.045/0.099
	Push-pull		–	1	10	XB7NT842	0.040/0.088
			1	1	10	XB7NT845	0.040/0.088
			–	2	10	XB7NT844	0.040/0.088
	Key release (n° 455)		–	2	10	XB7NS9444	0.072/0.159
			–	1	10	XB7NS9445	0.072/0.159

Circular legends, yellow, for mushroom head pushbuttons

Description	Marking on yellow background	Sold in lots of	Unit reference	Weight kg/lb
Used for "Emergency stop" function (1)				
Ø 60 mm/2.362 in. circular legend compatible with Emergency stop	–	5	ZBY9121	0.007/0.015
	ARRET D'URGENCE	5	ZBY9320	0.007/0.015
	EMERGENCY STOP	5	ZBY9120	0.007/0.015
	NOT-HALT	5	ZBY9220	0.007/0.015
	PARADA DE EMERGENCIA	5	ZBY9420	0.007/0.015
	ARRESTO DE EMERGENZA	5	ZBY9620	0.007/0.015
Ø 90 mm/3.543 in. circular legend compatible with Emergency stop	–	10	ZBY8140	0.008/0.018
	ARRET D'URGENCE	10	ZBY8130	0.008/0.018
	EMERGENCY STOP	10	ZBY8330	0.008/0.018
	NOT-HALT	10	ZBY8230	0.008/0.018
	PARADA DE EMERGENCIA	10	ZBY8430	0.008/0.018
	ARRESTO DE EMERGENZA	10	ZBY8630	0.008/0.018

PF514403



ZBY9130

(1) For compliance with standard EN/ISO 13850, paragraph 4.4.6, the Emergency stop logo  has been added.

Control units Ø 30

Harmony 9001K & SK range

Emergency stop pushbuttons

Presentation

The Ø 30 mm / 1.181 in. Harmony 9001 range of Emergency stop and Emergency switching off functions is robust and meet a great number of applications in heavy industries such as: petrochemical, metallurgy, mining, oil and gas, wastewater treatment, and automobile manufacturing.

- Two family of products are available :
 - The Harmony 9001K control and signalling units offering good robustness with a chromium plated metal bezel
 - The Harmony 9001SK control and signalling units, with a double insulated bezel designed for applications requiring a high resistance to corrosion
- This range includes:
 - Emergency stop trigger action and mechanical latching pushbuttons (conforming to standards EN/IEC 60204-1 and EN/ISO 13850)
 - Choice of accessories and spare parts common to both families,
 - Choice of aluminium or plastic legend plates.

Installation

- Harmony 9001 products are both simple and quick to install:
 - Block setting by single installer with a single screw contact block,
 - Automatic self-grounding operators without additional wiring,
 - Easy function identification thanks to the coloured contact blocks,
 - Clear window for status of contact operation and troubleshooting,
 - Side-by-side and/or stacked mounting of contact blocks to minimize enclosure space requirements.
- Connection is made through screw clamp terminals (cross headed slotted screw)

Environment

The performance features of these range meet the most demanding international standards and approvals:

- Degrees of protection:

Products are originally oil-tight, dust-tight and water-tight. No boot needs to be added.

 - For 9001K chromium plated metal bezel: IP 66 according to IEC 61140 and NEMA type 1, 2, 3, 3R, 4, 12 and 13
 - For 9001SK plastic bezel: IP 66 according to IEC 61140 and NEMA type 1, 2, 3, 3R, 4, 4X, 12 et 13.
- International standards:
 - EN/IEC 60204/1 et EN/ISO 13850 for Emergency stop mushroom head pushbuttons (if used with the Emergency stop legend plates)
- Product certifications:
 - International certifications: UL, CSA, NOM, RoHS, GOST

Control units Ø 30

Harmony 9001K & SK range


Emergency stop pushbuttons, contact blocks, and circular yellow legends




9001KR16H13



9001SKR16H13



9001KA1



9001 KN330

Emergency stop mushroom head pushbutton (with chromium plated metal bezel)

Shape of head	Type of push	Head color & material	Type of contacts			Reference	Weight kg/lb
			N/O	N/C	C/O		
Circular, Ø 40 mm / 1.575 in.	2 positions (1) Turn to Release Trigger action	Red, plastic	1	1	–	9001KR16H13	0.141/0.311
			2	2	–	9001KR16H2	0.141/0.311
			–	–	–	9001KR16 (2)	0.141/0.311

Emergency stop mushroom head pushbutton (with double insulated bezel)

Circular, Ø 40 mm / 1.575 in.	2 positions Turn to release Trigger action (1)	1	1	–	9001SKR16H13	0.141/0.311
		2	2	–	9001SKR16H2	0.141/0.311
		–	–	–	9001SKR16 (2)	0.141/0.311

Contact blocks with protected terminals

Description	Type of contacts			Reference	Weight kg/lb
	N/O	N/C	C/O		
Standard contact blocks	–	–	1	9001KA1 (3)	0.027/0.060
	1	–	–	9001KA2 (3)	0.023/0.051
	–	1	–	9001KA3 (3)	0.023/0.051
Late break contact blocks	–	–	1	9001KA4	0.027/0.060
	–	1	–	9001KA5	0.023/0.051
Early break contact blocks	1	–	–	9001KA6	0.023/0.051
Logic reed contact blocks Hermetically sealed	1	–	–	9001KA41 (3)	0.045/0.099
	–	1	–	9001KA42 (3)	0.045/0.099
	–	–	1	9001KA43 (3)	0.045/0.099
Power reed contact blocks Hermetically sealed	1	–	1	9001KA51 (3)	0.045/0.099
	–	1	–	9001KA52 (3)	0.045/0.099
	–	–	1	9001KA53 (3)	0.045/0.099

Emergency stop legend plate (plastic)

Description	Legend plate colour	Marking	Reference	Weight kg/lb
Ø 60 mm / 2.362 in.	Yellow	EMERGENCY STOP	9001KN9330	0.005/0.011
Ø 90 mm / 3.543 in.	Yellow	EMERGENCY STOP	9001KN8330	0.005/0.011

(1) Emergency stop device, conforms to EN/IEC 60204-1 and EN/ISO 13850 when used with Emergency Stop legend plate 9001KN8330 or 9001KN9330.

(2) Supplied without contact block. Contact blocks to be ordered separately.

(3) It is possible to mount up to 3 levels of contact blocks (maximum of 6 contacts blocks) on 9001 K and 9001 SK references. For additional contact blocks to be installed by the customer, please refer to Schneider Electric website, Harmony 9001K and Harmony 9001SK.

Operator dialogue terminals

Magelis™ XBTGH Advanced hand-held panel

Emergency stop function



Magelis XBTGH with emergency stop

Presentation

The Magelis XBTGH Advanced hand-held panel offer a portable touch screen terminal with 5.7" color screen and safety devices (Emergency stop, enabling grip switch, etc.)


The emergency stop button with 2 NC safety contacts and 1 NO auxiliary contact is used to stop the machine during emergency.

Operation

These terminals are available in multifunction levels (5.7") which features new information and communication technologies:

- High level of communication (embedded Ethernet, multi-link, Web server and FTP)
- External storage of data (Compact Flash memory card and USB memory stick) for storing production data and backing up applications
- Multimedia data with integrated image and sound management (digital or analog camera)
- Management of peripherals: Printers, bar code readers, loudspeakers, etc.

Communication



Magelis Standard Advanced panel communicate with PLCs via one or two integrated serial links, using communication protocols:

- Schneider Electric (Uni-TE, Modbus)
- Third-party: Mitsubishi Electric, Omron, Allen-Bradley and Siemens

Operator dialogue terminals

Magelis XBTGH Advanced hand-held panel

Emergency stop function



XBTGH2460



XBTZGJBOX



XBTZGHL●●

XBTGH Advanced hand-held panel ⁽¹⁾

Type of front panel	Number of ports	Application memory capacity	Compact Flash memory	Video input	Number of Ethernet ports	Reference	Weight kg/lb
Multifunction, 5.7" screen							
TFT color mode screen and Emergency stop button	1 COM1 1 USB	32 MB	Yes	No	1	XBTGH2460 (2)	–

Connection components

Description	Usage	Length m/ft.	Reference	Weight kg/lb
Junction box for XBTGH	Specifically for the XBTGH terminal, it enables: <ul style="list-style-type: none"> ■ 24 V $\overline{\text{DC}}$ power supply to XBTGH terminal ■ Connection of various safety inputs/outputs ■ Connection on multi-protocol serial link (9-way SUB-D) or Ethernet TCP/IP (RJ45) Can be mounted on 35 mm U_r rail	–	XBTZGJBOX (2) (3)	–
Interface cable for XBTGH	For connecting XBTGH terminal to junction box XBTZGJBOX	3/9.84	XBTZGHL3	–
		5/16.40	XBTZGHL5	–
		10/32.80	XBTZGHL10	–
		20/65.62	XBTZGHL20 (4)	–

(1) For more information on Magelis XBTGH functions, description and connection accessories, please refer to Magelis XBTGH Advanced hand-held panel catalog in our website www.schneider-electric.com.

(2) The XBTGH terminal is connected to junction box XBTZGJBOX using cable XBTZGHL●●, to be ordered separately.

(3) A junction box is required at each XBTGH terminal connection point.

(4) With this cable, the following limitations apply to the junction box:

- no RS 232C serial link
- an isolation box cannot be used
- 24 V $\overline{\text{DC}}$ supply voltage tolerance of approximately 10%

9									
9001KA1	3	XBY2U	5	ZB5AS944D	12	ZBE101	5	ZBV5B	6
9001KA2	3		7	ZB5AS964	12		14		15
9001KA3	3		8	ZB5AT82Y	13	ZBE102	5	ZBV18B1	6
9001KA4	3		14	ZB5AT84	12		14		15
9001KA5	3		16	ZB5AT844	12	ZBE201	5	ZBV18B3	6
9001KA6	3		17	ZB5AT8643M	12		14		15
9001KA41	3	Z		ZB5AW743	12	ZBE202	5	ZBV18B4	6
9001KA42	3	ZB2BE101	5	ZB5AX84	12		14		15
9001KA43	3		14	ZB5AZ009	14	ZBE203	5	ZBV18B5	6
9001KA51	3	ZB2BE102	5		16		14		15
9001KA52	3		14	ZB5AZ101	14	ZBE204	5	ZBV18B6	6
9001KA53	3	ZB4BS834	3		18		14		15
9001KN8330	3	ZB4BS844	3	ZB5AZ102	14	ZBE205	5	ZBV18G1	6
9001KN9330	3	ZB4BS864	3	ZB5AZ103	14		14		15
9001KR16	3	ZB4BS934	3	ZB5AZ104	14	ZBE501	5	ZBV18G3	6
9001KR16H2	3	ZB4BS944	3	ZB5AZ105	14		14		15
9001KR16H13	3	ZB4BS964	3	ZB5AZ114	14	ZBE502	5	ZBV18G4	6
9001SKR16	3	ZB4BT84	3	ZB5AZ1013	17		14		15
9001SKR16H2	3	ZB4BT844	3	ZB5AZ1014	18	ZBE503	5	ZBV18G5	6
9001SKR16H13	3	ZB4BVG35	7	ZB5AZ1015	16		14		15
		ZB4BVG45	7	ZB5AZ1023	17	ZBE504	5	ZBV18G6	6
		ZB4BW643	3	ZB5AZ1024	18		14		15
		ZB4BX84	3	ZB5AZ1025	16	ZBE505	5	ZBV18M1	6
		ZB4BZ009	5	ZB5AZ1033	17		14		15
			7	ZB5AZ1034	18	ZBE1013	8	ZBV18M3	6
			9	ZB5AZ1035	16		17		15
			11	ZB5AZ1043	17	ZBE1014	9	ZBV18M4	6
			20	ZB5AZ1044	18		18		15
		ZB4BZ62	11	ZB5AZ1045	16	ZBE1015	7	ZBV18M5	6
			20	ZB5AZ1053	17		16		15
		ZB4BZ64	11	ZB5AZ1054	18	ZBE1016	5	ZBV18M6	6
			20	ZB5AZ1055	16		14		15
		ZB4BZ65	11	ZB5AZ1414	18	ZBE1016P	5	ZBVB1	6
			20	ZB6AS834	4		14		15
		ZB4BZ66	11	ZB6AS934	4	ZBE1016P3	8	ZBVB3	6
			20	ZB6Y002	5		17		15
		ZB4BZ101	5	ZB6Y003	5	ZBE1023	8	ZBVB4	6
		ZB4BZ102	5	ZB6Y004	5		17		15
		ZB4BZ103	5	ZB6Y005	5	ZBE1024	9	ZBVB5	6
		ZB4BZ104	5	ZB6Y006	5		18		15
		ZB4BZ105	5	ZB6Y006A	5	ZBE1025	7	ZBVB6	6
		ZB4BZ106	5	ZB6Y009	5		16		15
		ZB4BZ107	5	ZB6Y010	5	ZBE1026	5	ZBVB14	9
		ZB4BZ107	14	ZB6Y011	5		14		18
		ZB4BZ114	5	ZB6Y016	5	ZBE1026P	5	ZBVB15	7
		ZB4BZ1013	8	ZB6Y018	5		14		16
		ZB4BZ1014	9	ZB6Y019	5	ZBE1026P3	8	ZBVB34	9
		ZB4BZ1015	7	ZB6Y56	3		17		18
		ZB4BZ1023	8	ZB6Y905	5	ZBE2013	8	ZBVB35	7
		ZB4BZ1024	9	ZB6Y906	5		17		16
		ZB4BZ1025	7	ZB6Y7001	4	ZBE2023	8	ZBVB44	9
		ZB4BZ1033	8	ZB6Y7130	4		17		18
		ZB4BZ1034	9	ZB6Y7230	4	ZBE2033	8	ZBVB45	7
		ZB4BZ1035	7	ZB6Y7330	4		17		16
		ZB4BZ1043	8	ZB6Y7430	4	ZBE2043	8	ZBVB54	9
		ZB4BZ1044	9	ZB6Y7630	4		17		18
		ZB4BZ1045	7	ZB6Z1B	5	ZBE2053	8	ZBVB55	7
		ZB4BZ1053	8	ZB6Z2B	5		17		16
		ZB4BZ1054	9	ZB6Z3B	5	ZBE2013	8	ZBVB64	9
		ZB4BZ1055	7	ZB6Z4B	5		17		18
		ZB4BZ1414	9	ZB6Z5B	5	ZBE5013	8	ZBVB65	7
		ZB5AS834	12				17		16
		ZB5AS842Y	13			ZBE5023	8	ZBVB66	7
		ZB5AS844	12				17		16
		ZB5AS934	12			ZBE5033	8	ZBVBG1	6
		ZB5AS942Y	13				17		15
		ZB5AS944	12			ZBE5043	8	ZBVBG3	6
							17		15
						ZBE5053	8	ZBVBG4	6
							17		15
						ZBE10163	8	ZBVBG5	6
							17		15
						ZBE10263	8	ZBVBG6	6
							17		15

ZBVG1	6	ZBVM54	9	ZBY9220	4
	15		18		11
ZBVG3	6	ZBVM55	7		13
	15		16		20
ZBVG4	6	ZBVM64	9	ZBY9230T	11
	15		18		20
ZBVG5	6	ZBVM65	7	ZBY9260	10
	15		16		19
ZBVG6	6	ZBY001	5	ZBY9260T	11
	15		7		20
ZBVG14	9		8	ZBY9320	4
	18		14		11
ZBVG15	7		16		13
	16		17		20
ZBVG34	9	ZBY8101	10		21
	18		19	ZBY9330T	11
ZBVG35	7	ZBY8130	10		20
	16		19	ZBY9360	10
ZBVG44	9		21		19
	18	ZBY8140	10	ZBY9360T	11
ZBVG45	7		21		20
	16	ZBY8160	10	ZBY9420	4
ZBVG54	9		19		11
	18	ZBY8230	10		13
ZBVG55	7		19		20
	16		21		21
ZBVG64	9	ZBY8260	10	ZBY9460	10
	18		19		19
ZBVG65	7	ZBY8330	10	ZBY9620	4
	16		19		11
ZBVJ1	6		21		13
	15	ZBY8360	10		20
ZBVJ3	6		19	ZBY9660	10
	15	ZBY8430	10		19
ZBVJ4	6		19	ZBZ001	5
	15		21		8
ZBVJ5	6	ZBY8460	10		14
	15		19		17
ZBVJ6	6	ZBY8630	10	ZBZ28	4
	15		19		13
ZBVJ15	7		21	ZBZ58	4
	16	ZBY8660	10		13
ZBVJ35	7		19	ZBZ1600	11
	16	ZBY9101	10		20
ZBVJ45	7		19	ZBZ1602	11
	16	ZBY9101T	11		20
ZBVJ55	7		20	ZBZ1604	11
	16	ZBY9120	4		20
ZBVJ65	7		11	ZBZ1606	11
	16		13		20
ZBVM1	6		20	ZBZ2102	11
	15	ZBY9121	8		20
ZBVM3	6		15	ZBZ3605	11
	15		17		20
ZBVM4	6		24	ZBZG156	6
	15		25		15
ZBVM5	6	ZBY91215	4	ZBZVG	6
	15		11		15
ZBVM6	6		13	ZBZVM	6
	15		20		15
ZBVM14	9		21		
	18	ZBY9130T	11		
ZBVM15	7		20		
	16	ZBY9140T	11		
ZBVM34	9		20		
	18	ZBY9160	10		
ZBVM35	7		19		
	16	ZBY9160T	11		
ZBVM44	9		20		
	18				
ZBVM45	7				
	16				

Schneider Electric Industries SAS

Head Office
35, rue Joseph Monier
F-92500 Rueil-Malmaison
France

www.schneider-electric.com/control

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Design: Schneider Electric
Photos: Schneider Electric