

4850, 4-pole, Socket, PCB terminals, DIN Plug/Socket



### Description


- PCB Mounting
- DIN Plug: 4-pole , straight

### Technical Data

Diameter	9.0 mm	Allowable Operation Temperature	-20°C to 70°C
Number of Poles	4-pole	Terminal	PCB terminals silver plated
Ratings DC	2 A / 12VDC	Lifetime	5000 Insertions
Ratings AC	1 A / 100VAC		
Dielectric Strength	250 VAC		
Insulation Resistance	> 50 MΩ @ 250VDC		
Material: Housing	Thermoplastic, black, UL 94V-0		

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [General Product Information](#)

### Dimensions [mm]



### All Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
DIN Plug/Socket	9.0	4-pole	PCB terminals	4850.2410

Most Popular.

Availability for all products can be searched real-time: <http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging unit 750 Pcs

## Mating Inlets/Plugs

### Category / Description



[DIN Plug/Socket Overview complete](#)

4850, 4-pole, Plug, solder terminal, DIN Plug/Socket

4850.1410

[DIN Plug/Socket further types to 4850.2410](#)