



## RP-B10 POS Printer

Reliability in high volume point-of-sale and hospitality environments is critical. Hardware failures have an immediate business impact, reducing revenue, lowering employee productivity, and creating unhappy customers.

The Seiko Instruments RP-B10 direct thermal receipt printer is ideal for the demanding workload of POS applications. Designed for durability, this heavy-duty printer rises to the challenge of high-volume print applications, yet is economical, simple to operate, and easy to integrate.

### Reliability You Can Count On:

Avoid downtime and gain peace of mind. The precision engineered RP-B10 receipt printer is rigorously tested to perform day in and day out in punishing high-volume point-of-sale environments. The printer is exceptionally durable, with the service life rated for a minimum 62 miles (100 km) total printing and 1.5 million cuts, and an MTBF rating of 360,000 hours.

### Exceptional Value:

Accelerate return on investment. The highly economical RP-B10 receipt printer packs tremendous value, making it the superior alternative for point-of-sale receipt printing.

### Seamless Integration and Ease of Use:

Get up and running quickly. The RP-B10 receipt printer speeds integration with included printer drivers and a software development kit. An array of utilities enables you to rapidly configure the printer, add a logo or coupons, print in grayscale, add a watermark, monitor the unit, and more.

A small footprint design enables the RP-B10 receipt printer to fit in tight spaces and free up valuable real estate. Countertop, vertical, and wall-mounting options provide deployment flexibility. An intuitive LED readout gives immediate notification of printer status.



The RP-B10, with EZ-OP drop-in paper replacement, is available in onyx black and ice white.

### Product Highlights

- Up to 200 mm/second print speed
- Heavy-duty design: minimum 62 miles of printing, 1.5 million cuts
- Small footprint with flexible mounting options
- Exceptional value delivering immediate ROI
- 3-year worry-free warranty



Seiko Instruments USA Inc.  
Thermal Printer Division  
2990 Lomita Blvd., Torrance, CA 90505  
Telephone (310) 517-7778  
Facsimile (310) 517-8154  
Email: [printerinfo@siu-la.com](mailto:printerinfo@siu-la.com)  
[www.siiprinters.com](http://www.siiprinters.com)



Model		RP-B10
Printing	Method	Direct thermal
	No. dots/line	576
	Resolution (dots/mm)	8
	Paper width (mm)	58/80
	Printing width (mm)	54/72
	Speed (max. mm/sec)	200
	Outside diameter of paper roll max (mm)	ø83
	Inside diameter of paper roll max (mm)	ø12
	Character matrix (HxW dots)	24 x 12, 24 x 24, 16 x 8, 16 x 16
	Character size (HxW mm)	3.0 x 1.5, 3.0 x 3.0, 2.0 x 1.0, 2.0 x 2.0
Type of Paper	Roll paper	
Character type	Code page: 11pages, Downloaded character, User-defined character JIS 1&2 Level Kanji	
Bar codes	UPC-A/E, JAN(EAN)8/13, ITF, CODABAR, Code39, Code93, Code128, QR, PDF417	
Power supply (V)	Specified AC adapter, External power (DC24±5%)	
Interface	RS-232C, USB	
Input buffer	10K bytes	
Commands	ESC/POST™ * conformity	
Auto-cutter	Heavy duty slide type with partial-cut option	
Operating temperature (°C)	5 to 45	
Service life	Abrasian resistance (km)	100**
	Auto-cutter	1,500,000 cuts
	MTBF	360,000 hours
Dimensions (WxDxH mm)	150.0 x 185.0 x 139.5***	
Mass (g)	Approx. 1300	
Compliance	FCC, CE, VCCI	
Accessories	AC adapter, AC cable, wall mounting kit, vertical mounting kit	
Cash drawer	2 drivers (24V / 1A)	
Body color	2 models: Onyx black, ice white	
Drivers	Windows®, OPOS**** (For Windows® XP/Vista)	
SDK*****	Status API, Devmode API (For Win32 API/ .net API)	
Utilities	Memory switch setting LOG management USB serial ID setting Non-volatile image registration Code page registration	

\* ESC/POS™: Registered trademark of SEIKO EPSON CORP.

\*\* Use recommended thermal paper.

\*\*\* Excluding protrusion.

\*\*\*\* OLE POS drivers.

\*\*\*\*\* The Windows® API, informally WinAPI, is Microsoft's core set of application programming interfaces (APIs) available in the Microsoft Windows® operating systems. The Win32 API is for Windows® operating system on a 32-bit processor. The .net API is for the .net framework on Windows® operating system.

Windows® is a registered trademark of Microsoft Corporation(USA).

Specifications subject to change without notice.