



Metal thin film chip resistors (precision)

RR series

Features

- Excellent characteristics in resistance tolerance, temperature coefficient of resistance, current noise, and linearity

Applications

- Any electronics applications that require accuracy and reliability such as automotive electronics, industrial test and measurement, consumer electronics and many others.

Specifications

* Stocked items: E-24 series (TCR P and Q, resistance tolerance D), other E-24 and E-96 series are made to order.

Dimensions



unit : mm

Dimension (inch)	RR0306 (0201)	RR0510 (0402)	RR0816 (0603)	RR1220 (0805)	RR1632 (1206)	RR2632 (1210)
L	0.60±0.05	1.00±0.05	1.60±0.20	2.00±0.20	3.20±0.20	3.20±0.20
W	0.30±0.05	0.50±0.05	0.80±0.20	1.25±0.20	1.60±0.20	2.60±0.20
A	0.12±0.05	0.20±0.10	0.30±0.20	0.40±0.20	0.50±0.20	0.50±0.20
B	0.12±0.05	0.25±0.05	0.30±0.20	0.40±0.20	0.45±0.20	0.45±0.20
T	0.23±0.03	0.35±0.05	0.40±0.10	0.40±0.10	0.40±0.10	0.40±0.10

Electrical characteristics

Series name	RR0306		RR0510		RR0816		RR1220		RR1632		RR2632			
power	1/20W		1/16W		1/16W		1/10W		1/8W		1/4W			
E series offered	E-24				E-24, E-96									
Resistance range (Ω)	10~30	33~22k	10~91	100~100k	10~91	100~360k	10~91	100~1M	10~47	51~1M	100~200k	10~47	51~1M	100~200k
Resistance tolerance (%)	±0.1% (B)	—	—	—	—	—	—	—	—	—	○	—	—	○
	±0.5% (D)	—	○	○	○	○	○	○	○	○	—	○	○	—
	±1.0% (F)	○	—	—	—	—	—	—	—	—	—	—	—	—
Temperature coefficient of resistance (ppm/°C)	±5 (V)	—	—	—	—	—	—	—	—	—	○	—	—	○
	±10 (N)	—	—	—	—	—	—	—	—	—	○	—	—	○
	±25 (P)	—	○	—	○	—	○	—	○	—	○	—	○	○
	±50 (Q)	—	—	—	—	○	—	○	—	○	—	○	—	—
	±100 (R)	○	—	○	—	—	—	—	—	—	—	—	—	—
Maximum voltage	15V		25V		75V		100V		150V		200V			
Operating temperature	-55°C~125°C													
Packaging	5,000pcs	—	—	—	—	○	—	○	—	—	○	—	—	○
	10,000pcs	—	—	○	—	—	—	—	—	—	—	—	—	—

Contact us for the jumper resistor in RR0816 size (part number: RL0816-JMP)

Part numbering system

RR 0816 P - 102 - D - (M) - (T5) - (*)** — Only given to 3 digit codes for RR0816 E-96 series

