

## Glass Passivated Single-Phase Bridge Rectifier

### FEATURES

- Ideal for printed circuit board
- High case dielectric strength of 1500 VRMS
- High surge current capability
- Typical IR less than 0.1μA
- UL Recognized File # E-326243
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



### MECHANICAL DATA

**Case:** GBU


Molding compound, UL flammability classification rating 94V-0

Packing code with suffix "G" means green compound (halogen-free)

**Terminal:** Matte tin plated leads, solderable per JESD22-B102

**Polarity:** As marked

**Weight:** 4 g (approximately)



| MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T <sub>A</sub> =25°C unless otherwise noted)   |                                      |              |         |         |         |            |         |         |                  |      |
|--|--------------------------------------|--------------|---------|---------|---------|------------|---------|---------|------------------|------|
| PARAMETER  | SYMBOL                               | GBU 801      | GBU 802 | GBU 803 | GBU 804 | GBU 805    | GBU 806 | GBU 807 | UNIT             |      |
| Maximum repetitive peak reverse voltage  | V <sub>RRM</sub>                     | 50           | 100     | 200     | 400     | 600        | 800     | 1000    | V                |      |
| Maximum RMS voltage  | V <sub>RMS</sub>                     | 35           | 70      | 140     | 280     | 420        | 560     | 700     | V                |      |
| Maximum DC blocking voltage  | V <sub>DC</sub>                      | 50           | 100     | 200     | 400     | 600        | 800     | 1000    | V                |      |
| Maximum average forward rectified current  | I <sub>F(AV)</sub>                   | 8            |         |         |         |            |         |         | A                |      |
| Peak forward surge current, 8.3 ms single half sine-wave                                       | I <sub>FSM</sub>                     | 200          |         |         |         |            |         |         | A                |      |
| Rating of fusing ( t<8.3ms)  | I <sup>2</sup> t                     | 166          |         |         |         |            |         |         | A <sup>2</sup> s |      |
| Maximum Instantaneous Forward Voltage (Note 1)<br>I <sub>F</sub> = 4 A<br>I <sub>F</sub> = 8 A | V <sub>F</sub>                       |              |         |         |         | 1.0<br>1.1 |         |         |                  | V    |
| Maximum reverse current @ rated VR<br>T <sub>J</sub> =25 °C<br>T <sub>J</sub> =125 °C          | I <sub>R</sub>                       |              |         |         |         | 5<br>500   |         |         |                  | μA   |
| Typical junction capacitance per leg (Note 2)  | C <sub>j</sub>                       | 211          |         |         |         | 94         |         |         | pF               |      |
| Typical thermal resistance   | R <sub>θJC</sub><br>R <sub>θJA</sub> |              |         |         |         | 2<br>21    |         |         |                  | °C/W |
| Operating junction temperature range   | T <sub>J</sub>                       | - 55 to +150 |         |         |         |            |         |         | °C               |      |
| Storage temperature range  | T <sub>STG</sub>                     | - 55 to +150 |         |         |         |            |         |         | °C               |      |

Note 1: Pulse test with PW=300μs, 1% duty cycle

Note 2: Measured at 1MHz and applied Reverse bias of 4.0V DC

| ORDERING INFORMATION |              |                     |         |           |
|----------------------|--------------|---------------------|---------|-----------|
| PART NO.             | PACKING CODE | PACKING CODE SUFFIX | PACKAGE | PACKING   |
| GBU80x<br>(Note 1)   | C2           | G                   | GBU     | 20 / Tube |
|                      | D2           |                     |         | 20 / Tube |
|                      | X0           |                     |         | Forming   |

Note 1: "x" defines voltage from 50V (GBU801) to 1000V (GBU807)

| EXAMPLE       |          |              |                     |                |
|---------------|----------|--------------|---------------------|----------------|
| PREFERRED P/N | PART NO. | PACKING CODE | PACKING CODE SUFFIX | DESCRIPTION    |
| GBU806 C2     | GBU806   | C2           |                     |                |
| GBU806 C2G    | GBU806   | C2           | G                   | Green compound |

**RATINGS AND CHARACTERISTICS CURVES**

( $T_A=25^\circ\text{C}$  unless otherwise noted)

FIG. 1- MAXIMUM DERATING CURVE FOR OUTPUT CURRENT




FIG. 2- MAXIMUM FORWARD SURGE CURRENT PER LEG



FIG. 3- TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG. 4- TYPICAL FORWARD CHARACTERISTICS PER LEG






FIG. 5- TYPICAL JUNCTION CAPACITANCE PER LEG




PACKAGE OUTLINE DIMENSIONS

**GBU**



| DIM. | Unit (mm) |       | Unit (inch) |       |
|------|-----------|-------|-------------|-------|
|      | Min       | Max   | Min         | Max   |
| A    | 21.80     | 22.30 | 0.858       | 0.878 |
| B    | 3.50      | 4.10  | 0.138       | 0.161 |
| C    | 7.40      | 7.90  | 0.291       | 0.311 |
| D    | 1.65      | 2.16  | 0.065       | 0.085 |
| E    | 2.16      | 2.54  | 0.085       | 0.100 |
| F    | 1.65      | 2.03  | 0.065       | 0.080 |
| G    | 1.52      | 2.03  | 0.060       | 0.080 |
| H    | 1.02      | 1.27  | 0.040       | 0.050 |
| I    | 4.83      | 5.33  | 0.190       | 0.210 |
| J    | 3.30      | 3.56  | 0.130       | 0.140 |
| K    | 18.30     | 18.80 | 0.720       | 0.740 |
| L    | 17.50     | 18.00 | 0.689       | 0.709 |
| M    | 1.90      | 2.16  | 0.075       | 0.085 |
| N    | 0.46      | 0.56  | 0.018       | 0.022 |

MARKING DIAGRAM



- P/N = Specific Device Code
- G = Green Compound
- YW = Date Code
- F = Factory Code

## Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.