



MULTILAYER CERAMIC CHIP CAPACITORS

CKG Series Commercial Grade MEGACAP Type

Type:

CKG32K [EIA CC1210]
CKG45K [EIA CC1812]
CKG45N [EIA CC1812]
CKG57K [EIA CC2220]
CKG57N [EIA CC2220]

Issue date:
Dec 2014



REMINDERS

Please read before using this product

SAFETY REMINDERS



REMINDERS

1. If you intend to use a product listed in this catalog for a purpose that may cause loss of life or other damage, you must contact our company's sales window.
2. We may modify products or discontinue production of a product listed in this catalog without prior notification.
3. We provide "Delivery Specification" that explain precautions for the specifications and safety of each product listed in this catalog. We strongly recommend that you exchange these delivery specifications with customers that use one of these products.
4. If you plan to export a product listed in this catalog, keep in mind that it may be a restricted item according to the "Foreign Exchange and Foreign Trade Control Law". In such cases, it is necessary to acquire export permission in harmony with this law.
5. Any reproduction or transferring of the contents of this catalog is prohibited without prior permission from our company.
6. We are not responsible for problems that occur related to the intellectual property rights or other rights of our company or a third party when you use a product listed in this catalog. We do not grant license of these rights.
7. This catalog only applies to products purchased through our company or one of our company's official agencies. This catalog does not apply to products that are purchased through other third parties.

Notice: Effective January 2013, TDK will use a new catalog number which adds product thickness and packaging specification detail. This new catalog number should be referenced on all catalog orders going forward, and is not applicable for OEM part number orders. Please be aware the last five digits of the catalog number will differ from the item description (internal control number) on the product label. Contact your local TDK Sales representative for more information.

(Example)

Catalog Issued date	Catalog Number	Item Description (On Delivery Label)
Prior to January 2013	C1608C0G1E103J	C1608C0G1E103JT000N
January 2013 and Later	C1608C0G1E103J080AA	C1608C0G1E103JT000N



CKG Series MEGACAP Type

Type: CKG32K [EIA CC1210], CKG45K [EIA CC1812],
CKG45N [EIA CC1812], CKG57K [EIA CC2220], CKG57N [EIA CC2220]

Features




- Twice the capacitance on single capacitor foot print.
- Lower ESR and ESL than Al caps.
- Capable of absorbing thermal and mechanical stress.
- Improved vibration performance.

Applications




- Automotive application (EPS, ABS, EV, HEV, LED lighting etc.)
- Smoothing circuits
- DC-DC converters
- LED, HID applications
- Temperature variable applications
- Piezoelectric-effect countermeasure

Design Structure



No.	NAME	MATERIAL
		Class 2
(1)	Ceramic Dielectric	BaTiO ₃
(2)	Internal Electrode	Nickel (Ni)
(3)		Copper (Cu)
(4)	Termination	Nickel (Ni)
(5)		Tin (Sn)
(6)	Metal Cap Joint	High Temp Solder
(7)	Metal Cap	42 Alloy

Shape & Dimensions



Single Type	
L	Body Length
W	Body Width
T	Body Height
E	Metal Terminal Width

Stacked Type	
L	Body Length
W	Body Width
T	Body Height
E	Metal Terminal Width



Catalog Number Construction

CKG • 57 • N • X7S • 1C • 107 • M • 500 • J • H

Series Name

Dimensions L x W (mm)

Code	Length	Width	Metal Terminal
32	3.60 ± 0.30	2.60 ± 0.30	0.80 ± 0.15
45	5.00 ± 0.50	3.50 ± 0.50	1.10 ± 0.30
57	6.00 ± 0.50	5.00 ± 0.50	1.60 ± 0.30

Structure

Code	Description
K	Single Type
N	Stacked Type

Temperature Characteristics

Temperature Characteristics	Capacitance Change	Temperature Range
X5R	± 15%	-55 to +85°C
X7R	± 15%	-55 to +125°C
X7S	± 22%	-55 to +125°C
X7T	+ 22/-33%	-55 to +125°C

Rated Voltage (DC)

Code	Voltage (DC)
1C	16V
1E	25V
1H	50V
2A	100V
2E	250V
2W	450V
2J	630V

Nominal Capacitance (pF)

The capacitance is expressed in three digit codes and in units of pico Farads (pF). The first and second digits identify the first and second significant figures of the capacitance. The third digit identifies the multiplier. R designates a decimal point.

Ex. 0R2 = 0.2pF; 103 = 10,000pF; 105 = 1,000,000pF = 1,000nF = 1μF

Capacitance Tolerance

Code	Tolerance
K	± 10%
M	± 20%

Nominal Thickness

Code	Thickness
290	2.90 mm
335	3.35 mm
500	5.00 mm

Packaging Style

Code	Style
A	178 mm Reel, 4 mm Pitch
J	330 mm Reel, 8 mm Pitch

Special Reserved Code

Code	Description
H	MEGACAP (Std)



Capacitance Range Chart

CKG32K [EIA CC1210]

Capacitance Range Chart

Temperature Characteristics: X7R ($\pm 15\%$), X7S ($\pm 22\%$), X7T (+22/-33%)
 Rated Voltage: 630V (2J), 400V (2W), 250V (2E), 100V (2A), 50V (1H), 25V (1E)

Capacitance (pF)	Code	Tolerance	X7R					X7S		X7T		
			2J (630V)	2E (250V)	2A (100V)	1H (50V)	1E (25V)	2A (100V)	1H (50V)	2J (630V)	2W (450V)	2E (250V)
47,000	473	K: $\pm 10\%$ M: $\pm 20\%$	■									
100,000	104				■					■		
150,000	154									■		
220,000	224			■							■	
330,000	334											■
470,000	474				■							
1,000,000	105				■	■						
2,200,000	225							■				
3,300,000	335								■			
4,700,000	475							■	■			
6,800,000	685									■		
10,000,000	106							■				

Standard Thickness

■ 3.35 mm



Capacitance Range Chart

CKG45K [EIA CC1812]

Capacitance Range Chart

Temperature Characteristics: X7R ($\pm 15\%$), X7S ($\pm 22\%$), X7T (+22/-33%)
 Rated Voltage: 630V (2J), 450V (2W), 250V (2E), 100V (2A), 50V (1H), 25V (1E), 16V (1C)

Capacitance (pF)	Code	Tolerance	X7R						X7S			X7T		
			2J (630V)	2E (250V)	2A (100V)	1H (50V)	1E (25V)	1C (16V)	2A (100V)	1H (50V)	1C (16V)	2J (630V)	2W (450V)	2E (250V)
100,000	104	K: $\pm 10\%$ M: $\pm 20\%$	■											
150,000	154											■		
220,000	224			■								■		
330,000	334												■	
470,000	474			■										
680,000	684												■	
1,000,000	105				■									
1,500,000	155					■								
2,200,000	225						■							
3,300,000	335							■	■					
4,700,000	475									■				
10,000,000	106										■			
22,000,000	226											■		

Standard Thickness

■ 2.90 mm



Capacitance Range Chart

CKG57K [EIA CC2220]

Capacitance Range Chart

Temperature Characteristics: X7R ($\pm 15\%$), X7S ($\pm 22\%$), X7T (+22/-33%)

Rated Voltage: 630V (2J), 450V (2W), 250V (2E), 100V (2A), 50V (1H), 25V (1E), 16V (1C)

Capacitance (pF)	Code	Tolerance	X7R						X7S			X7T		
			2J (630V)	2E (250V)	2A (100V)	1H (50V)	1E (25V)	1C (16V)	2A (100V)	1H (50V)	1C (16V)	2J (630V)	2W (450V)	2E (250V)
220,000	224	K: $\pm 10\%$ M: $\pm 20\%$	■											
330,000	334											■		
470,000	474			■								■		
680,000	684												■	
1,000,000	105			■	■								■	
1,500,000	155												■	
2,200,000	225				■								■	
3,300,000	335												■	
4,700,000	475				■	■								
6,800,000	685								■	■				
10,000,000	106							■		■				
15,000,000	156								■					
22,000,000	226						■							
47,000,000	476										■			

Standard Thickness

■ 3.35 mm



Capacitance Range Chart

CKG45N [EIA CC1812]

Capacitance Range Chart

Temperature Characteristics: X5R ($\pm 15\%$), X7R ($\pm 15\%$), X7S ($\pm 22\%$), X7T ($+ 22/-33\%$)
 Rated Voltage: 630V (2J), 450V (2W), 250V (2E), 100V (2A), 50V (1H), 25V (1E), 16V (1C)

Capacitance (pF)	Code	Tolerance	X5R		X7R						
			1H (50V)	1C (16V)	2J (630V)	2E (250V)	2A (100V)	1H (50V)	1E (25V)	1C (16V)	
220,000	224	M: $\pm 20\%$			■						
470,000	474					■					
1,000,000	105						■				
2,200,000	225							■			
3,300,000	335								■		
4,700,000	475								■		
6,800,000	685									■	
10,000,000	106			■							■
22,000,000	226										■
47,000,000	476				■						

Capacitance (pF)	Code	Tolerance	X7S			X7T		
			2A (100V)	1H (50V)	1C (16V)	2J (630V)	2W (450V)	2E (250V)
330,000	334	M: $\pm 20\%$				■		
470,000	474						■	
680,000	684							■
1,000,000	105							■
1,500,000	155							■
2,200,000	225							■
6,800,000	685			■				
10,000,000	106				■			
22,000,000	226							
47,000,000	476					■		

Standard Thickness
 5.00 mm



Capacitance Range Chart

CKG57N [EIA CC2220]

Capacitance Range Chart

Temperature Characteristics: X5R ($\pm 15\%$), X7R ($\pm 15\%$), X7S ($\pm 22\%$), X7T ($+ 22/-33\%$)

Rated Voltage: 630V (2J), 450V (2W), 250V (2E), 100V (2A), 50V (1H), 25V (1E), 16V (1C)

Capacitance (pF)	Code	Tolerance	X5R				X7R					
			2A (100V)	1H (50V)	1E (25V)	1C (16V)	2J (630V)	2E (250V)	2A (100V)	1H (50V)	1E (25V)	1C (16V)
470,000	474	M: $\pm 20\%$					■					
1,000,000	105							■				
2,200,000	225								■			
4,700,000	475									■		
10,000,000	106		■							■		
22,000,000	226			■							■	
33,000,000	336											■
47,000,000	476					■						
100,000,000	107											■

Capacitance (pF)	Code	Tolerance	X7S				X7T		
			2A (100V)	1H (50V)	1E (25V)	1C (16V)	2J (630V)	2W (450V)	2E (250V)
680,000	684	M: $\pm 20\%$					■		
1,000,000	105							■	
1,500,000	155								■
2,200,000	225								
3,300,000	335								
22,000,000	226		■	■					
47,000,000	476				■				
100,000,000	107					■			

Standard Thickness
 5.00 mm



Capacitance Range Table

Class 2 (Temperature Stable)

Temperature Characteristics: X5R (-55 to +85°C, ±15%)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number			
				Rated Voltage Edc: 100V	Rated Voltage Edc: 50V	Rated Voltage Edc: 25V	Rated Voltage Edc: 16V
10 µF	4532	5.00 ± 0.50	± 20%		CKG45NX5R1H106M500JH		
	5750	5.00 ± 0.50	± 20%	CKG57NX5R2A106M500JH			
22 µF	5750	5.00 ± 0.50	± 20%		CKG57NX5R1H226M500JH		
47 µF	4532	5.00 ± 0.50	± 20%				CKG45NX5R1C476M500JH
	5750	5.00 ± 0.50	± 20%			CKG57NX5R1E476M500JH	
100 µF	5750	5.00 ± 0.50	± 20%				CKG57NX5R1C107M500JH

Class 2 (Temperature Stable)

Temperature Characteristics: X7R (-55 to +125°C, ±15%)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number			
				Rated Voltage Edc: 630V	Rated Voltage Edc: 250V	Rated Voltage Edc: 100V	Rated Voltage Edc: 50V
47 nF	3225	3.35 ± 0.10	± 10%	CKG32KX7R2J473K335AH			
			± 20%	CKG32KX7R2J473M335AH			
100 nF	3225	3.35 ± 0.10	± 10%		CKG32KX7R2E104K335AH		
			± 20%		CKG32KX7R2E104M335AH		
4532	2.90 ± 0.10	2.90 ± 0.10	± 10%	CKG45KX7R2J104K290JH			
			± 20%	CKG45KX7R2J104M290JH			
220 nF	3225	3.35 ± 0.10	± 10%		CKG32KX7R2E224K335AH		
			± 20%		CKG32KX7R2E224M335AH		
4532	2.90 ± 0.10	2.90 ± 0.10	± 10%	CKG45KX7R2E224K290JH			
			± 20%	CKG45KX7R2E224M290JH			
5750	3.35 ± 0.15	3.35 ± 0.15	± 10%	CKG45NX7R2J224M500JH			
			± 20%	CKG57KX7R2J224K335JH			
470 nF	3225	3.35 ± 0.10	± 10%			CKG32KX7R2A474K335AH	
			± 20%			CKG32KX7R2A474M335AH	
4532	2.90 ± 0.10	2.90 ± 0.10	± 10%		CKG45KX7R2E474K290JH		
			± 20%		CKG45KX7R2E474M290JH		
5750	3.35 ± 0.15	3.35 ± 0.15	± 10%		CKG45NX7R2E474M500JH		
			± 20%		CKG57KX7R2E474K335JH		
			± 20%	CKG57KX7R2E474M335JH			
			± 20%	CKG57NX7R2J474M500JH			
1 µF	3225	3.35 ± 0.10	± 10%			CKG32KX7R2A105K335AH	CKG32KX7R1H105K335AH
			± 20%			CKG32KX7R2A105M335AH	CKG32KX7R1H105M335AH
4532	2.90 ± 0.10	2.90 ± 0.10	± 10%			CKG45KX7R2A105K290JH	
			± 20%			CKG45KX7R2A105M290JH	
5750	3.35 ± 0.15	3.35 ± 0.15	± 10%		CKG45NX7R2E105M500JH		
			± 20%		CKG57KX7R2E105K335JH	CKG57KX7R2A105K335JH	
			± 20%		CKG57KX7R2E105M335JH	CKG57KX7R2A105M335JH	
			± 20%		CKG57NX7R2E105M500JH		
1.5 µF	4532	2.90 ± 0.10	± 10%				CKG45KX7R1H155K290JH
			± 20%				CKG45KX7R1H155M290JH
2.2 µF	3225	3.35 ± 0.10	± 10%			CKG32KX7R2A225K335AH	
			± 20%			CKG32KX7R2A225M335AH	
4532	2.90 ± 0.10	2.90 ± 0.10	± 10%			CKG45KX7R2A225K290JH	
			± 20%			CKG45KX7R2A225M290JH	
5750	3.35 ± 0.15	3.35 ± 0.15	± 10%			CKG45NX7R2A225M500JH	
			± 20%			CKG57KX7R2A225K335JH	
			± 20%		CKG57KX7R2A225M335JH	CKG57KX7R2A225M335JH	
			± 20%		CKG57NX7R2E225M500JH	CKG57NX7R2A225M500JH	
3.3 µF	4532	2.90 ± 0.10	± 10%				CKG45KX7R1H335K290JH
			± 20%				CKG45KX7R1H335M290JH
5750	3.35 ± 0.15	3.35 ± 0.15	± 10%				CKG45NX7R1H335M500JH
			± 20%				CKG57KX7R2A335K335JH
			± 20%			CKG57KX7R2A335M335JH	



Capacitance Range Table

Class 2 (Temperature Stable)

Temperature Characteristics: X7R (-55 to +125°C, ±15%)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number			
				Rated Voltage Edc: 100V	Rated Voltage Edc: 50V	Rated Voltage Edc: 25V	Rated Voltage Edc: 16V
4.7 μ F	3225	3.35 \pm 0.10	\pm 10%			CKG32KX7R1E475K335AH	
			\pm 20%			CKG32KX7R1E475M335AH	
	4532	2.90 \pm 0.10	\pm 10%			CKG45KX7R1E475K290JH	
			\pm 20%			CKG45KX7R1E475M290JH	
		5.00 \pm 0.50	\pm 20%	CKG45NX7R2A475M500JH			
	5750	3.35 \pm 0.15	\pm 10%	CKG57KX7R2A475K335JH	CKG57KX7R1H475K335JH		
\pm 20%			CKG57KX7R2A475M335JH	CKG57KX7R1H475M335JH			
	5.00 \pm 0.50	\pm 20%	CKG57NX7R2A475M500JH				
6.8 μ F	4532	5.00 \pm 0.50	\pm 20%		CKG45NX7R1H685M500JH		
10 μ F	3225	3.35 \pm 0.10	\pm 10%			CKG32KX7R1E106K335AH	
			\pm 20%			CKG32KX7R1E106M335AH	
	4532	2.90 \pm 0.10	\pm 10%				CKG45KX7R1C106K290JH
			\pm 20%				CKG45KX7R1C106M290JH
		5.00 \pm 0.50	\pm 20%			CKG45NX7R1E106M500JH	
	5750	3.35 \pm 0.15	\pm 10%			CKG57KX7R1E106K335JH	
\pm 20%					CKG57KX7R1E106M335JH		
	5.00 \pm 0.50	\pm 20%	CKG57NX7R2A106M500JH	CKG57NX7R1H106M500JH			
15 μ F	5750	3.35 \pm 0.15	\pm 20%				CKG57KX7R1C156M335JH
							CKG45KX7R1C226M290JH
22 μ F	4532	2.90 \pm 0.10	\pm 20%				CKG45NX7R1C226M500JH
	5750	3.35 \pm 0.15	\pm 20%			CKG57KX7R1E226M335JH	
			\pm 20%			CKG57NX7R1E226M500JH	
33 μ F	5750	5.00 \pm 0.50	\pm 20%				CKG57NX7R1C336M500JH

Class 2 (Temperature Stable)

Temperature Characteristics: X7S (-55 to +125°C, ±22%)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number			
				Rated Voltage Edc: 100V	Rated Voltage Edc: 50V	Rated Voltage Edc: 25V	Rated Voltage Edc: 16V
3.3 μ F	3225	3.35 \pm 0.10	\pm 10%	CKG32KX7S2A335K335AH			
			\pm 20%	CKG32KX7S2A335M335AH			
	4532	2.90 \pm 0.10	\pm 10%	CKG45KX7S2A335K290JH			
			\pm 20%	CKG45KX7S2A335M290JH			
4.7 μ F	3225	3.35 \pm 0.10	\pm 10%	CKG32KX7S2A475K335AH	CKG32KX7S1H475K335AH		
			\pm 20%	CKG32KX7S2A475M335AH	CKG32KX7S1H475M335AH		
	4532	2.90 \pm 0.10	\pm 10%	CKG45KX7S2A475K290JH	CKG45KX7S1H475K290JH		
			\pm 20%	CKG45KX7S2A475M290JH	CKG45KX7S1H475M290JH		
6.8 μ F	3225	3.35 \pm 0.10	\pm 10%		CKG32KX7S1H685K335AH		
			\pm 20%		CKG32KX7S1H685M335AH		
	4532	5.00 \pm 0.50	\pm 20%	CKG45NX7S2A685M500JH			
5750	3.35 \pm 0.15	\pm 10%	CKG57KX7S2A685K335JH				
		\pm 20%	CKG57KX7S2A685M335JH				
10 μ F	3225	3.35 \pm 0.10	\pm 10%		CKG32KX7S1H106K335AH		
			\pm 20%		CKG32KX7S1H106M335AH		
	4532	5.00 \pm 0.50	\pm 20%	CKG45NX7S2A106M500JH	CKG45NX7S1H106M500JH		
5750	3.35 \pm 0.15	\pm 10%	CKG57KX7S2A106K335JH	CKG57KX7S1H106K335JH			
		\pm 20%	CKG57KX7S2A106M335JH	CKG57KX7S1H106M335JH			
15 μ F	5750	3.35 \pm 0.15	\pm 20%	CKG57KX7S2A156M335JH			
22 μ F	4532	2.90 \pm 0.10	\pm 20%				CKG45KX7S1C226M290JH
5750	5.00 \pm 0.50	\pm 20%	CKG57NX7S2A226M500JH	CKG57NX7S1H226M500JH			
47 μ F	4532	5.00 \pm 0.50	\pm 20%				CKG45NX7S1C476M500JH
							CKG57KX7S1C476M335JH
	5750	3.35 \pm 0.15	\pm 20%			CKG57NX7S1E476M500JH	
100 μ F	5750	5.00 \pm 0.50	\pm 20%				CKG57NX7S1C107M500JH



Capacitance Range Table

Class 2 (Temperature Stable)

Temperature Characteristics: X7T (-55 to +125°C, +22/-33%)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number		
				Rated Voltage Edc: 630V	Rated Voltage Edc: 450V	Rated Voltage Edc: 250V
100 nF	3225	3.35 ± 0.10	± 10%	CKG32KX7T2J104K335AH		
			± 20%	CKG32KX7T2J104M335AH		
150 nF	3225	3.35 ± 0.10	± 10%	CKG32KX7T2J154K335AH		
			± 20%	CKG32KX7T2J154M335AH		
	4532	2.90 ± 0.10	± 10%	CKG45KX7T2J154K290JH		
			± 20%	CKG45KX7T2J154M290JH		
220 nF	3225	3.35 ± 0.10	± 10%	CKG32KX7T2W224K335AH		
			± 20%	CKG32KX7T2W224M335AH		
	4532	2.90 ± 0.10	± 10%	CKG45KX7T2J224K290JH		
			± 20%	CKG45KX7T2J224M290JH		
330 nF	3225	3.35 ± 0.10	± 10%	CKG32KX7T2E334K335AH		
			± 20%	CKG32KX7T2E334M335AH		
	4532	2.90 ± 0.10	± 10%	CKG45KX7T2W334K290JH		
			± 20%	CKG45KX7T2W334M290JH		
	5750	3.35 ± 0.15	± 10%	CKG45NX7T2J334M500JH		
			± 20%	CKG57KX7T2J334K335JH		
5750	3.35 ± 0.15	± 20%	CKG57KX7T2J334M335JH			
		± 10%	CKG45KX7T2W474K290JH			
470 nF	4532	2.90 ± 0.10	± 20%	CKG45KX7T2W474M290JH		
			± 10%	CKG45NX7T2J474M500JH		
	5750	3.35 ± 0.15	± 10%	CKG57KX7T2J474K335JH		
			± 20%	CKG57KX7T2J474M335JH		
680 nF	4532	2.90 ± 0.10	± 10%	CKG45KX7T2E684K290JH		
			± 20%	CKG45KX7T2E684M290JH		
	5750	3.35 ± 0.15	± 10%	CKG45NX7T2W684M500JH		
			± 20%	CKG57KX7T2W684K335JH		
	5750	5.00 ± 0.50	± 20%	CKG57KX7T2W684M335JH		
			± 10%	CKG57NX7T2J684M500JH		
1 µF	4532	2.90 ± 0.10	± 10%	CKG45KX7T2E105K290JH		
			± 20%	CKG45KX7T2E105M290JH		
	5750	3.35 ± 0.15	± 10%	CKG45NX7T2W105M500JH		
			± 20%	CKG57KX7T2W105K335JH		
	5750	5.00 ± 0.50	± 20%	CKG57KX7T2W105M335JH		
			± 10%	CKG57NX7T2J105M500JH		
1.5 µF	4532	5.00 ± 0.50	± 20%	CKG45NX7T2E155M500JH		
			± 10%	CKG57KX7T2E155K335JH		
	5750	3.35 ± 0.15	± 20%	CKG57KX7T2E155M335JH		
			± 10%	CKG57NX7T2W155M500JH		
2.2 µF	4532	5.00 ± 0.50	± 20%	CKG45NX7T2E225M500JH		
			± 10%	CKG57KX7T2E225K335JH		
	5750	3.35 ± 0.15	± 20%	CKG57KX7T2E225M335JH		
			± 10%	CKG57NX7T2W225M500JH		
3.3 µF	5750	5.00 ± 0.50	± 20%	CKG57NX7T2E335M500JH		