



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
010	RELEASED	10-9-91	<i>MDR</i>

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions <u>MIL-STD-348</u>	Temperature Rating <u>-65°C To +165°C</u>
Frequency Range (GHz) <u>DC - 18</u>	<u>FIG 310.2</u>	Vibration - MIL-STD-202, Method 204, Condition D, 20G's
Volt Rating (VRMS MAX) <u>N/A</u>	Recommended Mating Torque <u>N/A</u>	Shock - MIL-STD-202, Method 107, Condition B
VSWR <u>1.04 + (.009 F(GHz))</u>	Mating Characteristics:	Thermal shock MIL-STD-202, Method 107, Condition B
Insertion Loss (dB MAX) <u>.04 √F(GHz)</u>	Insertion (MAX Lbs) <u>3.0</u>	Except High Temp <u>115°C</u>
RF Leakage (dB MIN) <u>-(100 - F(GHz))</u>	Withdrawal (MIN Oz) <u>1.0</u>	Moisture Resistance - MIL-STD-202, Method 106
Corona, 70,000 Ft (VRMS MIN) <u>333</u>	Force To Engage (In/Lbs MAX) <u>2.0</u>	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Dielectric Withstanding Voltage (VRMS MIN) <u>1000 @ sea level</u>	Force To Disengage (In/Lbs MAX) <u>2.0</u>	
Contact Resistance (Milliohms MAX)	Center Contact Captivation	
Center Contact <u>10.0</u>	Axial <u>6.0 Lbs</u>	
Outer Contact <u>2.0</u>	Radial <u>N/A</u>	
RF High Potential (VRMS MIN @ 5 MHz) <u>667 @ sea level</u>	Weight (Grams) <u>T.B.D.</u>	
I.R.(Megohms) <u>5000</u>		

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457, MIL-P-19468 AND FED SPEC L-P-403	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B196, ALLOY 173	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
GASKET	CONDUCTIVE SILVER/SILICONE ELASTOMERS	N/A
COMPONENT	MATERIAL	FINISH

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON

FRAC.	DEC.	ANGLES
± 1/64	± .005	± °

These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

DRAWN BY *MC* DATE 10-9-91

CHECKED BY *CV* DATE 10-9-91

APPD BY *MDR* DATE 10-9-91

USE ASS'Y PROCEDURE

NO. AP. N/A

AMP Incorporated
140 Fourth Avenue
Waltham, MA 02451-7599

TITLE **OSM TWO-HOLE FLANGE MOUNT JACK RECEPTACLE WITH EMI/RFI GASKET**

SIZE <u>B</u>	CODE IDENT NO. <u>26805</u>	<u>2052-3356-02</u>	REV <u>010</u>
SCALE <u>5:1</u>		SHEET <u>1</u> OF <u>1</u>	