



THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - TE Connectivity ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A1	REVISED PER ECO-17-001162	14AUG2017	SK	PO



NOTES

1. TERMINAL NUMBERS ARE FOR REFERENCE ONLY AND DO NOT APPEAR ON SWITCHES.
2. ALL MATERIALS AND FINISHES SHALL COMPLY WITH EU DIRECTIVE 2003/95/EC OF 27JAN2003 (ROHS).



PC HOLE LAYOUT

MATERIALS		
COMPONENT NAME	BASE MATERIAL	FINISH
HOUSING	PBT, UL94 V-0, GRAY	
FRAME	BRASS	NICKEL
BUTTON	PBT, UL94 HB, BLACK	
MOVABLE CONTACT	PHOSPHOR BRONZE	GOLD OVER NICKEL
TERMINAL (CONTACT AREA)	PHOSPHOR BRONZE	GOLD OVER NICKEL
TERMINAL (SOLDER AREA)	PHOSPHOR BRONZE	GOLD OVER NICKEL

SPECIFICATIONS	
CURRENT RATING, MAX.	50mA @ 48 VDC OR PEAK AC (2.4VA)
CURRENT RATING, MIN.	1µA @ 20 VDC OR PEAK AC (.02VA)
TERMINATION RESISTANCE	50 MILLIOHMS MAX AT 1.5mA 200µVAC
INSULATION RESISTANCE	1000 MEGOHMS MIN @ 500 VDC
DIELECTRIC WITHSTANDING VOLTAGE	500 V RMS AT SEA LEVEL
OPERATING TEMPERATURE	-20°C to +85°C
STORAGE TEMPERATURE	-40°C to +85°C
PLUNGER TRAVEL	.047±.010
ELECTRICAL LIFE	
50mA @ 48 VDC OR PEAK AC	10,000 CYCLES
1µA @ 20 VDC OR PEAK AC	50,000 CYCLES
.4VA MAX @ 20 VDC OR PEAK AC	

	2-1	2-3	(ON)	ON	.157	PC	2	1	APB1FGPC04	1825176-3
OBSOLETE	1-3	OFF	(ON)	OFF	.157	PC	1	1	APB1CGPC04	1825176-2
					ACTUATOR LENGTH	TERMINAL	THROWS	POLES	ALCO P/N	TE P/N
	TERMINALS CONNECTED		FUNCTION							

THIS DRAWING IS A CONTROLLED DOCUMENT. DWN MKC 02DEC05
 CHK -
 APVD -
 PRODUCT SPEC -
 APPLICATION SPEC -

STE TE Connectivity

APB SERIES PUSHBUTTON SWITCH, PC TERMINALS

SIZE CAGE CODE DRAWING NO RESTRICTED TO
 WEIGHT 0 A2 00779 C-1825176 -

CUSTOMER DRAWING SCALE 4:1 SHEET 1 OF 1 REV A1