



1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.
2. MATERIAL: HOUSING & COVER - THERMOPLASTIC, BLACK. TERMINALS - PHOS BRONZE PLATED WITH EITHER .000050 MINIMUM GOLD PLATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE. .000050 MIN TOTAL ON MATING SURFACE. GOLD FLASH PLATED ON TERMINATING SIDE. .000050 MINIMUM NICKEL UNDERPLATE OVER ENTIRE TERMINAL.
3. COVER SHOWN LOOSE BUT SHIPPED ASSEMBLED.
4. WIRE RANGE: 26 AWG SOLID THRU 30 AWG SOLID AND 28 AWG STRANDED RIBBON CABLE.
5. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.
6. FLAT CABLE SHALL BE FURNISHED BY CUSTOMER.
7. MATING FACE CONSISTS OF TWO ROWS OF TERMINALS ON .085 CENTERS. TERMINATING SIDE CONSISTS OF TERMINALS ON .100 CENTERS FOR AN EFFECTIVE .050 TERMINATION.
8. FOR MORE INFORMATION REFER TO AMP PRODUCT SPECIFICATION 108-6076 & APPLICATION SPEC 114-6030.

REV		DATE		BY	
GP	00	1/7/83	1/7/83	BMI	WJM
REVISIONS					
DESCRIPTION					
REVISED PER ECU-88-00737					

THIS DRAWING IS A CONTROLLED DOCUMENT		DATE		BY	
DRAWN BY: Z. BEZAL		1/14/83		WJM	
CHECKED BY: W. MILLIKENS		1/14/83		WJM	
APPROVED BY: [Signature]		DATE: 1/14/83		BY: WJM	
PARTIAL		SCALE: 2:1		SHEET 1 OF 1	
CUSTOMER DRAWING		SCALE: 2:1		SHEET 1 OF 1	

AS SHOWN	553596-1
DESCRIPTION	PART NUMBER
Yeo Electronics Corporation Huntingburg, IN 47109-3698	
PLUG ASSEMBLY, 14 POSITION SCREEN COCK, LOW PROFILE, SCREW CLAMP LATCH	
SIZE	DATE
A2100779	0007
REVISED TO	DATE