



SECTION A-A

- 1. TIN PLATE PER ASTM B 545 .000254 $[\ .000100]$ MIN THICK.
- 2. GOLD PLATE PER ASTM B 488 0.00076 $[\ .000030]$ MIN THICK OVER NICKEL PLATE PER QQ-N-290 0.00028 $[\ .000011]$ MIN THICK ON CONTACT AREA.
- 3. RECOMMENDED HOLE SIZE, PLATED OR UNPLATED:
 MACHINE INSERTION: 1.32 ± 0.05 $[\ .052 \pm .002]$
 HAND INSERTION: 1.32 $\begin{matrix} +0.10 \\ -0.00 \end{matrix}$ $[\ .052$ $\begin{matrix} +.004 \\ -.000 \end{matrix}$
- 4. APPLICATION TOOL PART NUMBER:
 MACHINE NO. 682127-3
 INSERTION HEAD NO. 682039-2
- 5. TO INSURE PROPER SPRING TENSION DO NOT EXCEED A 0.05 $[\ .002]$ DIFFERENCE IN PIN DIA WHEN CHANGING TO A SMALLER PIN.
- 6. BOTTOM PLUG KNOCKOUT TOOL PART NUMBER 69729 WITH TIP PART NUMBER 69728.
- 7. MATERIAL:
 SPRING: BERYLLIUM COPPER PER ASTM B 194
 EYELET: COPPER PER ASTM B 152
- 8. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

OPEN	0.56-0.64 $[\ .022 - .025]$	TIN 1	GOLD 2	4-5331272-3
	0.46-0.53 $[\ .018 - .021]$			3-5331272-9
KNOCKOUT	0.56-0.64 $[\ .022 - .025]$	TIN 1	TIN 1	3-5331272-5
			GOLD 2	2-5331272-7
CLOSED	0.46-0.53 $[\ .018 - .021]$	TIN 1	TIN 1	2-5331272-5
			GOLD 2	2-5331272-3
BOTTOM TYPE	RECOMMENDED PIN DIA 5	EYELET	FINISH	PART NO

8 OBSOLETE

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm[INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± 0.20 $[\ .008]$ 4 PLC ± - ± - ANGLES ± - ± -	DWN A. FERNANDEZ-DOCK5 20APR2005 CHK J. HAVENER 20APR2005 APVD J. HAVENER 20APR2005	NAME MINIATURE SPRING SOCKET ASSEMBLY SERIES 2
MATERIAL 7	FINISH SEE TABLE	PRODUCT SPEC 108-14008 APPLICATION SPEC 114-13152	SIZE A2
CUSTOMER DRAWING		WEIGHT -	SCALE 20:1
		RESTRICTED TO -	SHEET 1 of 1
			REV P

STE TE Connectivity