



4 COLOR OF HOUSINGS MAY RANGE FROM CLEAR TO GREEN OR YELLOW DUE TO HYGROSCOPIC NATURE OF RESIN. HOWEVER IT DOESN'T AFFECT THE FORM, FIT AND FUNCTION OF THE PRODUCT.

Index	Änderung	Tag	Name
F2	REVISED PER ECO-11-005139	28MAR11	HMR
G	REVISED PER ECR-13-019169	04SEP14	AV / DZ





1 PHOSPHOR UND HALOGEN FREI  
PHOSPHOR AND HALOGEN FREE

2 SCHÜTTGUT IN BEUTEL UND VERSANDKARTON  
PN 973 057-2  
BULK PACKAGING IN PLASTIC BAG AND  
CORRUGATED SHIPPING BOX PN 973 057-2

3 GWT 750° (WITHOUT FLAME) ACC. IEC  
60335-1 EDITION 06/2001  
GLÜHDRAHT PRÜFUNG 750° (OHNE FLAMME)  
NACH IEC 60335-1 AUSGABE 06/2001

Änderungen, die dem technischen Fortschritt dienen, behalten wir uns vor.

926 302-5	PA 6 UL 94 V-0 natur	 TE Connectivity	Benennung UNIVERSAL MATE-N-LOK 10-poliges Steckergehäuse			
926 302-4	PA 6.6 UL 94 V-0 weiß					
926 302-3	PA 6.6 UL 94 V-0 NATUR					
926 302-2	PA 6.6 UL 94 V-0 schwarz					
926 302-1	PA 66 UL 94 V-2 NATURAL					
Bestell-Nr.	Werkstoff	Oberfläche Farbe	Nicht tolerierte Maße ± 0.2 mm ±	Format <b>B</b>	Zeichnungs-Nr. 926 302	G
Gez. 1.7.80 Hück	Gepr. 29.8.1980 R. Blunck	Gepr. 29.8.80	Maßstab 2:1		Blatt-Nr.	