



CROSS-SECTION IN mm ²	
SINGLE CONNECTION	
0.20	X
0.25	X
0.35	X
0.50	X

NOTES

- 1 WIRE RANGE 0.2 - 0.5 mm²
- 2 INSULATION RANGE Ø1.0 - 1.6
- 3 SELECTIVE LUBRICATED IN INDICATED AREA WITH ANTI-FREETING LUBRICANT

	TIN (vorverzinnt)	CuZn30	△1-926984-1	D
926985-2	TIN (vorverzinnt)	CuSn4	926984-2	D
926985-1	TIN (vorverzinnt)	CuZn30	926984-1	D
LOOSE PIECE	FINISH	MATERIAL	PART NO.	REV.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: ±0.2	DWN JS 27-Jan-12	TE Connectivity
		CHK XP 27-Jan-12	
		APVD RS 27-Jan-12	
MATERIAL -	FINISH -	PRODUCT SPEC 108-18054 (DES. OBJ.)	NAME STANDARD TIMER CONTACT
		APPLICATION SPEC 114-18080	SIZE CAGE CODE DRAWING NO. RESTRICTED TO
		WEIGHT -	A3 00779 C=926984
CUSTOMER DRAWING			SCALE 5:1 SHEET 1 OF 1 REV D1