

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AF	50	AD	REVISED PER ECR-12-013445	18OCT12	KH PD

- 1 CONTINUOUS STRIP ON REELS
- 2 MAX FIRST INSERTION FORCE, 88.96 NEWTON [20 LBS] USING GAGE 100505.
- 3 WIRE SIZE IS #14-10 AWG
- 4 INSULATION RANGE IS 3.81-5.08 [.150-.200] DIA
- 5 MATING TAB THK IS 0.81±0.025 [.032±.001]
- 6 FOREIGN PRODUCTION ONLY
- 7 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

VIEW A-A
SCALE 10:1

SECTION B-B
SCALE 8:1

SECTION C-C
SCALE 8:1

TYPE	WIDTH	STRIP LENGTH ±0.38 ±[.015]	TYPE	WIDTH	±.051 [±.002] HEIGHT	WIRE
F	5.33 [.210]	6.4 [.252]	F	3.30 [.130]	2.108 [083] 2.413 [095] 2.921 [115]	2.0mm [14] 3.0mm [12] 5.0mm [10]
INSUL BARREL CRIMP		WIRE BARREL CRIMP				

FINISH	MATERIAL	PART NO.
6/7/7	SILVER	TEMP3 PHOS BRZ
6/7/7	TIN	TEMP3 PHOS BRZ
6/7/7	-	TEMP3 PHOS BRZ
6/7/7	SILVER	TEMP4 BRASS
6/7/7	TIN	BRASS
6/7/7	-	TEMP4 BRASS
6/7/7	FINISH	MATERIAL
6/7/7	FINISH	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	JR RUTH	7/10/89		TE Connectivity		
DIMENSIONS: mm [INCHES]		CHK	MS FEHER	7/10/89		RECEPTACLE, FASTON, .250 SERIES		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	C MEYERS	7/10/89		SIZE	CAGE CODE	DRAWING NO
0 PLC ± -		PRODUCT SPEC				A2	00779	C=42437
1 PLC ± -		APPLICATION SPEC			WEIGHT	-		
2 PLC ± -					CUSTOMER DRAWING	SCALE	5:1	
3 PLC ± 0.38 [.015]					SHEET	1 of 1		
4 PLC ± -					REV	AD		
ANGLES ± -								

1471-9 (3/11)