

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	G	SEE ECR 11-010607	17MAY2011	JS	LB
	G1	ECR-14-007191	25JUN2014	SK	JS

SECTION A-A

SECTION B-B

SECTION C-C

Kontakt geeignet für:
 Draht Groessenbereich 0.5 - 1.5 mm
 Isolationsbereich Ø2.0 - 3.0 mm

Notes

1 OBSOLETE

Leitungsquerschnitt in mm²

	Einzelanschlag	0.5	0.75	1.0	1.5
0.5	X	X			
0.75	X				
1.0	X				
1.5	X				

927936-4	1	STANDARD-TIMER Kontakt	vorverzinnt	CuNiSi	926965-4	1	F
927936-3	1	STANDARD-TIMER Kontakt	vorverzinnt	Kupfereisen	926965-3	1	F
927936-2	1	STANDARD-TIMER Kontakt	vorverzinnt	Bronze	926965-2		G
927936-1	1	STANDARD-TIMER Kontakt	vorverzinnt	Messing	926965-1		G
EINZELAUSFUEHRUNG	BENENNUNG EINZELTEIL	OBERFLÄCHE	WERKSTOFF	BANDWARE	REV.		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN GOERKE 01FEB1988

CHK BITSCH 27JUN2014

APVD Bleicher.M. 19JUN07

PRODUCT SPEC

APPLICATION SPEC

WEIGHT -

Customer Drawing

DIMENSIONS:
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±0.2mm
1 PLC	
2 PLC	
3 PLC	
4 PLC	±1°
ANGLES	

MATERIAL

SEE TABLE

FINISH

SEE TABLE

TE Connectivity

NAME STANDARD TIMER CONTACT

-

-

SIZE A3 CAGE CODE - DRAWING NO C-926965 RESTRICTED TO -

SCALE 5:1 SHEET 1 OF 1 REV G1

1470-19 (3/13)