



- △ COUPLING RING: POLYPHENYLENE, BLACK.
 ADAPTER, HOUSING AND PRESSURE PLATE: NYLON, BLACK.
 WIRE ENTRY SEAL: ELASTOMER, RED-IRON OXIDE.
- 2. CONNECTOR WILL ACCEPT (37) MULTIMATE SOCKET CONTACTS.
- △ 3. ORIENTATION HOLE USED IN THE MANUFACTURING PROCESS ONLY.
 THIS HOLE IS NOT INTENDED FOR WIRE INSERTION.

796288-1
 PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN C. DORWART 11 NOV 98	TE Connectivity	
DIMENSIONS: INCHES		CHK K. DOWHOWER 15NOV99	NAME K. DOWHOWER 15NOV99	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC 108-1579		
0. PLC ± -		APPLICATION SPEC		
1. PLC ± -		SIZE A1		
2. PLC ± 0.13(.005)		CAGE CODE 00779		
3. PLC ± -		DRAWING NO 796288		
4. PLC ± -		RESTRICTED TO		
ANGLES ± -		WEIGHT -		
MATERIAL △ 1		CUSTOMER DRAWING		
		SCALE 2:1		SHEET 1 OF 1
				REV C