



P.C. BOARD MOUNTING DIMENSIONS  $\Delta$ 3

- $\Delta$ 1 HOUSING: FLAME RETARDANT, 94V-0 RATED, GLASS FILLED, NYLON OR POLYESTER, COLOR: BLACK.  
CONTACTS: BRASS.  
INSERTS: ZINC.
- $\Delta$ 2 CONTACTS: SEE TABLE.  
INSERTS: CLEAR CHROMATE COATING.
- $\Delta$ 3 REFER TO APPLICATION SPEC FOR RECOMMENDED P.C. BOARD MOUNTING DIMENSIONS FOR AUTOMATIC INSERTION.
- $\Delta$ 4 GOLD FLASH ON THE MATING SURFACES, .000100 MIN TIN ON THE SOLDER END, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT.
- $\Delta$ 5 .000030 MIN GOLD PLATE ON THE MATING SURFACES, .000100 MIN TIN PLATE ON THE SOLDER END, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT  
-OR-  
GOLD FLASH OVER PALLADIUM-NICKEL PLATE, .000030 MIN TOTAL ON THE MATING SURFACES, .000100 MIN TIN ON THE SOLDER END, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT.

WITH INSERTS	$\Delta$ 5	5747467-4
WITH .120 DIA HOLE	$\Delta$ 5	5747467-2
WITH .120 DIA HOLE	$\Delta$ 4	5747467-1
REMARKS	FINISH	PART NUMBER

**COPYRIGHT 2005  
TYCO ELECTRONICS CORP  
ALL RIGHTS RESERVED**

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN G. PETERS 19SEP05	19SEP05	STE TE Connectivity	
0 PLC ± -	1 PLC ± -	CHK S. BOLASH 19SEP05	19SEP05	NAME M. WALMSLEY 19SEP05	
2 PLC ± -	3 PLC ± .005	APVD M. WALMSLEY 19SEP05	19SEP05	PRODUCT SPEC 108-40025	
4 PLC ± -	ANGLES ± °	APPLICATION SPEC 114-40015	114-40015	SIZE A1	CAGE CODE DRAWING NO. 00779
MATERIAL	FINISH	WEIGHT	—	SCALE 4:1	SHEET 1 OF 1
CUSTOMER DRAWING		DRAWING NO. 5747467		REV B	