



- ⚠ CONTACTS: PHOSPHOR BRONZE
RECEPTACLE HOUSING & PIN SPACER: UL V-0 RATED POLYESTER LCP, BLACK
BRACKET: ZINC
- ⚠ POSITION TOLERANCE APPLIES AT TIP ONLY.
- ⚠ CONTACTS: EITHER 0.00076 [.00030] MIN GOLD PLATE FOR A LENGTH OF 3.35 [.132] MIN ON MATING END OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, 0.00076 [.00030] MIN TOTAL FOR A LENGTH OF 3.35 [.132] MIN ON MATING END, 0.00381 [.000150] MIN TIN FOR A LENGTH OF 3.35 [.127] MIN ON OPPOSITE END, ALL OVER 0.00127 [.000050] MIN NICKEL UNDERPLATE ON ENTIRE CONTACT.
BRACKET: 0.00254 [.000100] MIN NICKEL OVER 0.00508 [.000200] MIN COPPER.
- ⚠ ACTUAL HOLE SIZE USED WILL DEPEND ON TRACE ROUTING REQUIREMENTS BETWEEN HOLES AND CONNECTOR PLACEMENT TECHNIQUE.

100 POSITION AS SHOWN

X	31.11 [1.225]	70.36 [2.770]	84.20 [3.315]	62.23 [2.450]	66.60 [2.622]	68.94 [2.714]	78.23 [3.080]	100	5749084-9
Y	15.24 [.600]	38.61 [1.520]	52.45 [2.065]	30.48 [1.200]	34.85 [1.372]	37.19 [1.464]	46.48 [1.830]	50	5749084-5
PWB PATTERN	G	F	E	D	C	B	A	NO. OF POSN	PART NUMBER

**COPYRIGHT 2005
TYCO ELECTRONICS CORP
ALL RIGHTS RESERVED**

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DWN: A. FERNANDEZ-DOCKS 02-15-05	APPROVED: S. BOLASH 02-15-05	NAME: M. WALMSLEY	DATE: 02-15-05	PRODUCT SPEC: PLUG ASSEMBLY, SHIELDED, RIGHT ANGLE, AMPLIMITE @.050 Series
MATERIAL: 3	FINISH: 1	SIZE: A1	CAGE CODE: 00779	DRAWING NO: 5749084	RESTRICTED TO: -	SCALE: 4:1

CUSTOMER DRAWING