



- ① PINS: 0.00076[.000030] MINIMUM GOLD IN CONTACT AREA, 0.00381[.000150] MIN TIN ON SOLDER TAILS, ALL OVER 0.00127[.000050] MINIMUM NICKEL.
- 2. CUSTOMER TO PROVIDE CARD GUIDANCE SYSTEM.
- ③ DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- 4. CONNECTOR REQUIRES USE OF 2 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD.
- ⑤ ASSEMBLY KEYED FOR 5 VOLT CARDS.
- ⑥ ASSEMBLY KEYED FOR LOW VOLT CARDS (3.3V).
- ⑦ HOUSING & ORGANIZER: LCP, COLOR; BLACK. PINS: BRASS.

⑥	1,17,34	ALL OTHER PINS	36,67	5535655-2
	35,51,68	OTHER PINS		
⑤	1,17,34	ALL OTHER PINS	36,67	5535655-1
	35,51,68	OTHER PINS		
VOLTAGE KEYING & IDENTIFICATION	5.0	4.25	3.5	PART NO
	[.197]	[.167]	[.138]	
"L" (PIN LENGTH) AND LOCATION				

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L VARELA - DOCK5 03-23-05	Tyco Electronics Corporation Harrisburg, PA 17105-3608
DIMENSIONS: mm [INCHES]		CHK S BOLASH 03-23-05	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M WALMSLEY 03-23-05	PIN HEADER ASSY, 68 POSN, RAISED HEIGHT, TOP BD MTG, THRU-HOLE, MEMORY CARD
0 PLC ± -		PRODUCT SPEC	
1 PLC ± -		APPLICATION SPEC	SIZE CASE CODE DRAWING NO A1 00779 C=5535655
2 PLC ± 0.13 [005]			
3 PLC ± -			RESTRICTED TO
4 PLC ± -			
ANGLES ± -			
FINISH ①		WEIGHT 8.5 GRAMS	
MATERIAL ⑦		CUSTOMER DRAWING	SCALE 4:1 SHEET 1 OF 1 REV 0

**COPYRIGHT 2005
 TYCO ELECTRONICS CORP
 ALL RIGHTS RESERVED**