

4

DRAWING MADE IN THIRD ANGLE PROJECTION

3

2

1

LOC AF DIST 50

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

, 19

© COPYRIGHT 19

BY AMP INCORPORATED, HARRISBURG, PA. ALL INTERNATIONAL RIGHTS

RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN PATENTS AND/OR PATENTS PENDING.

REVISIONS

P	F	ZONE	LTR	DESCRIPTION	DATE	APPROVED
	✓		C	REDRAWN	2/6/84	SS/

Technical drawing of a ring component. The front view shows a circular ring with a diameter of 7.14 [281]. The total width of the ring is 11.56 [455]. The distance from the center of the ring to the center of the hole is 8.57 [335]. The hole diameter is 4.42 [174] and 4.26 [168]. The side view shows a thickness of 5.33 [210] and a distance of 3.30 [130] from the center of the ring to the center of the hole. The hole diameter is also indicated as 3.30 [130].

Section A-A of the ring component. The total width of the section is 3.97 [155] and 3.30 [130]. The section shows a U-shaped cross-section with a central hole.

1. DIMS IN BRACKETS ARE IN INCHES.  
2. CONTINUOUS STRIP ON REELS.

# METRIC

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN <del>INCHES</del> MM		CONTRACT NO		0.8 - 2.0 mm <sup>2</sup> [#78-#14]		40951	
TOLERANCES ON:		DR 2-6-89		WIRE RANGE		PART NO	
DECIMALS ±0.38 [015]		CHK 2-6-89		<b>AMP</b>   AMP INCORPORATED Harrisburg, Pa.			
ANGLES ±		APPD 2-7-84					
MATERIAL 0.51 [020] BRASS		APPD 2-7-84		NAME RING			
FINISH NONE		DSGN APPD		SIZE B		FSCM NO 00779	
OTHER APPD				DRAWING NO 40951		SHEET	
				SCALE			

AMP 1470-15 REV 2-81

CUSTOMER DRAWING