



- 1 HOUSING MATERIAL: LIQUID CRYSTAL POLYMER PER ASTM D5138 LCPO00 G30A 32250.
- 2 CONTACT MATERIAL: PHOSPHOR BRONZE.
- 3 CONTACT FINISH:
 UNDERPLATE (ENTIRE CONTACT):
 0.00127 MIN NICKEL PER SAE-AMS-QQ-N-290.
 ON MATING SURFACES:
 CONFORMS TO ALL TESTING SPECIFIED FOR TELCORDIA UNCONTROLLED ENVIRONMENT.
 ON LEADS
 0.00381 MIN TIN PER ASTM B 545 OVER UNDERPLATE.
 LUBRICATION (MIN MATING SURFACES):
 SURFACE CONDITIONER AFTER PLATING.
- 4 PART MARKING, LOCATED APPROXIMATELY AS SHOWN.
- 5 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

	4.25	6.5	34	17	35.88	72	1-5536501-1
	4.25	6.5	130	65	131.88	264	1-5536501-0
	4.25	6.5	106	53	107.88	216	1-5536501-9
	4.25	6.5	118	59	119.88	240	1-5536501-8
	4.25	6.5	82	41	83.88	168	1-5536501-7
	4.25	6.5	58	29	59.88	120	5536501-6
	4.25	6.5	70	35	71.88	144	5536501-5
	4.25	6.5	94	47	95.88	192	5536501-4
	4.25	6.5	46	23	47.88	96	5536501-3
	4.25	6.5	22	11	23.88	48	5536501-2
	4.25	6.5	10	5	11.88	24	5536501-1
	E	D	C	B	A	FINISH	NO OF POSN
							PART NUMBER

RECOMMENDED CIRCUIT PATTERN PER IPC-D300 TYPE II, CLASS C (COMPONENT SIDE)

THIS DRAWING IS A CONTROLLED DOCUMENT.

OWN: B. MCMASTER	30AUG04
CHK: R. WERTZ	30AUG04
APPD: R. WERTZ	30AUG04

STE TE Connectivity

Z-PACK 2mm FB, SIGNAL MODULE, PIN ASSEMBLY 2mm

SIZE: A1 CAGE CODE: 00779 DRAWING NO: 5536501

SCALE: 4:1 SHEET: 1 OF 1 REV: A2