

POSITIONS Polzahl	n	a±0.2	b	c	d _{-0.2}	e _{-0.25}	f	CODING Kodierung	CAVITY NUMBERING Kammerbezeichnung	ORDER NO. REV. Bestell-Nr.	ORDER NO. REV. Bestell-Nr.	WEIGHT Gewicht	POS.	QTY Stueck	DESCRIPTION Benennung Einzelteil	MATERIAL Werkstoff	SURFACE/Oberflaeche COLOUR/ Farbe
21	6	38.5	30	45	42.5	38.5	36.5	B (GROOVES) Nuten A-C		5-966140-6 A	4-966140-6 A	18.3g	4	7	TAB (43.4mm)	CuSn0.15/0.20	SEL. SILVER PLATED
										3-966140-6 C	6-966140-6 C		3	7	TAB (34.4mm)	CuSn0.15/0.20	SEL. SILVER PLATED
										2-966140-6 C	6-966140-6 C		2	7	TAB (25.4mm)	CuSn0.15/0.20	SEL. SILVER PLATED
										4-966140-6 C	6-966140-6 C		5	1	21 POS. HOUSING	PA66-GF13	NATURAL/natur
										3-966140-6 C	6-966140-6 C		4	7	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
18	5	33.5	25	40	37.5	33.5	31.5	A (GROOVES B-C) (Nuten B_C)		6-966140-1 C	3-966140-1 C	16.0g	3	7	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED
										2-966140-1 C	6-966140-1 C		2	7	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED
										4-966140-1 C	6-966140-1 C		1	1	18 POS. HOUSING	PA66-GF13	BLACK/schwarz
										3-966140-1 C	6-966140-1 C		4	6	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
										2-966140-1 C	6-966140-1 C		3	6	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED
15	4	28.5	20	35	32.5	28.5	26.5	A (GROOVES B-C) (Nuten B_C)		6-966140-2 C	3-966140-2 C	13.6g	2	5	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED
										1-966140-2 C	6-966140-2 C		1	1	15 POS. HOUSING	PA66-GF13	BLACK/schwarz
										4-966140-2 C	6-966140-2 C		4	5	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
										3-966140-2 C	6-966140-2 C		3	5	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED
										2-966140-2 C	6-966140-2 C		2	5	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED
12	3	23.5	15	30	27.5	23.5	21.5	A (GROOVES B-C) (Nuten B_C)		6-966140-3 C	3-966140-3 C	11.2g	4	4	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
										3-966140-3 C	6-966140-3 C		3	4	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED
										2-966140-3 C	6-966140-3 C		2	4	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED
										5-966140-3 C	6-966140-3 C		5	1	12 POS. HOUSING	PA66-GF13	NATURAL/natur
										4-966140-3 C	6-966140-3 C		4	3	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
9	2	18.5	10	25	22.5	18.5	16.5	A (GROOVES B-C) (Nuten B_C)		6-966140-4 C	3-966140-4 C	8.9g	3	3	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED
										2-966140-4 C	6-966140-4 C		2	3	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED
										1-966140-4 C	6-966140-4 C		1	1	9 POS. HOUSING	PA66-GF13	BLACK/schwarz
										4-966140-4 C	6-966140-4 C		4	2	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
										3-966140-4 C	6-966140-4 C		3	2	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED
6	1	13.5	5	20	17.5	13.5	11.5	A (GROOVES B-C) (Nuten B_C)		6-966140-5 C	3-966140-5 C	6.6g	2	2	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED
										1-966140-5 C	6-966140-5 C		1	1	6 POS. HOUSING	PA66-GF13	BLACK/schwarz
										4-966140-5 C	6-966140-5 C		4	2	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
										3-966140-5 C	6-966140-5 C		3	2	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED
										2-966140-5 C	6-966140-5 C		2	2	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED

POSITIONS Polzahl	n	a±0.2	b	c	d _{-0.2}	e _{-0.25}	f	CODING Kodierung	CAVITY NUMBERING Kammerbezeichnung	ORDER NO. REV. Bestell-Nr.	ORDER NO. REV. Bestell-Nr.	WEIGHT Gewicht	POS.	QTY Stueck	DESCRIPTION Benennung Einzelteil	MATERIAL Werkstoff	SURFACE/Oberflaeche COLOUR/ Farbe
21	6	38.5	30	45	42.5	38.5	36.5	B (GROOVES) Nuten A-C		8-966140-6 A	1-966140-6 A	18.3g	4	7	TAB (43.4mm)	CuSn4	TINNED/verzinkt
										3-966140-6 F	9-966140-6 F		3	7	TAB (34.4mm)	CuSn4	TINNED/verzinkt
										2-966140-6 F	9-966140-6 F		2	7	TAB (25.4mm)	CuSn4	TINNED/verzinkt
										4-966140-6 F	9-966140-6 F		1	1	21 POS. HOUSING	PA66-GF13	BLACK/schwarz
										3-966140-6 F	9-966140-6 F		4	7	TAB (43.4mm)	CuSn4	TINNED/verzinkt
18	5	33.5	25	40	37.5	33.5	31.5	A (GROOVES B-C) (Nuten B_C)		9-966140-1 F	6-966140-1 F	16.0g	3	6	TAB (34.4mm)	CuSn4	TINNED/verzinkt
										2-966140-1 F	9-966140-1 F		2	6	TAB (25.4mm)	CuSn4	TINNED/verzinkt
										1-966140-1 F	9-966140-1 F		1	1	18 POS. HOUSING	PA66-GF13	BLACK/schwarz
										4-966140-1 F	9-966140-1 F		4	5	TAB (43.4mm)	CuSn4	TINNED/verzinkt
										3-966140-1 F	9-966140-1 F		3	5	TAB (34.4mm)	CuSn4	TINNED/verzinkt
15	4	28.5	20	35	32.5	28.5	26.5	A (GROOVES B-C) (Nuten B_C)		9-966140-2 F	6-966140-2 F	13.6g	2	5	TAB (25.4mm)	CuSn4	TINNED/verzinkt
										1-966140-2 F	9-966140-2 F		1	1	15 POS. HOUSING	PA66-GF13	BLACK/schwarz
										4-966140-2 F	9-966140-2 F		4	5	TAB (43.4mm)	CuSn4	TINNED/verzinkt
										3-966140-2 F	9-966140-2 F		3	5	TAB (34.4mm)	CuSn4	TINNED/verzinkt
										2-966140-2 F	9-966140-2 F		2	5	TAB (25.4mm)	CuSn4	TINNED/verzinkt
12	3	23.5	15	30	27.5	23.5	21.5	B (GROOVES) Nuten A-C		8-966140-3 A	1-966140-3 A	11.2g	4	4	TAB (43.4mm)	CuSn4	TINNED/verzinkt
										3-966140-3 F	9-966140-3 F		3	4	TAB (34.4mm)	CuSn4	TINNED/verzinkt
										2-966140-3 F	9-966140-3 F		2	4	TAB (25.4mm)	CuSn4	TINNED/verzinkt
										5-966140-3 A	9-966140-3 A		5	1	12 POS. HOUSING	PA66-GF13	NATURAL/natur
										4-966140-3 F	9-966140-3 F		4	4	TAB (43.4mm)	CuSn4	TINNED/verzinkt
9	2	18.5	10	25	22.5	18.5	16.5	A (GROOVES B-C) (Nuten B_C)		9-966140-4 F	6-966140-4 F	8.9g	3	3	TAB (34.4mm)	CuSn4	TINNED/verzinkt
										2-966140-4 F	9-966140-4 F		2	3	TAB (25.4mm)	CuSn4	TINNED/verzinkt
										1-966140-4 F	9-966140-4 F		1	1	9 POS. HOUSING	PA66-GF13	BLACK/schwarz
										4-966140-4 F	9-966140-4 F		4	3	TAB (43.4mm)	CuSn4	TINNED/verzinkt
										3-966140-4 F	9-966140-4 F		3	3	TAB (34.4mm)	CuSn4	TINNED/verzinkt
6	1	13.5	5	20	17.5	13.5	11.5	A (GROOVES B-C) (Nuten B_C)		9-966140-5 F	6-966140-5 F	6.6g	4	2	TAB (43.4mm)	CuSn4	TINNED/verzinkt
										3-966140-5 F	9-966140-5 F		3	2	TAB (34.4mm)	CuSn4	TINNED/verzinkt
										2-966140-5 F	9-966140-5 F		2	2	TAB (25.4mm)	CuSn4	TINNED/verzinkt
										1-966140-5 F	9-966140-5 F		1	1	6 POS. HOUSING	PA66-GF13	BLACK/schwarz
										4-966140-5 F	9-966140-5 F		4	2	TAB (43.4mm)	CuSn4	TINNED/verzinkt

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN: Mahlike, B. 160CT2014	 TE Connectivity
DIMENSIONS: mm		CHK: Krauss, S. 170CT2014	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD: Goepfel, C. 200CT2014	NAME: TAB HEADER, 2.8x0.8, 6-21 POS. Messerleiste, 2.8x0.8, 6-21 pol.
 0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ±0°		PRODUCT SPEC: -	
MATERIAL: SEE PARTS LIST		FINISH: SEE PARTS LIST	APPLICATION SPEC: -
SIZE: A1		CAGE CODE: 00779	DRAWING NO: C=966140
RESTRICTED TO: -		WEIGHT: -	SCALE: 2:1
Customer Drawing		SHEET: 2 OF 2	REV: F6