



3.68	.145	26.42	1.040
2.070	.0815	12.70	.500
1.57	.062	10.351	.4075
1.40	.055	9.80	.386
1.00	.039	7.34	.289
0.76	.030	6.86	.270
0.25	.010	6.210	.2445
0.13	.005	6.10	.240
0.08	.003	5.99	.236
0.05	.002	5.33	.210
0.00381	0.000150	5.08	.200
0.00127	0.000050	4.14	.163
0.00076	0.000030	3.86	.152
MM	IN	MM	IN

CONVERSION TABLE

RECOMMENDED MOUNTING HOLE PATTERN FOR 1.57 THICK P.C. BOARD

- PINS TO COMPLY WITH AMP SOLDERABILITY SPEC 109-11-3.
- MATES WITH PLUG P/N 770581-1.
- COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
- RECOMMENDED FOR EDGE MOUNTING.
- 0.00381 MIN MATTE TIN LEAD OVER 0.00127 MIN NICKEL ENTIRE LENGTH OF PIN.
- 0.00076 MIN GOLD PLATE IN THE LOCALIZED PLATE AREA, 0.00381 MIN MATTE TIN LEAD IN THE LOCALIZED PLATE AREA, BOTH OVER 0.00127 MIN NICKEL.
- 0.00381 MIN MATTE TIN OVER 0.00127 MIN NICKEL ENTIRE LENGTH OF PIN.
- 0.00076 MIN GOLD PLATE IN THE LOCALIZED GOLD PLATE AREA, 0.00381 MIN MATTE TIN IN THE LOCALIZED TIN PLATE AREA, BOTH OVER 0.00127 MIN NICKEL.

BRASS	8 GOLD	NYLON, UL94V-0	WHITE	1-770972-1
BRASS	7 TIN	NYLON, UL94V-0	WHITE	1-770972-0
BRASS	6 GOLD	NYLON, UL94V-0	WHITE	770972-2
BRASS	5 TIN-LEAD	NYLON, UL94V-0	WHITE	770972-1
MATERIAL	FINISH	MATERIAL	COLOR	PART NUMBER
PIN		HOUSING		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN K. WHITAKER 16AUG2005	CHK C. JONES 16AUG2005	APVD G. JONES 16AUG2005	NAME
0 PLC ± -	1 PLC ± -	STE TE Connectivity			TE Connectivity
2 PLC ± -	3 PLC ± 0.13	PRODUCT SPEC			HEADER ASSEMBLY, RIGHT ANGLE, WITH SHORT PEG, 12 CIRCUIT, MINI UNIVERSAL MATE-N-LOK(TM)
4 PLC ± -	ANGLES ± -	APPLICATION SPEC			SIZE: A1
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SCALE: 5:1	SHEET 1 OF 1	REV G

CUSTOMER DRAWING