

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2005

© COPYRIGHT 2005

ALL RIGHTS RESERVED.

LOC
ALDIST
2

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	J2	ECR-11-005629	17AUG2011	C. J	R. P
	J3	ECR-12-015397	17SEP2012	MGT	R. P

NOTES:

Bemerkungen:

	2-6µm Sn OVER Ni IN CRIMP-AREA 2-6µm Sn über Ni in der Crimpzone
	0.8µm Au OVER Ni IN CONTACT-AREA 0.8µm Au über Ni in der Kontaktzone
	SUITABLE FOR Ø1.0-2.5mm Für Isolations Ø1.0-2.5mm geeignet
	0.8µm Au OVER 1.3µm Ni ON INSIDE OF WIRE BARREL AND CONTACT AREA 0.8µm Au über 1.3µm Ni in der Drahtcrimp und Kontaktzonen, sonst 1.3µm Ni

Superseded by 350851-7	926895-7	926884-7	CuZn30		
	926895-6	926884-6	CuSn4		
	926895-3	926884-3	CuSn4	PRE-TIN	
	OBSOLETE	926895-2	926884-2	CuZn30	
	926895-1	926884-1	CuZn30	PRE-TIN	
	LOOSE PIECE	PART NO.	MATERIAL	FINISH	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. Skoda	07NOV2005	TE Connectivity	
DIMENSIONS: mm		CHK R. Vlcek	-		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD -	-	NAME UNIVERSAL MNL SOCKET 0.2-0.8 mm ² WIRE RANGE	
0 PLC ±0.2		PRODUCT SPEC 108-1031	-	SIZE A3	
1 PLC ±0.2		APPLICATION SPEC 114-18011	-	CAGE CODE 00779	DRAWING NO G-926884
2 PLC ±0.2		WEIGHT -	-	RESTRICTED TO -	
3 PLC ±		CUSTOMER DRAWING	-	SCALE 5:1	SHEET 1 OF 1
4 PLC ±				REV J3	
ANGLES ±°					
FINISH SEE TABLE					

1470-19 (3/11)