



RECOMMENDED PANEL CUTOUT [1] SCALE 1:1

RECOMMENDED PC BOARD LAYOUT

1.75 [0.069]	32.36 [1.274]	1.40-1.98 [0.055-0.078]
2.74 [0.108]	30.05 [1.183]	0.79-1.40 [0.031-0.055]
B	A	PANEL THICKNESS

- [1] PANEL CUTOUT FOR REAR MOUNTED PIN BLOCK.
- [2] SEAMS OF ALL PINS TO BE ORIENTED TOWARD HOLE X SIDE.
- [3] POLYESTER, BLACK.
- [4] 0.76um [0.000030] MIN GOLD PER MIL-G-45204 FOR A LENGTH OF 6.35 [0.250] MIN FROM MATING END, GOLD FLASH ON REMAINDER, BOTH OVER 1.27um [0.000050] MIN NICKEL PER QQ-N-290.
- [5] 2.54um [0.000100] MIN TIN-LEAD PER MIL-T-10727 OVER 2.54um [0.000100] MIN COPPER PER MIL-C-14550.
- [6] 2.54um [0.000100] MIN TIN PER MIL-T-10727 OVER 2.54um [0.000100] MIN COPPER PER MIL-C-14550.
- [7] OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

PRELIMINARY	[5]	[4]	5.59 [0.220]	211580-6
OBSOLETE	[6]	[4]	3.56 [0.140]	211580-5
	[6]	[4]	19.76 [0.778]	211580-4
	[5]	[4]	3.56 [0.140]	211580-3
	[5]	[4]	19.76 [0.778]	211580-2
	POST FINISH	CONTACT FINISH	G	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT. DIN L.SIPE 09/09/92. CHK R.STONE 10-15-92. APVD -

DIMENSIONS: mm [INCHES]. TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± -, 1 PLC ± -, 2 PLC ± 0.13 [0.005], 3 PLC ± 0.013 [0.0005], 4 PLC ± -, ANGLES ± -.

MATERIAL FINISH WEIGHT -

SIZE: A1. CAGE CODE: 00779. DRAWING NO: 211580. RESTRICTED TO: -

CUSTOMER DRAWING. SCALE: 2:1. SHEET: 1 OF 1. REV: N4.

**STE** TE Connectivity  
CONNECTOR BLOCK FOR PINS WITH FEMALE JACKSCREW THREAD, 62 POSN, METRIMATE