



- THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308
  - MAX WIRE INSUL. TO BE USED WITH THIS PLUG IS .054 DIA.
  - METAL RETENTION CLIPS ARE INCLUDED IN INSERTS
  - PACKAGE MARKED M 24308/4-333F
  - THIS PLUG WILL ACCEPT SIZE 22 PIN CONTACT M 24308/13 OR AMP # 204370
- AMP PART NO. MARKED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS  
 UL/CSA DESIGNATION MARKED IN THIS AREA.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C.C.THOMAS 12-4-87	TE Connectivity
DIMENSIONS: INCHES		CHK F.C.BALLEW III 1-25-88	
		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLG ± - 1 PLG ± - 2 PLG ± - 3 PLG ± .005 4 PLG ± - ANGLES ± 0°30'	APVD F.C.BALLEW III 1-25-88 NAME AMPLIMITE PLUG FOR PIN CONTACTS HI-DENSITY D CONNECTOR SIZE 5, 78 POSN., SERIES 90 WITH FLOAT BUSHINGS
MATERIAL SEE CALLOUTS		FINISH SEE CALLOUTS	PRODUCT SPEC APPLICATION SPEC SIZE CAGE CODE DRAWING NO A1 00779 C=204533 WEIGHT CUSTOMER DRAWING SCALE 4:1 SHEET 1 OF 1 REV S