



RECOMMENDED LAYOUT FOR .062 THICK P.C. BOARD

- 1. PARTS COMPLY WITH TE SOLDERABILITY SPEC. NO. 109-11-3
- 2 CONTACT IS PLATED OVERALL WITH .000050 NICKEL, THEN .000030 GOLD OVER CONTACT LENGTH INDICATED AND TIN PLATED ON SOLDER TAIL END.

Unpublished copy not to be reproduced nor published without written permission of AMP Incorporated

350210-2	NYLON NATURAL	COPPER ALLOY	- GOLD [2]

350210-1 NYLON - NATURAL COPPER ALLOY - PRETIN

ASSEMBLY NO. HSG. MATL & COLOR PIN MATL & FINISH

T2	REVISED PER ECR-13-008342	AV	RP	12NOV 2013
T1	REVISED PER ECO-11-005294	RK	HMR	07APR 11
LTR	REVISION RECORD	DR	CHK	DATE

REQUIRED PER ASSEMBLY				
DESCRIPTION				

DR 4-12-73 <i>9. Edman</i>			MATERIAL AND FINISH SEE TABLE			TE Connectivity		
CHK 4/12/73 <i>Em Peterson</i>			WIRE - RANGE - INSULATION -H- -H-			CLASS .084 DIA. PIN		
DE 4-13-73 <i>Thumler</i>			TOLERANCE EXCEPT AS NOTED +/- .015 +/- 1° 0'			TYPE PIN HEADER		
APP 4-13-73 <i>Thumler</i>			SCALE -H-			LOC CM B NO 350210 REV T2		
			NAME 3 CIRCUIT MATE-N-LOK P.C. BOARD HEADER					

PRINTED IN U.S.A. DIMENSIONS IN INCHES, DO NOT SCALE PRINT. WAS P-72-6198