



DESIGNED FOR USE WITH	.141 SR CABLE
CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.144
CONTACT	.037

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 0	RELEASED	8/2/95	<i>D. Comello</i>

**DESIGN CONTROL REQUIRED**

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 304.1	Temperature Rating -65°C TO +125°C
Frequency Range (GHz) DC to 18	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition D
Volt Rating (VRMS MAX) @ Sea Level 599	Torque 12 - 15 LBS	Shock MIL-STD-202, Method 213, Condition I
VSWR 1.06 + .007 fGHz	Force to Engage and Disengage (In/Lbs MAX) 6.0	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp 200°C
Insertion Loss (dB MAX) .05 √ fGHz	Cable Retention	Moisture Resistance MIL-STD-202, Method 106, Except Step 7b (Vibration) Shall Be Omitted
RF Leakage (dB MIN) -(90 -f(GHz))	Axial Force (Lbs) 60	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Corona, 70,000 Ft (VRMS MIN) 500	Torque (In/Oz) 55	
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 2500	Weight (Grams) TBD	
Contact Resistance (Milliohms MAX)		
Center Contact 1.5		
Outer Contact 2.0		
Cable to Housing 2.0		
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 1500		
I.R.(Megohms MIN) 10,000		

COMPONENT	MATERIAL	FINISH
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	PHOSPHOR BRONZE PER QQ-B-750, GRADE B2	N/A

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	DRAWN BY <i>D. Comello</i> DATE 8/2/95	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	
	CHECKED BY		
FRAC. DEC. ANGLES ± 1/64 ±.005 ± °	APPD BY <i>D. Comello</i> 8/2/95	AMP	
These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE	TITLE OSN STRAIGHT CABLE PLUG DIRECT SOLDER ATTACHMENT	
	408-04915 (30-001)	SIZE B	CODE IDENT NO. 26805
	NO. AP.	1250-1119-00	REV 01 0
		SCALE 3:1	SHEET 1 OF 1