



Convolex Lightweight, flexible, convoluted tubing

Convolex* non heat-shrinkable tubing is manufactured from radiation cross-linked Polyvinylidene fluoride. It forms the basis of a total harnessing system, comprising strain tape, terminations and Tyco Electronics Raychem branded heat-shrinkable moulded parts. Convolex tubing offers good resistance to mechanical damage in the form of abrasion resistance and high crush strength, whilst being extremely light. It has an operating temperature range from -55°C to +150°C and is available in a wide range of sizes.

Key Features:

- Operating temperature range -55°C to +150°C
- Highly flame retarded
- Harnessing conduit with annular convolutions
- Non heat-shrinkable

Convolex

Lightweight, flexible, convoluted tubing

Typical data

Specifications

Tyco Electronics Raychem RK 6048


Ordering Information

The size of tubing chosen must have an internal diameter which is a minimum of 30% larger than the wire bundle to be covered in order to facilitate installation and retain flexibility

Standard length Supplied on spools

Colour Black (-0)

Dimensions



Ordering description	Internal diameter	Outside diameter	Pitch	Wall thickness	Bend radius	Spool quantity	Weight
	A (min) mm	B (max) mm	C (nom) mm	(nom) mm	(nom) mm	m	g/m
Convolex 9/32 - 0	6.0	10.6	3.3	0.33	32.0	60	24
Convolex 3/8 - 0	8.3	13.2	3.3	0.33	38.0	60	31
Convolex 7/16 - 0	10.1	15.2	3.8	0.38	44.0	60	35
Convolex 1/2 - 0	11.4	16.8	3.8	0.38	51.0	30	42
Convolex 5/8 - 0	14.5	19.8	3.8	0.38	64.0	30	58
Convolex 3/4 - 0	17.5	23.9	4.2	0.38	76.0	30	71
Convolex 7/8 - 0	20.5	27.4	4.2	0.38	89.0	30	87
Convolex 1 - 0	23.6	30.5	3.8	0.38	102.0	30	92
Convolex 1 1/4 - 0	30.0	36.6	3.8	0.46	114.0	20	150
Convolex 1 5/8 - 0	39.6	47.0	3.8	0.51	150.0	20	215

*Raychem, Convolex, Tyco Electronics and TE logo are trademarks

All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Tyco Electronics makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Tyco Electronics only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product.

Literature No: 5-1773448-5 October 2007

tycoelectronics.com



Our commitment. Your advantage.