

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	26JUN2015	DW	CW

SCALE 1:2


NOTES:

1. TECHNICAL CHARACTERISTICS:
 HOOD MATERIAL: DIE CAST ALUMINIUM ALLOY
 SURFACE: POWDER COATED, INSIDE AND OUTSIDE
 GREY COATING
 OPERATION TEMPERATURE: -40-+125°C
 DEGREE OF PROTECTION: IP65 (MATED)

注释:

1. 技术参数:
 上壳材料: 铝合金
 表面处理: 粉末涂层, 里外喷漆, 灰色
 工作温度: -40-+125°C
 防护等级: IP65(配合)

T1230160132-100	H16B-TSH-M32 INSIDE AND OUTSIDE COATING	HIGH CONSTRUCTION	M32
T1230160140-100	H16B-TSH-M40 INSIDE AND OUTSIDE COATING		M40
PART NUMBER	DESCRIPTION	TYPE	IG1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 26JUN2015 David Wang	 TE Connectivity	
DIMENSIONS: mm		CHK 26JUN2015 Chris Wang		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 26JUN2015 Xiang Xu	PRODUCT SPEC 108-137013	
0 PLC ±-		APPLICATION SPEC 114-137013		SIZE A3
1 PLC ±-		WEIGHT -		CAGE CODE 00779
2 PLC ±-		Customer Drawing		DRAWING NO T12X01601XXX00
3 PLC ±-		SCALE 1:1		RESTRICTED TO -
4 PLC ±-		SHEET 1 OF 1		REV A
ANGLES ±-				
FINISH -				
MATERIAL -				

1470-19 (3/13)