

REV. 0

DCO 141524

|              |                 |                            |
|--------------|-----------------|----------------------------|
| COIL: @ 25°C | RESISTANCE      | 1560 OHMS ±10%             |
|              | NOMINAL VOLTAGE | 26.5 VDC                   |
|              | MUST OPERATE    | 14.2 VDC                   |
|              | MUST RELEASE    | 8.0 VDC MAX, 1.37 VDC MIN. |


ENVIRONMENT:

|             |     |        |      |              |    |     |
|-------------|-----|--------|------|--------------|----|-----|
| VIBRATION   | 10  | CPS TO | 3000 | CPS @        | 30 | g's |
| SHOCK       | 75  | g's    | 6    | MS. DURATION |    |     |
| TEMPERATURE | -65 | °C TO  | +125 | °C           |    |     |

NOTES:

|                |            |
|----------------|------------|
| OPERATE TIME   | 2 MS MAX   |
| RELEASE TIME   | 1.5 MS MAX |
| CONTACT BOUNCE | 1.5 MS MAX |

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: LOW LEVEL TO  
1A 28 VDC RESISTIVE 100,000  
OPERATIONS

DR. B.D. 11/16/99 *CK Ferry* 11/16/99



PRMAC-26XS

CUST. C.I.I.  
 CUST. NO. STANDARD REV.

'PRMA' RELAY