


REV. 0
DCO 143304

| | |
|-----------------|---------------------------|
| COIL: @ 25°C | |
| RESISTANCE | 3300 OHMS ±10% |
| NOMINAL VOLTAGE | 26.5 VDC |
| MUST OPERATE | 14.0 VDC |
| MUST RELEASE | 8.0 VDC MAX, 1.4 VDC MIN. |

| | |
|--------------|-----------------------------|
| ENVIRONMENT: | |
| VIBRATION | 10 CPS TO 3000 CPS @ 30 g's |
| SHOCK | 75 g's 6 MS. DURATION |
| TEMPERATURE | -65 °C TO +125 °C |

| | |
|--------|--|
| NOTES: | OPERATE TIME 4.0 MS MAX. |
| | RELEASE TIME 7.5 MS MAX. |
| | CONTACT STABILIZATION TIME 2.0 MS MAX. |

CUSTOMER DATA SHEET



TERMINAL VIEW

| | |
|-----------------|-------------------------------------|
| CONTACT RATING: | LOW LEVEL TO 1A |
| | 28 VDC RESISTIVE 100,000 OPERATIONS |

DR. ASB 11/13/01 *[Signature]* 11/13/01

CII Technologies
advanced control electronic solutions

CUST. OPL
CUST. NO. M39016/16-036M REV.

"JMSD" RELAY

JMSCD-26XM