



- △ ZINC.
- △ STAINLESS STEEL.
- 3. TO ASSEMBLE JACKSCREW REFER TO INSTRUCTION SHEET #1189.
- △ HOLE CENTRALLY LOCATED WITHIN ±0.07 [.003] OF THE 5.54 [.218] DIA AND THE 2.77/2.84 [.109/.112] DIA CENTER LINES.
- △ CHROMATE CONVERSION, CLEAR WITH HEXAVALENT CHROMATE.
- △ CHROMATE CONVERSION, CLEAR W/O HEXAVALENT CHROMATE.

OBSELETE	△	2.87 [.113]	201910-5
	-	2.11 [.083]	201910-3
	△	2.87 [.113]	201910-1
NOTES	A		PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K. FOLTZ 05/26/94	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm [INCHES]		CHK R. STONE 06/16/94	APVD	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME JACKSCREW KIT, UNASSEMBLED, FEMALE, M SERIES		
0 PLC ± -		PRODUCT SPEC		
1 PLC ± -		APPLICATION SPEC		
2 PLC ± 0.13 [.005]		SIZE A1		
3 PLC ± -		CAGE CODE 00779		
4 PLC ± -		DRAWING NO 201910		
ANGLES ± -		RESTRICTED TO		
MATERIAL JACKSCREW BODY: △ JACKSCREW TIP: △ JACKSCREW PIN: △		FINISH JACKSCREW BODY: SEE NOTES JACKSCREW PIN: PASSIVATE		WEIGHT -
CUSTOMER DRAWING		SCALE 4:1		SHEET 1 OF 1
		REV L1		